# CHEMICAL ANALYSES.

## Α

FIRST, SECOND, AND THIRD CHEMICAL REPORTS, AND CHEMICAL ANALYSES OF THE HEMP AND BUCKWHEAT PLANTS.

BY ROBERT PETER, M. D., ETC., ETC., CHEMIST TO THE SURVEY, AND JOHN H. TALBOTT AND A. M. PETER, ASSISTANTS.

STEREOTYPED FOR THE SURVEY
BY MAJOR, JOHNSTON & BARBETT.

YEOMAN PRESS, FRANKFORT, KENTUCKY.
1884.

This page in the original text is blank.

## CONTENTS.

																						1	PAGE.
FIRST CHEMICAL REPORT .					•			•	•	•	•	•	•	•	•	•	•		•	•	٠	•	1
SECOND CHEMICAL REPORT			•					•	•	•		•		•	•	•				•	٠	٠	181
THIRD CHEMICAL REPORT.		•			•					•				•					è				347
CHEMICAL EXAMINATION OF	т	н	E	н	E	ME	,	AN	ID	F	TT	CI	cτ	VI	11	C.A	т	P	T./	AN	T	S	430

This page in the original text is blank.

### PREFACE TO SECOND EDITION (NEW SERIES).

It being necessary to publish a new edition of the Reports of the Geological Survey, it is thought proper to change the arrangement of the reports in the several volumes. This is advisable in order to bring together in one volume the several reports relating to a given subject or locality. In the first edition (second series) the volumes were made up of reports, regardless of subjects treated, and in order to learn all that may be published of a locality, the reader must examine several volumes. For instance, the reports on the iron ores and the iron manufacture of Greenup, Carter, Boyd, and Lawrence counties is in volume 1, and the Report on the Geology of the above named counties is in volume 2. The Chemical Reports and the reports on the Timbers are scattered through four volumes. This arrangement of reports could not have been avoided in the early history of the Survey without a delay in the publication of the volumes. It is thought that the arrangement in this edition will more fully meet the wants of the public, and will render the reports more valuable.

The first volumes of this edition will comprise the following: Chemical Analyses, Reports on the Eastern Coal Field; Reports on the Western Coal Field; Reports on Timbers. Other volumes will be published from time to time, preserving the same order of grouping reports. Some of the preliminary reports contained in the first edition have been omitted, in order that there may be no duplication when the final reports are published. I am of the opinion that enough preliminary or reconnoissance work has been done by the Survey, and the work will be directed with a view of securing (so far as the means will permit) complete reports on the geology, soils, timbers, etc., of the various regions

IV PREFACE.

studied. As the stereotyped plates of the omitted preliminary reports are preserved, new editions may be ordered should there be a demand for them. A change has also been made in the size of the volume by decreasing the size of the margin, which, it is thought, will make the volume a more convenient size, both for library use and for sending through the mails.

JOHN R. PROCTER, State Geologist.

## GEOLOGICAL SURVEY OF KENTUCKY.

N. S. SHALER, DIRECTOR.

## CHEMICAL REPORT

OF THE

SOILS, MARLS, CLAYS, ORES, COALS, IRON FUR NACE PRODUCTS, MINERAL WATERS, &c., &c., of Kentucky,

BY ROBERT PETER, M. D., &c., &c., CHEMIST TO THE KENTUCKY GEOLOGICAL SURVEY.

ASSISTED BY

JOHN H. TALBUTT, S. B., CHEMICAL ASSISTANT.

THE FIRST CHEMICAL REPORT IN THE NEW SERIES AND THE FIFTH SINCE THE BEGINNING OF THE SURVEY.

This page in the original text is blank.

### INTRODUCTORY LETTER.

CHEMICAL LABORATORY OF THE
KENTUCKY STATE GEOLOGICAL SURVEY,
LEXINGTON, Kv., April 19th, 1875.

Professor N. S. SHALER, Chief Geologist, &c.:

DEAR SIR: I have the pleasure herewith to report the results of the chemical work performed in this laboratory, for the State Geological Survey, since September, 1873, to nearly the present date. So much could not have been effected but for the able and efficient assistance of Mr. John H. Talbutt, who has given his constant attention to this labor.

Very respectfully,

ROBERT PETER.

3

### CHEMICAL REPORT

OF THE

## SOILS, MARLS, CLAYS, ORES, COALS, IRON FUR-NACE PRODUCTS, MINERAL WATERS, &c., &c., OF KENTUCKY.

By ROBERT PETER, M. D., &c., &c.

In the eighty-six soil analyses, which are appended, only a portion of ten counties of the State is represented, and the greater number of these soils are not to be classed amongst our most fertile. The limits of the range of variation of their several constituents is shown in the following table, viz:

	Pr. ct.	No.		County.		Pr. ct.	No.	County.
Organic and volatile matters vary from		in 1300	of	Boyd	to	1.815	in 1398	of Carter.
oxides vary from	15.763	in 1 396	of	Carter	to	2.740	in 1571	of Hardin.
Lime carbonate varies from				Campbell	to			of Hardin.
Magnesia varies from				Campbell	to	, , ,		of Boyd.
Phosphoric acid varies from			1	Fayette	to		f in 1396	of Carter. of Hardin.
Potash varies from	.662	in 1 396	of	Carter	to	.062	J in 1325	of Campbell of Campbell
Soda varies from	. 286	in 1407	of	Carter	to	trace.		of Hardin.
from	74.840	in 1396	of	Carter	to	92.455	in 1634	of Ohio.
from	2.650	in 1558	of	Hardin	to	.225	in 1572	of Hardin.
Water expelled at 212° F. varies		33						
from	5.075	in 1329	of	Campbell	to	.800	in 1571	of Hardin.

The extremes may represent very rich and very poor soils; but not the general character of the soils of the counties named. The method of analyses of the soils does not vary much from that described in volume III of the Kentucky Geological Reports. The principal object was, as there stated, to obtain comparative results, which would enable the scientific agriculturist to form an opinion as to the chemical constitution of our soils in their relation to husbandry; without attempting to perform the almost hopeless task of giving all the minuter constituents of each, or of presenting all those physical conditions which exert so great an influence on their practical fertility. To this end the several soils were treated as nearly alike as possible: air-dried together, digested for an equal time at nearly the same temperature in acid of a uniform strength, &c., &c. The specific gravity of the chlorohydric acid used being about 1.10.

The process of digestion in water, containing carbonic acid, was not employed in all, because of the press of work in the laboratory, mainly. There can be no doubt, however, that, used with proper care, this process will indicate the relative proportion of soluble plant food in the soil at the time. As this may very well vary, under different physical atmospheric conditions, it was not considered of essential value in the comparative analyses.

The well-known fact that various physical conditions exert a powerful influence on the productiveness of soils which have a similar chemical composition, has, in recent times, singularly perverted the minds of chemists, and consequently of agriculturists, in relation to the value of soil analyses. Because the chemical conditions of a soil are not the only ones necessary to productiveness, they have, by a perverted logic, jumped to the conclusion that these conditions are of no consequence whatever.

But if these chemical conditions are indispensable to the fertility of the soil, how much injury has been done in recent years to the scientific study of the soil and of agriculture, by the great outcry which has been raised against this kind of investigation! The comparative chemical examination of the soils of a State or country can only be made under the patronage of the government. Individual efforts are inadequate to effect it; nor could they, if adequate, so economically conduct it. The writer believes that the geological survey of any region should always include this study of the soils; yet very little has been done in this direction in all the recent State surveys, and a valuable opportunity has been lost, which in many instances cannot recur, of studying the chemical conditions of the virgin soil of various parts of our country.

Chemists are naturally somewhat averse to soil analysis; it requires so much time and labor, so much care must be taken to secure accuracy, and there is so little variety in the work, and so small an appreciation of its value and significance amongst the people when done, that they gladly avoid it. But, in the course of time, most of them who are not too much prejudiced against the teachings of experience, arrive at the same conclusion with Prof. Aug. Voelcker, of the English Royal Agricultural College: "There was a time when I thought with many other young chemists, that soil analyses would do every thing for the farmer; three or four years of further experience and hard study rather inclined me to side with those men who consider that they are of no practical utility whatever; and now, after eighteen years of continued occupation with chemico-agricultural pursuits, and, I trust, with more matured judgment, I have come to the conclusion that there is hardly any subject so full of practical interest to the farmer as that of the chemistry of soils. The longer and more minutely soil investigations are carried on by competent men, the greater. I am convinced, will be their practical utility."-Jour. of Roy. Agr. Soc. of Eng., 1865.

Even Prof. S. W. Johnson, whose somewhat harsh criticism, in 1861, of some of the former labors in this field of the writer, seemed to sound the key-note of the clamor against this kind of study in this country, has so far yielded his opposition as to give us in his valuable work, "How Crops Feed," 1870, the comparative analyses of several soils, and to point out the significance of their chemical composition. But he is careful to caution the reader, page 368, that although the analysis may

show the amount of the mineral fertilizers in a soil, it cannot tell how much of them "is at the disposal of the present crop;" and on page 271: "These facts show how very far chemical analysis, in its present state, is from being able to say definitely what any given soil can supply to crops, although we owe nearly all our precise knowledge of vegetable nutrition directly or indirectly to this art."

He might very truly have added, that we should not be able to say that a suitable *chemical* composition of a soil was not the only condition necessary to its fertility, unless we had thoroughly studied that condition. It is only by means of chemical analyses that we find out the equally indispensable nature of the physical conditions. He cannot fail to admit that it is impossible to make progress in our knowledge of the soil and its actions and conditions without a thorough study of its chemical characters.

In accordance with this outcry against this sort of investigation the difficulties of obtaining good samples for analyses has been exaggerated. In a country like that of most of this State, where there is comparatively but little quarternary or transported material constituting the soil, and especially before its character has been much altered by a dense population, there is little difficulty, with the use of necessary precautions, in obtaining representative samples of large areas similar in character and position. In many large districts in our State the soil has been formed in place by the disintegration of the rocks. In other parts, where surface action has been greater, more judgment and care must be exerted in the collection of the soils; but in no part of the State, probably, is so great local variety to be seen in the soils as frequently may be observed in the northeastern States, where the transporting action of water and of ice, in former epochs, has produced a high degree of local irregularity in the nature of the surface deposits.

In the collection of the samples of our Kentucky soils the causes of local and accidental differences of composition were, as much as possible, avoided.

Because of the very small proportion of the essential ingredients of the soil, which are carried off in crops, as compared with the whole amount of the earth, taken to the depth through which the roots of plants absorb nourishment, it has been denied that it is possible by chemical analysis to show their diminution in the old field soil, as compared with the virgin soil. Indeed it has been *logically* demonstrated to be impossible. But, it should be recollected that when, by the acid digestion, we separate these essential soluble ingredients from the greater mass of the soil, left as *sand and insoluble silicates*, which amount to from about seventy-five to ninety-two per cent. of the whole, the probabilities of error in the determination of these minuter ingredients must not be calculated into the whole weight of the soil, but into that smaller part which we have thus extracted from it.

Logic apart, the fact still remains, that in one hundred and forty-nine duplicate analyses, made by the writer for the Kentucky, Arkansas, and Indiana Surveys, in which the chemical composition of the virgin soil was compared, under similar conditions of treatment, with soil of a neighboring old field in the same locality, one hundred and twenty-two out of the one hundred and forty-nine showed a marked diminution of most of the essential ingredients of the soil in that of the old field as compared with the virgin soil. This certainly is not an accidental result.

In the soil analyses at present reported the results are not so striking in this relation. Partly because the samples had not, in several cases, been collected with special reference to this investigation, and partly because of greater local variations of the soil in the regions in which they were obtained.

In calculating the probable amount of exhaustion of the essential soil ingredients, it should be recollected that as much, and sometimes more, may be alienated from the soil by the solvent action of the atmospheric agents, while the surface is much exposed in the cultivation of hoed crops, than is absorbed and removed by the products. Hence the exhaustion of the soil is much more rapid under these cir-

cumstances than is generally allowed. In other words, the exhaustion of the soil when under cultivation in hoed or plowed crops, during which time a large portion of its surface is kept bare of vegetation and subjected to the leaching action of rains, is much greater than can be accounted for by the amount of the essential ingredients which are taken from it in its products.

In several instances, in the analyses of the soils described above, the "sand and insoluble silicates," left after digestion, for ten days in the acid, were analyzed by the admirable process of Professor J. Lawrence Smith, for the determination of the amount of fixed alkalies held in the form of insoluble silicates. As will be seen, in the detailed report and in the tables, the quantity of potash and soda thus held in the soil in the samples in question are, in most cases, considerable, ranging from 0.485 to 2.731 per cent. of potash to the whole soil, and 0.165 to 1.306 per cent. of soda.

It is evident that, although at *present insoluble*, and hence unavailable for plant nourishment, these alkalies are doubtless gradually released and brought into a soluble form by weathering and under the influence of the products of vegetable decay, so that they tend to prolong the fertility of the soil.

The seventeen *limestone* and *lime* analyses, of specimens from nine counties only, represent but a small part of our various lime rocks. But even these exhibit their great industrial value, including, as they do, limestones useful for the fluxing of our iron ores, as well as for purposes of construction in the form of building stone or cement, while some of them would be valuable as fertilizers on the land. The so-called lithographic stone of Barren county and of other corresponding localities may, for some purposes, with well-selected samples, replace the more costly foreign stone.\*

The eighty-two iron ores which have been analyzed are from eleven counties, principally of the northeastern portion of the

<sup>\*</sup>Note.-I have found it impossible to use this stone for crayon or transfer work.

State. Sixty-four of these are limonite ores; twenty-seven are clay ironstones or carbonate ores; and only one, to be found probably only in limited quantity in Lawrence county (see No. 1594), is of the red hematite variety.

The proportion of metallic iron, in the limonite ores examined, varies from 19.344 per cent. to 57.148 per cent. In the carbonate ores analysed the per centage of metallic iron ranges from 10.960 per cent. in what may be termed only a ferruginous limestone, up to 40.465 per cent.

Of the one hundred and ten specimens of coal, &c., which were examined by proximate analysis, eighty-nine were from eleven counties in Kentucky; of which five counties, viz: Boyd, Carter, Greenup, Lawrence, and Menifee, are in our northeastern coal field; and six, viz: Butler, Edmonson, Grayson, Hopkins, Muhlenburg, and Ohio counties, are in the southwestern coal field. All these coals are of the splint, dry coal, or semi-cannel coal variety; cleaving generally into thin layers, which have more or less fibrous coal between them. Although some of them make a good coke, they do not generally soften or swell much when heated or burnt, and hence, when they do not contain an unusual quantity of sulphur, they can be used, without preliminary coking, for the smelting of iron. Some of these coals, however, are quite sulphurous, and some contain a large proportion of ash,† but the better samples compare favorably with the best coals of the neighboring States.

For the purpose of this comparison seven of the best coals of the State of Ohio, two of the best of those of Illinois, and four of the celebrated "block coals" of Indiana, used there for iron smelting, &c., were submitted to similar processes of analysis with our Kentucky coals. We give the general comparative results in the following tables:

<sup>†</sup> In some cases, as the samples for analysis were taken from new and imperfect openings, it is more than probable the coals will be found to be better than is represented in the analyses given.

AVERAGE COMPOSITION OF THE COALS FROM THE NORTHEASTERN KEN-TUCKY COAL FIELD.

Counties.	Number of samples analyzed.	Specific gravity.	Volatile combustible matters.		Per cent. of ash.	Per cent. of sulphur.
Boyd	13	1.337	33.43	54.35	*8.46	†2.292
Carter	333233	1.331	33.39	53.45	8.17	‡1.886
Greenup	14	1.375	34.50	52.20	9·37 6.86	3.165
Lawrence	6	1.326	36.27	53.85	6.86	1.285
Menisee	2	1.319	33.55	53.42	10.36	2.544
General average	51	1.3376	34.23	53.45	8.62	2.234

#### AVERAGE COMPOSITION IN THE SOUTHWESTERN COAL FIELD.

Counties.	Number analyzed.	Specific gravity.	Volatile combustible matters.	Fixed carbon.	Per cent, of ash.	Per cent. of sulphur.
Butler	1 8	1.378	30.66	54.94	11.00	2.544
Edmonson	8	1.360	34.01	52.34 49.78	2 14.38	3.312 2.083
Hopkins	2	1.385	32.95	52.55	11.20	5.019
Muhlenburg	11	1.312	36.42	53.26		2.949
Ohio	3	1.362	34.90	53.77	8.16	3.103
General average	33	1.3636	33.70	52.77	10.34	3.166

AVERAGE COMPOSITION OF THE SELECTED COALS FROM NEIGHBORING STATES.

STATES.	Number analyzed.	Specific gravity.	Volatile combustible matters.			Per cent. of sulphur.
Ohio	7	1.327	34.51	55.17	6.43	1.494
Illinois	2	1.310	31.95	59.06	5.96	1.924
Indiana	3	1.313	35.93	54.24	7.23	1.946
General average	12	1.317	34.13	56.12	6.54	1.768

This comparison is more or less imperfect, because the samples, which were too few in number to make it complete, were not averaged with special reference to it. Yet it measurably corroborates opinions held by geologists and others in regard

<sup>By leaving out the exceptional ash of No. 1291, the average is = 7.94.
Without No. 1291 this average would be = 2.036.
This is the average of fifteen of the coals only.
By leaving out the exceptional ash of No. 1454, the average would be = 12.21.</sup> 

to our two coal fields. For instance, it will be seen in the general averages that the coals of the southwestern field have more ash and sulphur, and a higher specific gravity, than those of the northeastern, and that the relative proportions of the combustible matters, volatile or fixed, are less in the former The differences, however, are not very remarkable.

In each of these particulars the coals from our neighboring States of Ohio, Illinois, and Indiana, show less difference than might have been expected, in view of the fact that they had been collected from some of the most celebrated coal mines, as representing the *best coals* of those States. The following tables illustrate this:

TABLE OF THE EXTREMES OF COMPOSITION OF THE COALS.

Counties.	Volatile combus- tible matters. From	Fixed carbon. From	Ashes. From	Sulphur. From
Boyd	29.70 to 36.70 27.22 to 36.26	46.86 to 57.90 44.64 to 58.88	5.10 to 14.74 3.20 to 12.10	1.285 to 5.361 .724 to 3.483
Greenup	31.66 to 37.70	47.00 to 56.70	5.40 to 13.00	.746 to 5.934
Lawrence	33.90 to 39.00	47.84 to 57.80	1.80 to 13.70	.736 to 3.785
Menisee	33.06 to 34.04	50.24 to 56.60	7.40 to 13.06	.997 to 4.092
Greatest extremes	27.22 to 39.00	44.64 to 58.88	1.80 to 14.74	.724 to 5.361
Butler	30.66		11.00	2.544
Edmonson	32.00 to 39.00	45.46 to 54.26	6.94 to 14.34	1.059 to 8.685
Grayson	25.86 to 35.80	40.14 to 55.52	7.50 to 29.60	.777 to 3.565
Hopkins	30.00 to 35.90	51.10 to 54.00	6.90 to 15.50	2.759 to 7.280
Muhlenburg	30.60 to 43.08	49.80 to 58.80	3.72 to 11.80	.640 to 4.032
Ohio	33.50 to 36.20	52.20 to 55.10	7.10 to 9.00	2.837 to 3.332
Greatest extremes	25.86 to 43.08	40.14 to 58.80	3.72 to 29.60	.640 to 8.685
State of Ohio	29.68 to 36.68	54.16 to 57.06	4.20 to 8.72	.756 to 2.247
State of Illinois	31.86 to 32.04	55.64 to 59.54	5.16 to 6.76	1.376 to 2.472
State of Indiana	35.10 to 36.38	53.50 to 53.58	5.28 to 9.00	1.664 to 2.373
Greatest extremes	29.68 to 36.38	53.50 to 59.54	4.20 to 9.000	.756 to 2.472

TABLE OF THE COMPOSITION OF ELEVEN SELECTED KENTUCKY COALS FROM SEVERAL COUNTIES.

Counties.	Number.	Specific gravity.	Volatile combustible matters.		Per cent. of ash.	Per cent. of sulphur.
Boyd	1286	1.308	33.30	57.60	5.80	2.480
Boyd	1289	1.320	34.50	55.40	5.10	1.285
Carter	1346	1.288	34.36	54.60	4.40	.724
Carter	1347	1.290	27.22		7.50	.973
Carter	1353	1.274	34.50	58.50	3.20	2.164
Edmonson	1418	1.336	35.14	54.26	6.94	2.706
Greenup	1492	1.292	33.90	56.70	6.20	.746
Greenup	1493	1.289	34.96	55.54	5.40	1.590
Hopkins	1579	1.322	35.90	54.00	6.90	2.759
Lawrence	1589	1.281	35.30	57.80	1.80	.736
Lawrence	1593	1.284	39.00	54.76	3.74	1.066
General average		1.298	34.36	56.18	5.18	1.566

To show the great importance of collecting true and faithful average samples of the coal beds, for the purpose of analysis, two picked cabinet specimens were taken and analyzed, to-wit:

No.1280 (b). Coal No. 7, from Turkey-pen Hollow, Boyd county. No. 1348 (b). Coal No. 7, Pritchard's coal, Mt. Savage Furnace, Carter county.

The comparative results of the analyses are as follows—thoroughly air-dried:

	A = 1	Ave'ge sample.  No. 1280 (a).	8	170 170
Specific gravity	Not determ'd.	1.358	Not determ'd.	1.435
Hygroscopic moisture Volatile combustible matters Coke	4.70 34.30 61.00	3.40 32.30 64.30	4.50 37.10 58.40	5.40 32.70 61.90
Total volatile matters	39.00 59.04 1.96	35.70 55.40 8.90	41.60 56.40 2.00	38.10 52.52 9.38
Total	100.00	100.00	100.00	100.00
Per centage of sulphur	0.983	1.230	0.571	2.356

As the value of a coal bed bears a very near relation to that of its average product, it is easily to be understood that the analysis of a *selected* sample may be of very little utility. On the other hand, the selection of a true average sample of the bed may often be a task of considerable difficulty.

The determination of the proportion of *sulphur* in coals has been much neglected in this country; and where it has been done the method generally used has been to oxidate the powdered coal in strong nitric or nitro-hydrochloric acid. This mode of analysis is not so perfect as fusion with a mixture of nitre, carbonate of soda, and salt, &c., which always, when properly managed, brings all the sulphur into the form of soluble sulphate, in whatever state it may have existed in the coal. This exhaustive mode was employed in all our estimations of this substance, and hence the quantities obtained may seem greater than are shown to exist in similar coals which have been treated with the acids.

As has now been extensively demonstrated, the sulphur in coals is rarely all combined with iron as sulphide or bi-sulphide. Some frequently exists in a free or uncombined condition, as is shown in an analysis described in the following pages. Some of it is frequently in the form of lime sulphate.

When it is recollected that vegetable matters, decomposing in a solution of sulphates of lime, magnesia, iron, &c., reduce these salts to sulphides, with the production of hydrogen sulphide in the case of the earthy salts, and when we reflect that this gaseous compound, HS, is decomposed, with the deposition of free sulphur, on contact with the air, we can easily understand how most of our coals must contain not only pyrites but free sulphur.

In the thirty-four marls, marly shales, sands, and silicious concretions, which have been analyzed, we find a general prevalence of lime, fixed alkalies, phosphoric acid, sulphuric acid, &c. Some of the marls and shales contain these in such considerable proportions as to make them locally useful for the amelioration of poor sandy land. Some of these find an application as mineral paint, for which they are adapted by their

agreeable tint and other properties. Some of the more silicious could be used in the manufacture of glass, as well as for other purposes; some of post-tertiary silicious clays, or soft sandstones, might be made into bricks for scouring purposes, &c., while others, which contain but little lime, magnesia, oxide of iron or alkalies, would prove quite refractory in the fire.

But the fire-clays and plastic clays of the coal fields, of which the analyses of sixteen are appended, are especially deserving attention; and from their abundance, superior quality, and vicinity to fuel, should form the basis of extensive industries. Amongst them may be found some of the best of fire-clays, as well as some well-fitted to the manufacture of pottery ware of various kinds, including the better sorts of delf, stone china, or queensware. Skill, capital, and enterprise are all that are needed, on these somewhat neglected deposits, to make them of very great value to individuals as well as to the public. Only the want of these essentials causes us to pay a heavy tax to foreign nations for our pottery ware, when the materials for the manufacture lie measurably neglected at home. simply the history repeated of the importation of bricks from Holland to build houses in Albany, and the packing of English bricks, on the backs of horses, over the Alleghenies, to construct the barracks at old Fort Duquesne on the Ohio.

The nineteen samples of pig iron which have been analyzed are mostly of the kind known as foundry iron. On reference to the general table of their composition, it will be seen that they present considerable variety in this respect; as for example:

The per centage of	iron ranges	between	•					1.0		*1	85.455 to	95.840
	carbon										2.040 to	4.400
	phosphorus										0.123 to	1.029
	sulphur										a trace to	0.150
The specific gravity	, porting • 100 to 100	"									6.406 to	7.782

Of the numerous *mineral waters* of our State the analyses of twenty-one are given in the present report, mostly from one locality.

#### BATH COUNTY.

No. 1269—Limonite Iron Ore. "From Block-house ore bank, one and a half miles from the Old Slate Furnace, Bath county. Bed ten to twelve feet thick; on the Clinton Group. Collected by Philip N. Moore."

Ore generally dense and dark-colored, with some dark ochreous ore. Structure cellular and oölitic.

	-	CO	MF	OS	11	10	N,	, 1	OR	IEL	AT 212° F.
Iron, peroxide	8 3										76.077 = 53.254 per cent. of iron.
Alumina	8 3	3 3		. :							2.592
Manganese, brown oxide	8		. 3								.430
Lime, carbonate											.130
Magnesia											. 281
Sulphuric acid											.030 = 0.011 per cent. of sulphur.
Phosphoric acid											.731 = .319 per cent. of phosphorus.
Water, expelled at red heat.	o •				.0010	•	•				12.300
Silica and insoluble silicates									•	•	8.180 = 6.160 per cent, of silica.
											100.751

The phosphoric acid determination was made by Chancel's process, viz: by means of acid nitrate of bismuth solution, after the separation of the iron oxide, and is believed to be nearly correct. The iron ore in the Clinton Group, especially the "dye-stone ore," is usually quite phosphatic. This does not prevent it from being quite valuable for the production of iron for many purposes, although it may not be made to yield the higher grades of bar iron or steel.

#### BARREN COUNTY.

No. 1421—Limestone. "Oilitic Limestone. Upper layers of upper sub-carboniferous limestone. Glasgow Junction, Barren county. Collected by Prof. N. S. Shaler."

A compact, nearly white, fine oölitic limestone, with a ferruginous stain on the exposed surfaces probably derived from the superincumbent soil.

No. 1422—Limestone (compact). "Upper Sub-carboniferous Limestone. Glasgow Junction. Collected by N. S. Shaler."

A light-grey, fine granular, or compact limestone, which might be a good lithographic stone but for the presence of some imbedded fossils and minute specks of iron peroxide. No. 1423—LIMESTONE. Labeled "Lithographic Stone; below the building stone. Upper sub-carboniferous limestone. Glasgow Junction. Collected by Prof. N. S. Shaler."

A light-grey, compact, or very fine granular rock, which might be a perfect lithographic stone but for the minute imbedded fossils and the small occasional specks of iron peroxide, &c., which it contains. Some layers, however, are reported measurably free from these imperfections, and found to be good enough, on actual trial, for some ordinary lithographic purposes.

COMPOSITION OF THESE BARREN COUNTY LIMESTONES, DRIED AT 212° F.

															No. 1421.	No. 1422.	No. 1423.
Specific gravity			•0								×	×			2.678	2.721	2.689
Lime, carbonate					•										98.050	77.550	82.960
Magnesia, carbonate															.363	13.214	7.655
Alumina, and iron and	l m	anı	gai	ne	se	ox	id	es							.511	2.680	2.680
Phosphoric acid			•												 .051	.051	.115
Sulphuric acid															. 260	.192	.260
Potash													••		.115	.154	.135
Soda			•												. 327	. 188	. 156
Silica and insoluble si	lica	tes	•	•	•	•	٠	٠	٠	•	-	•	٠	•	1.060	6.060	6.160
Total		•				ï	:		•	ĸ	٠				100.737	100.189	100.121
Per centage of lime															50.428	43.428	46.457
Per centage of phospi	horu	ıs.					j.		•	•					.022	.022	.050
Per centage of sulphu	r .		-		-	100									. 104	.077	. 104

No. 1421 would yield a very pure white lime.

#### BOYD COUNTY.

No. 1270—CLAY IRON-STONE, &c. Labeled "Grey Limestone Ore. J. P. Jones' drift, near Ashland. Average sample selected by P. N. Moore."

A mixed sample, with oölitic carbonate of iron, dark grains united with a whitish cement, portions of compact carbonate, and of *limonite* ore.

No. 1271—CLAY IRON-STONE. Labeled "Wilson Creek Blue Block Ore. Average sample, taken from Star Furnace stock pile, by P. N. Moore."

A fine-granular ore of various shades of dark-grey, with some slight incrustations of limonite. Not adhering to the tongue.

No. 1272—CLAY IRON-STONE. Labeled "So-called Limestone Ore, from Williams' Creek. Star Furnace stock pile. Averaged by P. N. Moore."

A granular and oölitic proto-carbonate of iron (containing much carbonate of lime). Oölitic grains nearly black, in a whitish cement.

SUMMARY OF THE COMPOSITION OF THESE BOYD COUNTY CLAY IRON-STONES, DRIED AT 212° F.

	-	_	_	-	-		-	-	-		-	7.5				
														No. 1270.	No. 1271.	No. 1272.
Iron, carbonate													_	32.285	66.854	19.802
Iron, peroxide														12.784	.276	21.433
Alumina (by difference)														11.968	4.260	1.193
Lime, carbonate														21.125	2.460	30.205
Magnesia, carbonate														.691	4.086	a trace.
Manganese, carbonate														.465	.572	.240
Phosphoric acid (anhydr.) .														- 377	.709	.257
Sulphuric acid (anhydr.)													8	. 267	.885	.157
Silica and insoluble silicates														19.730	18.360	23.080
Water and loss					•	•		•	•	•		•	•	. 308	1.538	3.633
Total	•	٠	•	*:	•	•			٠	٠	•		æ	100.000	100.000	100.000
Per centage of iron	•	•• ••		•	•	٠	•	•		•		•	•	24.591	32.466	23.109
Per centage of phosphorus.		•	•	•	·	•		٠	•	•	•			. 164	. 308	.112
Per centage of sulphur			•	•	•	•	•	•	•				•	. 107	.354	.063
Per centage of silica			•	•					•	_			-		15.500	18.960

Of these ores, No. 1271 would be the best, as it is the richest; but its considerable proportions of phosphorus and sulphur will somewhat injure the toughness of the iron it

yields. No. 1272 is not so objectionable in this respect. This ore as well as No. 1270, containing a large proportion of lime, although comparatively poor in iron, may yet be profitably smelted, especially in mixture with richer ores. They will obviously require less fluxing material than the other ores.

No. 1273—LIMONITE. Labeled "Slate Ore. Head of Cane Creek, on the road to Star Furnace, Boyd county. Average sample selected by P. N. Moore."

In irregular curved layers, varying in hardness and color from yellowish-brown to blackish-brown; frequently inclosing soft ochreous nodules.

No. 1274—LIMONITE. Labeled "Yellow Kidney Ore, sampled from a number of places by P. N. Moore. Star Furnace property."

Irregular curved layers of dark-colored limonite (brown hæmatite), incrusted by and inclosing soft ochreous ore.

No. 1275—LIMONITE. Labeled "Limestone Ore;" average sample selected by P. N. Moore. Bellefont Furnace.

Ore varying from brownish-yellow to dark brown (mostly dark brown), with some proto-carbonate of iron, ferruginous limestone, and a little calc. spar intermixed.

No. 1276—LIMONITE. Labeled "Yellow Kidney Ore;" average sample selected by P. N. Moore. Buena Vista Furnace.

Irregular curved layers of limonite, varying from soft, brownish-yellow to dense, dark brown ore.

No. 1277—LIMONITE, &c. Labeled "Yellow Kidney Ore, or Kidney Ore below the No. 7 Coal." Straight Creek, Buena Vista Furnace. Average sample collected by P. N. Moore.

Limonite layers of various depth of color, with some fine granular carbonate of iron and thin veins of calc. spar. No. 1278—LIMONITE. Labeled "Black Kidney Ore." Average sample, from Stock Branch Hollow, just south of Star Furnace. Collected by P. N. Moore.

In irregular curved layers, generally of a dark purplishbrown color, with some soft ochreous nuclei and layers.

SUMMARY OF THE COMPOSITION OF THESE BOYD COUNTY LIMONITES, DRIED AT 212° F.

	No. 1273.	No. 1274.	No. 1275.	No. 1276.	No. 1277.	No. 1278.
Iron, peroxide	53.653	58.960	51.802	61.344	56.022	54.055
Iron, carbonate			10.594		8.821	
Alumina (by difference)	4.324	7.284	4.523	4.236	7.194	4.919
Manganese, brown oxide	. 368	. 380	a trace.	a trace.	a trace.	.420
Lime, carbonate	a trace.	.430	7.480	.750	2.520	.080
Magnesia	, 101	.227	.440	. 208	1.271	a trace.
Phosphoric acid (anhydr.) .	.313	.376	. 570	.795	.526	.076
Sulphuric acid (anhydr.)	.220	.206	.089	.041	.090	.096
Combined water	10.150	10.800	8.772	11.200	10.126	10.450
Silex and insoluble silicates .	30.940	21.210	15.730	21.480	13.430	30.080
Moisture and loss		.127				
Total	100.069	100.000	100.000	100.054	100.000	100.176
Per centage of iron	37.551	41.272	41.357	42.941	43 - 473	37.838
Per centage of phosphorus .	.137	. 164	.231	- 347	. 229	.033
Per centage of sulphur	.086	.082	.035	.016	.036	.038
Per centage of silica	29.560	19.980	13.160	18.560	11.660	24.260

These are all good ores; Nos. 1273 and 1278 being the poorest in iron and the most silicious. The proportion of sulphur is small in all of them, and of phosphorus is probably not enough to injure the iron for ordinary uses. Nos. 1275 and 1277 would probably be improved for smelting by a previous roasting.

No. 1279—Coal. Labeled "Coal No. 7, from drift one quarter mile above the store, on Furnace Branch of Straight Creek, Buena Vista Furnace. Average sample of both parts of the bed, by P. N. Moore."

- No. 1280—Coal. Labeled "Coal No. 6, from Turkey-pen Hollow; Old Clinton Tract; Bellefont Furnace. Averaged by P. N. Moore."
- No. 1281—COAL. Labeled "Coal No. 7, three feet thick, no parting; Chadwick Creek. Average sample, selected by A. R. Crandall."
- No. 1282—Coal. Labeled "Coal No. 5, eighty-five feet below the yellow kidney ore, drift south side of Straight Creek, one third of a mile from Buena Vista Furnace. Averaged by P. N. Moore."
- No. 1283—Coal. Labeled "Keys Creek Coal, No. 6. Average sample collected by A. R. Crandall."
- No. 1284—Coal. Labeled "Coal No. 3, from drift on Hood's Creek, one third of a mile southeast of Bellefont Furnace. Average sample collected by A. R. Crandall."

A splint coal, exhibiting some fibrous coal and fine particles of pyrites between the layers.

No. 1285—Coal. Labeled "Coal No. 6, from Horse Branch (or Run), near Catlettsburg, Boyd county. Average sample, collected by A. R. Crandall."

A splint coal. Some fibrous coal between the layers, with a little ferruginous incrustation.

No. 1286—Coal. Labeled "Coal No. 7, from the Ashland Company's mine No. 4, Coalton, Boyd county. Average sample, by P. N. Moore."

A dark, glossy, splint coal, with some fibrous coal between the layers.

No. 1287—Coal. Labeled "Coal No. 7, from entry No. 4; cross-entry; slate roof; Dry Branch. Average sample, by P. N. Moore."

A jet-black pure-looking coal.

No. 1288—Coal. Labeled "Coal No. 7, three hundred yards from the end of No. 4 entry. Trace Creek, Boyd county. Averaged by P. N. Moore."

A pure jet-black coal. Very little fibrous coal or pyrites apparent.

No. 1289—Coal. Labeled "Coalton Coal, No. 7. Two hundred and fifty yards from west end of No. 4 entry, &c. Averaged by P. N. Moore."

Contains more fibrous coal and pyrites than the two preceding.

- No. 1290—COAL. Labeled "Coalton Coal, No. 7, from Mr. Bryan's Bank, Four Mile Creek, Boyd county. Collected by A. R. Crandall. Average sample."

  Jet black. Contains very little pyrites or fibrous coal.
- No. 1291—Coal. Labeled "Coal No. 11. Wm. A. Bolt's coal. East Fork of Little Sandy river, above Bolt's Fork, Boyd county. Average sample, collected by A. R. Crandall."

  A jet-black coal. But little fibrous coal or pyrites apparent.

  [See Appendix, No. 1645, for analysis of another Boyd county coal.]

COMPOSITION OF THESE BOYD COUNTY COALS, DRIED AT 212º F.

	J	COMPOSITION	I ON OF	THESE	E DOID	COOMIN		אם יפיושאי	DAILED AT	717			
	No. 1279.	No. 1280.	No. 1281.	No. 1882.	No. 1283.	No. 1284.	No. 1285.	No. 1286.	No. 1287.	No. 1288.	No. 1389.	No. 1290.	No. ragt.
Specific gravity	1. 328	1.358	1.304	r. 34o	1.279	1.366	1.315	1.308	1.340	1.336	1.320	1.365	1.49
Hygroscopic moisture. Volatile combus. mat'rs. Coke	59.55 8.95.50	33.40 64.30	3.50 34.16 62.34	33.30	32.56 64.50	3.20 29.70 67.10	36.70 50.60	33.30 53.40	4.40 31.10 54.50	4.06 34.24 61.70	34.50 36.50 50.50	34.06	35.88
Total	100.00	100.00	100.00	100.00	100.00	100.00	100.00	8.001	100,00	100.00	100.00	100.00	100.00
Total volatile matters . Fixed carbon in coke . Ashes	40.40 52.78 6.82	35.70 55.40 8.00	37.66 55.30 7.10	35.50 53.00 11.50	35.50 56.76 7.74	32.90 55.10 12.00	39.40 52.60 8.00	36.60 57.60 5.80	35.50 57.90 6.60	38.30 54.70 7.00	39.50 55.40 5.10	38.06 53.20 8.74	38.40 46.86 14.74
Total	100.00	100.00	8.8	100.00	100.00	100.00	100,00	100.00	100.00	100.00	100.00	100.00	100.00
Character of the coke .	Dense.	Dense.	Dense.	Dense.	Spongy.	Friable.	Spongy.	Mod.dense.	Spongy.	Spongy.	Spongy.	Spongy.	Spongy.
Color of the ash	Light lilac-grey.	Light purple-grey	Purple- grey.	Lilac-grey	Lilac-grey.	Drab-grey.	Dark lilac-grey.	Light lilac-grey.	Lilac-grey.	Lilac-grey.	Light br'wn-grey.	Dove colored.	Brownish grey.
Per centage of sulphur.	3.765	1.230	2.370	1.999	1.972	1.793	1.711	2.480	2.095	1.854	1.285	8%	3.361

With a few exceptions these may all be considered very These few contain rather too large a proportion good coals. of ash. This will not prevent them from being very good fuel for ordinary purposes. Some of them have a notable proportion of sulphur, which may render them measurably unsuitable for the working of iron, but which will not be otherwise injuri-It may be remarked, however, that the estimation given above is of the total amount of sulphur in the coal, in whatever form of combination it may exist. The analyses for the determination of the sulphur having been made by deflagrating the powdered coal with a mixture of nitre, carbonate of soda, and common salt (each chemically pure, of course), and not by the usual process of oxidation with nitric acid, &c., the extraction of the sulphur is therefore more complete than usual. are all splint coals.

The relation between the specific gravity and the proportion of ash does not seem to be a constant one, as may be seen in the following statement:

Specific gravity									1.279	Per centage of ash			•		7.74
									1.304						 7.10
							: 10		1.308						5.80
									1.315						8.00
									1.320						5.10
									1.328						6.82
									1.336				٠		7.00
		·					- 3		1.340						6.60
		٠	89			٠			1.358				ु		8.90
		į.	3		1				1.364				•		11.50
		•							1.365						8,74
		•		į.				٠	1.366						12.00
									1.404						14.74

In the appendix are given, for comparison, the analyses of some of the most celebrated Indiana, Ohio, and Illinois coal, which are used in the smelting of iron, &c.

No. 1292—MARLY SHALE. From near the top of the ridge between Clinton Furnace and Cannonsburg, Boyd county.

A friable indurated marly clay, of dirty-greenish and brownish colors.

Alumina, and iron and ma	nga	ane	ese	0	kid	les										٠	12.643
Lime, carbonate						•											.480
Magnesia																	. 929
Phosphoric acid																	.217
Sulphuric acid																	.079
Potash			•	•													1.387
Soda			• 1							•			14				. 080
Water expelled at red heat											•						5.830
Silica and insoluble silicate	s.		•														77.560
Loss																	.795

On treating this marl, by ignition with carbonate of lime and chloride of ammonium, for the complete separation of its alkalies, according to the method proposed by Prof. J. Lawrence Smith, we obtained a total of 3.989 per cent. of potash and 0.639 per cent. of soda. So that about two thirds of the potash is in such a state of combination, in the silicates of this marly clay, as to resist the solvent action of chlorohydric acid, of specific gravity 1.1, although digested for eight or ten days in the sand-bath heat. Possibly admixture with slacked quick-lime might help to set free this considerable proportion of alkali, and make it an available mineral fertilizer for exhausted light soils.

No. 1293—Pig. Iron. "Hot Blast No. 1, Bellefont Furnace, Boyd county. Collected by P. N. Moore."

A moderately coarse-grained dark-grey iron. Yields to the file, and extends somewhat under the hammer.

No. 1294 — Pig Iron. "Hot Blast No. 1, Foundry, Buena Vista Furnace. Collected by P. N. Moore."

A coarse-grained grey iron. Yields to the file; extends a little under the hammer.

No. 1295—Pig Iron. "Mill Iron No. 1, Ashland Furnace, Boyd county. Stone-coal Iron. Sent by Col. Douglas Putnam, jr."

A very fine-grained light-grey iron. Yields to the file. Brittle.

No. 1296—Pig Iron. "Mill Iron No. 2. Stone-coal Iron. Ashland Furnace. Sent by Col. Douglas Putnam, jr.

Not quite so fine-grained as the preceding. Light-grey. Yields to the file. Brittle.

VOL. 1.-CHEM. 3.

No. 1297—Pig Iron. Foundry Iron. Ashland Furnace, &c., &c. (as above). Coarser-grained than the preceding.

Yields to the file. Brittle.

#### COMPOSITION OF THESE BOYD COUNTY PIG IRONS.

	No. 1293.	No. 1294.	No. 1295.	No. 1296.	No. 1297.
Specific gravity	7.132	7.127	6.410	6.503	6.406
Iron	93.208	93.712	91.420	90.899	89.731
Graphite	3.350	2.990	2.460	2.560	1.660
Combined carbon	. 220	.210	.240	.160	.790
Manganese	.054	.056	.195	.236	.471
Silicon	2.389	1.908	3.709	5.121	6.308
Slag	1.160	.600	.540	.760	1.120
Aluminum	.193	.644	Not est.	Not est.	Not est.
Calcium	. 144	.104	.176	.072	.152
Magnesium	.095	.095	.233	.106	.060
Potassium	.047	.063	Not est.	Not est.	Not est.
Sodium	.032	.010	Not est.	Not est.	Not est.
Phosphorus	. 194	. 380	. 385	-394	.461
Salphur	.005	.066	.082 Loss .560	.045	.015
			1.055 .500		
Total	101.091	100.838	100.000	100.353	100.768
Total carbon	3.570	3.200	2.700	2.720	2.450

No. 1298—VIRGIN SOIL. "From woods in the valley of East Fork of Little Sandy river, taken to six inches below the surface. Farm of Vincent Calvin, near Cannonsburg, Boyd county. Collected by J. A. Monroe."

Soil of a dirty-buff color. All passed through the coarse sieve (289 meshes to the inch).

No. 1299—Sub-soil of the preceding, &c., &c.

Of a buff color; lighter in tint than the preceding. All passed through the coarse sieve.

No. 1300—VIRGIN SOIL. "Southeastern slope of hill sixty feet above the bed of the creek. V. Calvin's farm, &c., &c. Sample taken six inches from the surface by J. A. Monroe."

Of a dark dirty-drab grey color. The coarse sieve removed from it a considerable proportion of small fragments, many of which are angular, of ferruginous sandstone. No. 1301—Sub-soil of the preceding, taken two feet below the surface, &c., &c.

Lighter colored than the preceding; dirty-drab grey. Sifted out more of ferruginous sandstone fragments than from the preceding.

No. 1302—Old Field Soil. "Surface soil from a field forty-five years in cultivation, on East Fork of Little Sandy. Farm of V. Calvin, near Cannonsburg."

Soil of a dirty dark-buff color. All passed through the coarse sieve.

No. 1303—"Sub-soil of the next preceding, taken two and a half feet from the surface, &c."

Of a dirty-buff color, lighter in tint than that of the surface soil. All passed through the coarse sieve.

COMPOSITION OF THESE BOYD COUNTY SOILS, DRIED AT 212° F.

	No. 1298.	No. 1299.	No. 1300.	No. 1301.	No. 1302.	No. 1303.
Organic and volatile matters. Alumina, and iron and man-	3.140	3.085	7.985	5.190	4.915	4.905
ganese oxides	5.091	6.642	7.425	9.984	9.019	9.675
Lime, carbonate	.214	.116	.571	.392	.259	.276
Magnesia	.034	.178	.352	.251	.333	.053
Phosphoric acid	.134	.083	.208	. 191	.156	. 160
Sulphuric acid	trace.			trace.	.038	trace.
Potash	.317	.307	.435	.205	-344	.282
Soda	.076	.099	.045	.050	.027	.176
Sand and insoluble silicates .	90.490	88.420	81.410	83.230	83.765	83.385
Water expelled at 380° F	.650	.525	.915	.500	1.235	1.315
Loss		- 545	-554	.007		
Total	100.146	100.000	100.000	100.000	100.001	100.227
Hygroscopic moisture	1.375	1.735	2.225	1.700	2.335	2.840
Potash in the insol. silicates.	Not estima	ted.				
Soda	Not estima	ted.				
Character of the soil	Virgin soil. Val- ley.	Sub-soil.	Virgin soil. Slope of hill.	Sub-soil.	Old field.	Sub-soil.

These soils, if sufficiently drained and properly cultivated, may be made quite productive, although the silicious material is in rather large proportion in some. By comparing the composition of the virgin soil No. 1300, with that of the corresponding old field soil No. 1302, it will be seen that cropping, without the use of manures, has notably diminished the phosphoric acid, potash, and lime carbonate, while the relative proportion of the sand and silicates is increased.

[For Bourbon County Limestone, see the Appendix.]

#### BRACKEN COUNTY.

No. 1304—Soil. Labeled "Top Soil, one to eight inches from surface. Old field in grass; thin and bare in places. Sample from a fertile corner, beyond the fence where it had been out of culture for five years or more." Collected by Prof. N. S. Shaler.

Of a dark grey-buff color. Contains no gravel or coarse sand.

No. 1305 — "Sub-soil of the preceding; taken fourteen to eighteen inches below the surface, just above the rock substratum. It has some faint traces of original bedding, showing that it had been formed by decomposition of rock in place. Collected by Prof. N. S. Shaler."

Of a handsome yellowish-buff color. No gravel.

No. 1306—Top Soil of the field No. 1304; taken in a worn place; has been longer in cultivation and is much more worn than that. Will not hold sod. Has been in cultivation over twenty years. Collected by Prof. N. S. Shaler."

Of a yellowish-buff color, very little darker than that of the sub-soil. Contains a small quantity of small fragments of red ferruginous shale.

EXTRACTED FROM 1000 PARTS OF THESE SOILS (AIR DRIED) BY DIGESTION IN CARBONIC ACID WATER.

	No. 1304.	No. 1305.	No. 1306.
Organic and volatile matters	0.483	0.600	0.294
Alumina, and iron and manganese oxides	.013	.013	.010
Lime, carbonate	.496	.040	.080
Magnesia		.023	.014
Potash	.030	.010	.020
Soda	.020	.020	.020
Soluble silica	.060	.130	.110
Phosphoric, sulphuric, and nitric acids and loss	.184	. 130	.118
Total extract from 1000 parts	1.316	0.960	.666
Color of the extract	Light brown.	Light brownish grey.	Brownish grey.

#### COMPOSITION OF THESE BRACKEN COUNTY SOILS, DRIED AT 212° F.

	No. 1304.	No. 1305.	No. 1306.
Organic and volatile matters	4.140	4.775	3 · 335
Alumina	5.837	5.513	3.837
Iron, peroxide	7.150	6.025	3.965
Manganese, brown oxide		.170	.070
Lime, carbonate	a trace.	a trace.	a trace.
Magnesia	.297	.269	. 268
Phosphoric acid	.233	.424	.217
Sulphuric acid	a trace.	a trace.	a trace.
Potash	.110	. 197	.135
Soda	a trace.	.174	.076
Sand and insoluble silicates	82.140	81.970	87.815
Water expelled at 380° F	1.015	1,.100	not est.
Total	101.147	100.617	99.718
Water expelled at 212° F	2.200	3.200	2.300

These soils are all deficient in lime. Top-dressing with this material would doubtless greatly improve their productiveness. This should, however, be accompanied with the use of clover or other green fertilizing crops, to increase the proportion of humus, which is also deficient in the soils. The difference in the amount of soluble matters extracted by digestion in water charged with carbonic acid, as well as the relative proportions of the potash, &c., in that extracted matter, and the amount

of sand and silicates, correspond with the observed relative productiveness of the soils.

No. 1307—SILICIOUS MUDSTONE (of Dr. Owen). Rock below Soil No. 1304; averages from twenty-eight to thirty-five inches. Uniform. Some of the layers completely decomposed; all of them softened by decay. Three miles northwest of Germantown. Collected by Prof. N. S. Shaler.

A dirty grey-buff, friable, sandy shale. Adhering to the tongue. Many fossils in the laminæ.

		•	:01	4P	osi	ITI	ON	١,	DR	IE	D	٨٦	Г 2	212	20	F.			
Silica																		76.060	
Alumina, and iron and ma	nga	an	ese	0	xic	des												14.959 (by difference	e).
Lime, carbonate																	•	.500	1
Magnesia, carbonate																		. 345	
Phosphoric acid																		.486	
Potash																		2.735	
Soda																		1.515	
Water expelled at red heat				•	•													3.400	
State of the state																			
																		100 000	

This analysis having been made by fusion, instead of digestion in acids, &c., &c., gives the total contents of alkalies and phosphoric, as well that quantity which may be immediately available for plant nourishment as that which for the present is locked up in firm combination in the silicates, which can only become available in the natural course of long weathering.

#### BRECKINRIDGE COUNTY.

No. 1308—" RED UNDER CLAY, from near Brandenburg. Collected by Mr. G. E. Chick.

A somewhat adhesive ferruginous clay, of a dark brick-red color; containing some fragments of weathered chert.

#### COMPOSITION, DRIED AT 212° F.

Organic and volatile matters, mostly water	9.000
Alumina, and iron and manganese oxides	20.860
Lime, carbonate	1.060
Magnesia	.684
Phosphoric acid	.230
Sulphuric acid	.061
Potash (including that in the silicates)	.982
Soda (including that in the silicates)	.50L
Sand and insoluble silicates	66.680

Although this clay contains a considerable per centage of potash, nearly one per cent., it is not probable that it could be profitably used as a fertilizer, because of the fact that a very large proportion of its alkalies is in the insoluble silicates, where they would not be immediately available for plant nourishment.

It might be employed, however, to improve the condition of light sandy soils.

## BUTLER COUNTY.

No. 1309—LIMONITE. Labeled "Ore from the farm of Jas. E. Taylor, near the mouth of Little Reedy; one mile and a half from Green river. Average sample by J. R. Proctor."

Limonite in irregular laminæ; with much softer ochreous ore.

No. 1310 — LIMONITE. Labeled "Ore above the upper coal. Stevens' coal mine, near the mouth of Bear Creek. Average sample by P. N. Moore."

In dense, curved, dark-brown laminæ, incrusted by and inclosing softer ochreous ore.

COMPOSITION OF THESE LIMONITES, DRIED AT 212° F.

																No. 1309.	No. 1310.
Iron, peroxide																48.049	44 · 794
Alumina															.	. 171	2.391
Manganese, brown oxide															.	. 140	a trace.
Lime, carbonate																. 540	.643
Magnesia																. 195	.234
Phosphoric acid																-345	.535
Sulphuric acid																.473	. 158
Water expelled at red heat .			•													9.750	7.700
Silica and insoluble silicates																31.900	44.180
Alkalies, &c., and loss																.437	
Total	•	٠	•		•	×	٠	•	٠	•	•	•	٠		٠	100.000	100.815
Iron, per centage				•							•					33.634	31 . 482
Phosphorus, per centage														įė.		. 150	. 233
Sulphur, per centage	•						•			•	•	•				. 189	.063
Silica, per centage				•							•				•	29.460	42.200

The somewhat large proportion of *phosphorus* in these two ores may make the iron obtained from them somewhat "coldshort," and the sulphur in No. 1310 is in rather too large quantity. In other respects these ores are good, and they might be profitably smelted for ordinary foundry iron.

No. 1311—CLAY IRON-STONE. Labeled "Ore from Jno. Hudson's on Young's Ferry road. Average sample by P. N. Moore."

A dark grey, fine-granular iron carbonate, partly converted into limonite.

No. 1312—CLAY IRON-STONE. Labeled "Ore resting on the coal at Knob Lick, half a mile from Big Reedy Creek, near road to Young's Ferry. Average sample by P. N. Moore."

Granular iron carbonate, somewhat oölitic, partly converted into limonite, and containing small fragments of fibrous coal.

COMPOSITION OF THESE CLAY IRON-STONES, DRIED AT 212° F.

																				No. 1311.	No. 1312.
Iron, carbonate											•									29.914	22.58
Iron, peroxide																				17.945	17.31
Alumina																				3.583	.83
Lime, carbonate	•				•										•					12.036	6.71
Magnesia, carbonate	•			•															.	3.677	2.830
Manganese, carbonate																			. [	a trace.	a trace
Phosphoric acid																				.467	.973
Sulphuric acid																				. 381	.473
Silex and insoluble silicate	s.																		.	28.040	44.240
Water and loss		•	•	•			•	•	•	•	•	•		•	•	•				3.957	4.040
Total	•	•	٠	•		٠	٠		•		•	•	٠	٠		÷	•	٠		100.000	100.000
Iron, per centage	•		•				•	•		•			•			•			-	27.041	22.969
Phosphorus, per centage.		÷						•		•		•	•						-	. 204	.423
Sulphur, per centage	*		٠	•													•		-	.152	. 189
Silica, per centage		*																	-	25.260	42.760
Specific gravity																				not est.	not est

No. 1313—Coal. Labeled "Stevens' coal. Stevens' bank, Bear Creek, two miles from Green river, Butler county. Average sample by P. N. Moore."

A deep-black coal, breaking into thin layers under the hammer. Fibrous coal and fine-grained pyrites between the laminæ. Contains a little shale.

# COMPOSITION OF THE AIR-DRIED COAL.

	No. 1313.
Specific gravity	1.378
Hygroscopic moisture	3.40 30.66 65.94
Total	100.00
Total volatile matters	34.06 54.94 11.00
Character of the coke	Spongy.
Color of the ash	Brownish lilac-grey.
Per centage of sulphur	2.544

No. 1314—LIMESTONE, from Barren river, near the mouth of Gasper Creek; sub-carboniferous. From the stock pile of Airdrie Furnace. Sampled by P. N. Moore."

A light-grey, fossiliferous limestone.

COMPOSITION.	DRIED	AT	2120	1.7
COMPOSITION.	DETELD	~ .	212	F .

Lime, carbonate	 	93.020 = 52.091 per cent. of lime.
Magnesia, carbonate	 	2.088
Alumina, and iron and manganese oxides	 	.917
Phosphoric acid		.243 = 0.106 per cent, of phosphorus.
Sulphuric acid	 	.604 = .242 per cent, of sulphur.
Silica and insoluble silicates	 	2.760
Water and loss	 	. 368
	10 <del>c</del>	<del></del>
		100.000

#### CALDWELL COUNTY.

GALENA (lead sulphide), selected from specimens sent by S. Marble & Son, Princeton, Kentucky, from their lead mine in this county. The vein is in the sub-carboniferous limestone, described as generally five feet wide. The mine has a twenty feet drift, forty-five feet wide. The gangue of the ore is principally fluor-spar, containing more or less zinc blende.

This ore was examined principally for its proportion of silver; and by a careful analysis of the lead, obtained from it by reduction with the usual flux (of soda carbonate, potash nitrate, and sodium chloride), solution of the reduced metal in diluted nitric acid, and precipitation of the filtered solution by means of a very dilute solution of lead chloride, a very small proportion of silver was obtained, not exceeding in amount two hundred and sixty-six (266) grains to the ton (of 2,000 pounds) of the selected galena. As is well-known, pure galena contains from eighty-one to eighty-six per cent. of lead in general

This mine cannot, therefore, be profitably worked for silver; but if fluor-spar is found to be practicably valuable for the purification of iron from phosphorus, &c., this, as well as the lead, may be advantageously explored.

# CAMPBELL COUNTY.

No. 1315—MARLY SHALE. Labeled "Clay Marl, from Cincinnati Group; quarter of a mile from Newport, on the Alexandria Turnpike; upper blue clay. Collected by Prof. N. S. Shaler." Lower Silurian.

A dark-grey, soft shale. Adhering to the tongue.

No. 1316—MARL. Labeled "Marl, from the silicious mud-stone of Dr. Owen, ten feet from the surface. Not distinctly stratified. Gallows Gap. Collected by Prof. N. S. Shaler."

Buff-colored; friable; fine-grained.

No. 1317—CLAY SHALE. Labeled "Newport Reservoir; three hundred and forty feet above the Ohio river. A mixture of the clays in a set of beds, containing a few limestone layers, six feet from the surface to twelve feet." Collected by Prof. N. S. Shaler.

A yellowish, soft shale, with some softer ferruginous clay mixed. Adhering to the tongue.

No. 1318—CLAY SHALE. Labeled "Newport Reservoir, upper blue clay, three hundred and twenty feet above high water in the Ohio river." Collected by Prof. N. S. Shaler.

A dark, bluish-grey soft shale. Adhering to the tongue.

No. 1319—CLAY. Labeled "Brick Clay, about three feet above high water in the Ohio river; Newport, Kentucky." Collected by Prof. N. S. Shaler.

A light, ferruginous, yellow silicious clay.

No. 1320—Sandy Ferruginous Clay. Labeled "Sandy Clay, three feet from surface; Mt. Vernon road, half a mile from Alexandria Turnpike." Collected by Prof. N. S. Shaler. Of a light reddish-brown color:

No. 1321—Ferruginous Clay, &c. Labeled "Ferruginous Conglomerate; side of road, one mile north of Grant's Creek. North head waters of Phillips' Creek." Collected by Prof. N. S. Shaler.

Ferruginous clay, with nodules of impure hydrated peroxide of iron included.

No. 1322—Sand. "Labeled "Moulding Sand, Columbia Trace, half a mile northeast of Newport Water-Works Reservoir." Collected by Prof. N. S. Shaler.

A fine sand of a dirty-salmon color, composed mainly of minute rounded quartz grains. No. 1323—SAND. Labeled "Sand beneath the Brick Clay. Section on Columba corner of Harris street; Newport, Kentucky." Collected by Prof N. S. Shaler.

A moderately fine sand, of a dirty-buff color. Examined with the glass it showed mostly rounded grains of hyaline, yellow and milky quartz, with dark grains of some ferruginous mineral.

COMPOSITION OF THESE CAMPBELL COUNTY MARLS, CLAYS, AND SANDS, DRIED AT 212° F.

	No 1315	No 1316	No. 1317	No. 1318	No. 1319	No. 1320	No. 1321	No. 1322	No. 1323
Silica	47.320	68.760	58.080	51.420	72.660	82.560	57.160	81.66o	85.840
manganese	28.050	12.050	31.490	29.450	20.500	12.223	33.540	12,700	3.500
Lime, carbonate	13.440	9.860	.660	6.850		.160	.860	a truce.	7.400
Magnesia, carbonate	1.135	3.859.	1.135	1.256	.832	a trace.	1.776	a trace.	.206
Potash	3.254	1.329	3.045	4.124	1.243	.675	2.698	. ~ 56	not est.
Soda	.640	.976	. 986	.567	not est.	.282	.555	.637	not est.
Phosphoric acid	Not esti	.223		.122	. 192	not est.	not est.	a trace.	not est.
Water expelled at red heat	4.800	2.200	4.700	4.400	4.200	4.100	3.411	4.400	2,200
Loss	.966	-743		1.811	-373				. 764
Total	100.000	100,000	100.351	100.000	100.000	100.000	100,000	100.153	100.000

These marly shales, marls and clays, are not especially valuable as fertilizers, although some of them contain considerable proportions of potash and phosphoric acid. The former, however, is mostly in firm combination in the silicates, which are insoluble in acids, so that it can only be made available by long weathering, or, possibly, by the action of lime, &c.

No. 1315 appears to be the best of them. They all would be useful as top-dressing for improving light sandy soil.

The sands have no peculiar interest, although useful for many well-known purposes.

No. 1324—Soil. Labeled "Virgin Soil, in open woods, farm of Gen. G. B. Hodge. Flat Woods; waters of Phillips' Creek; one and a half miles southeast from Grant's Lick. Timber—white oak, hickory, small beech, and walnut." Collected by Prof. N. S. Shaler.

Soil of a warm yellowish-drab color. It all passed through the coarse sieve (of 289 meshes to the inch), except some 36 rootlets, a very small quantity of shot-iron ore, and a few small rounded pebbles of milky quartz.

No. 1325—Soil. Labeled "Old Field Soil. Field adjoining the woods whence came No. 1324. Cultivated in corn and tobacco for more than forty years. No manuring. Still brings a little corn. Sample one to seven inches from the surface." Collected by Prof. N. S. Shaler.

Soil of a warm yellowish-drab color. All passed through the coarse sieve except a few fragments of wood, two or three small water-worn pebbles of milky quartz, and some small angular fragments of decomposing chert. It also contains some fine shot-iron ore.

No. 1326—Soil. Labeled "Same old field as the preceding. Plowed in 1871 to the depth of twenty inches and sub-soiled. Now (1873) in timothy grass. Seems to want lime." Collected by Prof. N. S. Shaler.

Color, &c., much as in preceding soil.

No. 1327—Soil. Labeled "Sub-soil, twelve inches from the surface, same field as preceding, forty years in cultivation. Silicious mudstone beneath." Collected by Prof. N. S. Shaler. Soil of a yellowish-drab color; more yellowish than preceding. All of it passed through the coarse sieve, except a very small quantity of shot-iron ore.

No. 1328—Soil. Labeled "Spur of hill sixty feet above the position of the preceding soils. In corn for two years. Twenty bushels to the acre this year (1873); bad culture. Surface soil."

Soil of drab color. Lighter colored than any of the preceding soils. Moist soil cakes in the bag like clay. It mostly passed through the coarse sieve, leaving only some shot-iron ore and small quartz pebbles, &c. No. 1329—Soil. Labeled "Virgin Soil, border of cultivated field, newly cleared. Slope faces southwest. Land reputed rich; but in the midst of much poor land. Sells for two hundred dollars per acre. Youtsey's land, eight miles from Newport, Alexandria Turnpike." Collected by Prof. N. S. Shaker.

A clay soil of a dark buff-grey color. Aggregated, on drying in the bag, &c., into quite hard, irregular and angular small lumps. Makes a very tenacious, sticky clay when wet.

No. 1330—Soil. Labeled "Sub-soil (under the preceding soil) two feet from the surface, &c." Collected by Prof. N. S. Shaler.

A clay soil of a light grey-buff color; aggregating into pretty compact lumps on drying.

See No. 1334 for composition of the limestone underlying this land.

No. 1331—Soil. Labeled "A curious gravelly loam, two feet below surface, with bits of chert, from the sub-carboniferous of Upper Licking. Silicious mudstone and limestone below. Upper waters of Pond Creek, near Pond Creek Post-office, on new turnpike, about four miles southwest of Alexandria." Collected by Prof. N. S. Shaler.

A deep yellow-buff colored sub-soil, containing nearly one sixteenth of its weight of fragments of ferruginous shaly sand rock, rounded quartzose pebbles, and shot-iron ore.

No. 1332—Soil. Labeled "Old field in grass. Slope of 10° south. Resting on river detritus. Side of run near Newport, Kentucky." Collected by Prof. N. S. Shaler.

Soil of a dark grey-buff color. All of it passed through the coarse sieve.

No. 1333—Soil. Labeled "Bottom field of the next preceding, taken two feet from the surface. Detrital grit. Twenty feet above high water of Ohio river."

Soil of a handsome orange-grey, or grey-orange-buff color. Aggregated into friable clods.

COMPOSITION OF THESE CAMPBELL COUNTY SOILS AND SUB-SOILS, DRIED AT 212° F.

	No. 1324	No. 1325	No. 1326	No. 1327	No. 1328	No. 1329	No. 1330	No. 1331	No. 1332	No. 1333
Extracted from 1,000 parts by carbonated water	2.290	1.700	1.220	0.830	1.860	2.700	5.650	0.716	1.080	1.200
co	MPOSIT	ION OF	тне с	ARBONI	CACID	WATER	EXTRA	ст.		
Organic and volatile mat-										
ters	1.060	1.030	0.580	0.530	0.720	0.690	0.490	0.316	0.396	0.81
Alumina, oxd. iron, &c.	.320	. 130	.110	.040	.080	.020	.050	1010.	.060	
Manganese oxide	,060	.070	. o8c	not est.	not est.	not est.	not est.	not est∫		.030
Lime, carbonate	.610	.400	.260	.090	. 760	1.620	4.440	. 180	.430	.280
Magnesia	080	.036	.004	.040	.010	not est.	-450	.030	.010	.040
Nitric acid	Not esti		reserve seri	CONTRACTOR OF	000000000000000000000000000000000000000	less as a	l se es	200000000	and the second	
Phosphoric acid	a trace.	a trace.	a trace,	a trace.	a trace.	a trace.	a trace.	a trace.		a trace.
Sulphuric acid	a trace.	a trace.	a trace.	a trace.	a trace	a trace.	a trace.	a trace.	a trace.	a trace.
Chlorine	Not esti	mated.								
Potash	.060	.070	.050	.010	.050	.030	.020	.020	.037	.020
Soda	.010	,050	.040	.030	.020	.040	.020	.040	.015	.020
Soluble silica	, 122	.090	.055	.150	.170	.070	. 180	. 130	.080	.067
Loss			,021		.050	.230			.052	
Total	2.322	r.876	1.220	0.890	1.860	2.700	5.650	0.726	1.080	1.272
	I		· · · · ·	1	, DK.	ED AT				
Organic and volatile mat- ters	3.650	2.555	2.540	2.435	8.965	7.615	5.960	5.160	2.775	2.135
Alumina	3.375	3.415	3.900	3.868	4.040	5.175	5.323	3.815	1.587	2.737
Iron oxide	3.125	3.038	3.274	3.972	4.787	6.750	6.800	4.300	2.980	4.465
Manganese, br. oxide	.059	.037	not est.	.427	.471	.260	.080	. 390	.070	.320
Lime, carbonate	.130	.090	. 125	.125	.450	.990	3.890	a trace.	a trace.	a trace.
Magnesia	.034	.496	.008	.250	.250	. 520	.500	.474	.191	. 300
Phosphoric acid	.145	. 100	.093	.122	.003	.483	.313	.420	.256	.240
Sulphuric acid	a trace.	a trace.	a trace.		a trace.	a trace.	a trace.	a trace.	a trace.	a trace.
Potash	.120	.062	.064	.062	.240	. 726	. 593	- 443	.115	. 125
Soda	.047	.132	. 160	,100	.071	a trace.	.019	.045	.048	. 106
Soluble silica •	.045	.090	.055	.015	.170	.070	. 180	. 130	.080	.067
Sand and insoluble sili-	1000000	00000000			300.000	100.400	0	-	000300000	2027-004
cates	87.545	89.335	88.305	87.560	78.963	75.590	75.415	83.775	91.655	89.040
Water expelled at 380° F.	1.160	1 110	1.020	1.040	1.500	1.850	1.017	1.250	1.035	1.010
Luss	. 563		. 366	.015						
Total	100,000	100.469	100.000	100.000	100,000	100.000	100, 180	100.202	100.792	100.545
					===					
	1.765	1.550	1.665	2.235	2.550	5.075	4.300	4.825	1.400	2.215
Water expelled at 212° F. Potash in insoluble sili-	1.705	1.330		C 10/09/15/2009						1,020,021,035
Potash in insoluble sili- cates	not est.	1.311	not est	1.477	not est.	2.731	not est.	not est	not est.	not est.
Potash in insoluble sili-		10.000,000	0.0000000000000000000000000000000000000	1.477	not est. not est.	2.731 .929	not est. not est.	not est not est.	not est. not est.	not est.

<sup>\*</sup> It is proper to state, that this quantity does not represent the "soluble silica" which might have been extracted by boiling the "silicious residue" in solution of carbonate of soda. &c., but simply the amount which was held in the acid solution of the soil. But little importance was attached to this determination, not because its existence in the plant is considered by many modern agricultural chemists as "an accident" and "unessential," if not "useless" (see "How Crops Feed," by Prof. S. W. Johnson, page 353); but because it is to be found, ordinarily, dissolved in all waters which percolate soils. Moreover, Prof E. A. Hilgard shows that the amount of soluble silica in the silicious residue of a soil usually bears a pretty constant relation to the quantity of lime in it. Its proportion at any given time doubtless depends on the relative decomposition of the silicates of the soil at that time.

In addition to the determinations given in the preceding table of the composition of these soils, the "sand and insoluble silicates" were analyzed, by the method of fusion, &c., &c., with the following results, viz:

COMPOSITION OF THE SAND AND INSOLUBLE SILICATES IN THE 100 PARTS, DRIED AT 212° F.

	No. 1325.	No. 1327.	
Silica	89.560 7.650)	88.66o	
Lime	.324 }	9.310	
Magnesia Potash	. 260 J 1 . 464	1.684	= 1.311 and 1.477, severally calculated into 100
Soda	.743	. 346	parts of the soil.
Total	100.001	100.000	

An attempt was also made, with the use of the celebrated Nobel's apparatus, to submit some of these soils to silt analysis; *i. e.* to determine the relative proportions of the fine and coarser earthy material contained in them; but the results of comparative operations on the same soil were so discordant that no value whatever could be attached to them.

The writer regrets that he was not able, for want of time, &c., to apply to the silt analyses of some of these soils the improved apparatus devised by Prof. Eugene W. Hilgard, and used by him in his researches on the soils and clays of Mississippi, while he was the State Geologist, as described by him in a paper read by him at the Portland meeting of the American Association for Advancement of Science, August, 1873, and published in American Journal of Science and Arts, October and November, 1873.

The chemical analyses were conducted very much as is described in volume III of Kentucky Geological Reports, except that a larger quantity of the soil was digested in water containing carbonic acid, charged under the atmospheric pressure only, and found by analysis to contain about 0.9 of its volume of this gas. Instead of filtering the solution, a proportional quantity of it was drawn off from the residue by means of a pipette of proper construction.

The residue obtained by evaporating this solution, frequently deflagrated when ignited, showing the presence of nitrates.

This was observed, in a marked degree, with the extracts from Nos. 1324, 1325, 1326, 1327, and 1329.

The above table of the results of the analyses of these soils is interesting, as demonstrating, what has frequently been called in question by agricultural chemists in recent times, the possibility of ascertaining the agricultural capabilities of soils by chemical analysis; having due reference, of course, to the physical conditions.

For the purpose of more ready comparison of some of the results of these analyses, we copy in the following table the proportions of some of the most essential ingredients and educts of these soils:

	Extracted by carbon- ated water from 1,000 parts.	Extracted by acids from 100 parts.											
		Organic and volatile matters.	Lime, car- bonate.	Phosphoric acid.	Potash.								
No.		. 6											
1324, virgin soil	1.876	3.650 2.550	0.130	0.145	.062								
1326, old field, same locality	1.220	2.554	.125	.093	.064								
1327, sub-soil, same locality	.891	2.435	.125	.122	.062								
1328, new field, same locality	1.860	8.965	.450	.093	.483								
1329, virgin soil (Youtsey's), high priced; considered rich	2.700	7.615	.990	.483	.726								

Youtsey's land will be seen, by reference to Appendix No. A. 12, to be strikingly like the California adobe soil in composition and consistence. It also resembles good blue grass soil. The others show a deficiency of lime, potash, and organic matters, or *lumus*, except that of the "new field," which, like No. 1325, is apparently deficient in phosphoric acid, and which would be much more productive under better culture than it has received, and with the application of phosphate or superphosphate of lime. The use of lime, wood ashes, and of green crops, especially of clover, would be beneficial to these soils of Col. Hodges?

No. 1334—LIMESTONE. Labeled "Blue Limestone (Cincinnate Group), just below soils Nos. 1329 and 1330. Youtsey's land, Alexandria Turnpike, eight miles from Newport, Campbell county." Collected by Prof. N. S. Shaler.

A firm coarse-grained semi-crystalline, dark-grey limestone full of fossils, corals and shells, with some included nodules of light olive-grey granular material.

# COMPOSITION DRIED AT 2120 F.

Lime, carbonate	93.200 = 52.192 per cent. of lime.
Magnesia, carbonate	2.291
Alumina, and iron and manganese oxides	1.700
Sulphuric acid	.535 = .214 per cent. of sulphur.
Phosphoric acid	.076 = .033 per cent. of phosphorus.
Potash	.173
Soda	. 384
Silex and insoluble silicates	2.360
t <del>-</del>	<del></del>
	100.719

A limestone not very rich in mineral fertilizers, which would yield a good lime for building purposes.

No. 1335—"MARLY SHALE, from two miles south of Newport, Licking Three Mile Creek. Geological position, 'Cincinnati Group,' fifty feet above high water mark of the Ohio river." Collected by Prof. N. S. Shaler.

A friable shale of a handsome light olive-grey color, containing fragments of small encrinital stems and of orthis multicoste.

No. 1336—"Marly Shale, from Licking Three Mile Creek, two miles back of Newport (Cincinnati Group). About sixty feet above high water mark of the Ohio river. The beds are about thirty feet thick, with thin partings, and can be easily stripped. Test their value as marl." Collected by Prof. N. S. Shaler.

Of a light olive-grey color. The laminæ are thinner than in the preceding.

COMPOSITION OF THESE MARLY SHALES; DRIED AT 212° F.

																	022								No. 1335.	No. 1336.
Silica		•																							54.160	57.260
Alumina															en.			•							12.269	16.782
Iron peroxide, w	rit	h s	50	m	e 1	ma	ng	gai	e	æ	ox	id	е .					•							15.550	11.500
Lime, carbonate	٠,		2		•																				7.800	4.560
Magnesia																									. 165	.778
Phosphoric acid			ĺ.															•		•					.281	.008
Sulphuric acid .																									.659	.233
Potash																										4.471
Soda			e co																						.926	1.072
Soda Water expelled a	t	rec	1	he	at	an	d	la	SS	•	•		•	•	٠	•	•	•	•	•	•	٠	•	•	4.892	3.336
Total				6											•										100.000	100.000

These marly shales resemble in composition the marls and clays reported above.

## CARTER COUNTY.

No. 1337—CLAY. Labeled "Fire-clay; average sample from the upper bed, four feet thick, on both sides of the hill. Ridge between Grassy and Three Prong Creeks, Boone Furnace property. Whole bed eight to ten feet thick. Collected by Philip N. Moore."

The dried clay is quite compact, scarcely to be scratched with the nail; has a soapy feel; not adhering to the tongue. Breaks into sharp angular fragments. It is of a light-grey color.

No. 1338—CLAY. "From ridge between Grassy and Three Prong Creeks, Boone Furnace property. Lower bed. Collected by P. N. Moore."

Compact, breaking into sharp angular fragments; hardly to be scratched with the nail; slightly adhering to the tongue; has a somewhat soapy feel. Presents, in parts, an approach to an oölitic structure. Color dark-grey, passing into dovecolor.

No. 1339—CLAY. "From same locality as preceding. Rougher part of the upper layer, &c., &c. Collected by P. N. Moore."

A light-grey compact rock, of a harsh gritty feel; not to be scratched with the nail. Under the glass showing many rounded grains of quartzose sand. Ferruginous incrustation on the surface

No. 1340—CLAY. "Fire-clay under coal. Old Orchard Diggings, Boone Furnace property, Carter county. Collected by P. N. Moore."

A compact shaly clay, with some of the lamellar surfaces polished in various planes. Has a soapy feel, and no grit. Of a dull dove-grey color.

No. 1341—CLAY. "Fire-clay from same bed as Nos. 1337, 1338, and 1339. A dark-colored sample from the lower part of the deposit." Collected by P. N. Moore.

Compact fine-granular; hardly scratched with the nail; adhering very slightly to the tongue. Of a dark brownish-slate color.

No. 1342—CLAY. "Fire-clay under the twelve inch coal Geo. Osenton's land, near Grayson, Carter county. Sampled by J. A. Monroe."

A grey or ash-grey clay in a pulverulent condition.

No. 1343—CLAY SHALE. Labeled "Argillaceous Shale, with some Lingulæ near the top. Railroad cut, half mile south of Station (Eastern Kentucky Railroad), Grayson, Carter county. Collected by Prof. N. S. Shaler."

A soft friable shale of a light buff-grey color, mottled and colored between the laminæ with ferruginous and black.

COMPOSITION OF THESE CLAYS, &c., OF CARTER COUNTY, DRIED AT 212° F.

	No 1337.	No. 1338.	No. 1339.	No. 1340.	No. 1341.	No. 1342	No. 1343.
Silica	48.560	45.960	54.620	62.460	45.560	64.260	66 060
Alumina	37-471	38.531	32.466	27.203	43-775	24.604	23.726
Iron, oxide	a trace.	a trace.	a trace.	a trace.	a trace.	not est.	not est.
Lime	.112	.145	a trace.	a trace.	. 145	. 538	*.300
Magnesia	a trace.	a trace.	a trace.	a trace.	a trace.	. 200	*.121
Phosphoric acid	. 255	. 563	.243	.147	-307	.946	.127
Sulphuric acid	not est.	not est.	not est.	not est.	not est.	.157	not est.
Potash	. 289	.250	.212	1.850	.963	751	2.093
Soda	.283	.341	.679	.584		.515	2.273
Water expelled at red heat	13.030	14.210	11.780	7.756	8.522	8.300	5.300
Total	100.000	100,000.	100.000	100.000	100.000	100.280	100,000

<sup>·</sup> Carbonates.

The composition of these clays indicate that most of them are highly "refractory" or fire-clays, and that all could be used for the manufacture of stone-ware, terra cotta, &c. Those which burn white might be used for "delf ware," or "queen's-ware," so called.

The most refractory are, probably, Nos. 1337, 1338, and 1339; the next, Nos. 1342, 1341, and 1340. The least refractory of all is the clay shale, No. 1343, which, however, notwithstanding its more than two per cent. each of potash and soda, would answer for the manufacture of stone-ware, and, most probably, of ordinary fire-brick.

It is found that a large relative proportion of silica or sand increases the refractory quality of the clay, and, according to the experiments of E. Richters\* (1868), this quality is least affected by magnesia; more so by lime; still more by iron oxide; and most by potash. The influence of phosphates has not been fully determined.

For comparison, the analyses of two of the best Kaolin clays of France, of the best Stourbridge clay of England, and of a crucible clay, are here appended:

															(a)	(6)	(c)	<i>(d)</i>
Silica															48.68	55.30	63.40	47.50
Alumina .															36.92	30.30	31.70	34.37
Iron oxide																2.00	3.00	1.24
Lime															not given.	not given	not given.	. 50
Magnesia.	_														.52	.40	not est.	1.00
Phosphoric	a	cid											•	•	not given.			0.774.5.55.47
Sulphuric a	ci	d													not given.	1	1	
Potash					-	-			200		-				not est.	1.10)		not est.
Soda							-			-	-	•			. 58	2.70	1.90	not est.
Water expe	lle	d	at	re	d	he	at .	•	•		•	٠	•		13.13	8.20	not given.	1.00

<sup>(</sup>a) Porcelain clay of Saint Yriciex; analyzed by Forchammer.
(b) Porcelain clay of China; analyzed by Ebelmann and Salvetat.
(c) Stourbridge fire-clay; analyzed by Prof. F. A. Abels.
(d) Crucible clay. Almerode, in Kurhessen.

It is evident our fire-clays do not suffer in comparison with these, and that the industrial value of these large deposits in our coal measures is very considerable.

[For other fire-clays see Greenup county, &c.]

<sup>\*</sup> R. Wagner's Chemical Technology, American edition, page 294.

# COALS OF CARTER COUNTY.

No. 1344—"COAL, probably sub-conglomerate, at Old Orchard Diggings. (Eight inches of coal, four inches of slate, six inches of coal.) Boone Furnace property."

A dull slaty coal, having much fibrous coal between the laminæ. Exterior stained with iron oxide.

No. 1345—"COAL, No. 7, from old entry back of Star Furnace. Upper layer twenty inches thick (Coalton coal). An average sample, collected by A. R. Crandall."

Breaks easily into thin irregular laminæ, with some fibrous coal between. Incrusted somewhat with iron oxide.

No. 1346—"COAL, No. 7, from old entry back of Star Furnace.

Bottom layer, two feet two inches thick. Collected by A. R.

Crandall."

A pure-looking coal; fracture glossy and pure black, somewhat like that of asphaltum. Very little fibrous coal, pyrites, or ferruginous incrustation apparent.

- No. 1347—"COAL, No. 7, from entry back of Star Furnace. Middle layer, two feet thick. Collected by A. R. Crandall." Appears to be intermediate in quality to the two preceding.
- No. 1348—"COAL, No. 7 (Coalton). Average sample from Wiley Pritchard's bank, near Mount Savage Furnace, Carter county. Collected by J. A. Monroe."
- No. 1349—"COAL, No. 7. Average sample of the six feet Coalton coal, from all parts of the bed. Divide between Stinson and Straight Creeks. (Two hundred and seventy-five feet level.) Mount Savage property. Averaged by P. N. Moore."
- No. 1350—"COALTON COAL (No. 7 coal), from drift on Gumbranch of Straight Creek. Mount Savage Company drift, lower part of the bed. Averaged by P. N. Moore."

- No. 1351—"COALTON COAL (No. 7 coal), from drift on Gum branch of Straight Creek. Upper part of bed, Mt. Savage property. Averaged by P. N. Moore."
- No. 1352—"Average sample of Coalton coal (No. 7), Watson Bank, Willard, Carter county. Averaged by J. A. Monroe."
- No. 1353—"COAL (No. 1) from Graham bank, Little Fork of Little Sandy river, near Willard. Average sample by P. N. Moore."

[See appendix, Nos. 1646 and 1647, for the analyses of two other samples of the coal from this bank.]

No. 1354—"Coalton Coal (No. 7), from main entry, west of Dry Fork, Willard. Averaged by P. N. Moore."

A jet-black pure-looking coal, showing iridescent colors on portions, and having very little fibrous coal or pyrites.

No. 1355—"Coalton Coal (No. 7) from Old Lost Creek drift, near Willard. Averaged by P. N. Moore."

Of rather a rusty black color; shows but little fibrous coal or ferruginous stain.

- No. 1356—"Coal (No. 2) from Kibby drift, Everman's Creek, two miles from Grayson, Carter county. Average sample by J. A. Monroe."
- No. 1357—"COAL (No. 1) from Stone-coal branch of Tygert Creek, Carter county. Averaged by P. N. Moore."
- No. 1358—"Coal (probably No. 2) from a quarter of a mile north of N. Lewis' house, Barrett's Creek, Carter county. Averaged by P. N. Moore."
- No. 1359—"Coal (probably No. 3) from Carter farm, two miles east of Grayson, on Dr. Jones' land (not a very good average sample). P. N. Moore."

COMPOSITION OF THESE CARTER COUNTY COALS. AIR DRIFT

.0	ຽ	COMPOSITION	TION	OF THESE		CARTER		COUNTY	COALS	, AIR	COALS, AIR DRIED	J.				
	No. 1344	No. 1344 No. 1345 No. 1		No. 1347	No. 1348	No. 1349	No. 1350	No. 1351	No. 1352	No. 1353	No. 1354	No. 1355	346 No. 1347 No. 1348 No. 1359 No. 1350 No. 1351 No. 1353 No. 1354 No. 1355 No. 1356 No. 1357 No. 1358 No. 1359	No. 1357	No. 1358	No. 1359
Specific gravity	1.330	1.377	1.288	1.290	r.435	1.347	1.340	1.323	1.326	1.274	1.352	1.337	1.289	1.298	1.307	1.388
Hygroscopic moisture			6.60 34.36 59.04	6.40 27.22 66.38	32.70	6.95 33.96 59.14	6.45 5.23	6.06 32.94 61.00	4.45 62.60 62.00	34.50	3.20	33.96	34.10	33.50	33.70	8.6.98 8.8.8
Lotal	8.8	8.8	8.00	100.00	00.00	00.00	100.80	100.00	100.00	100.00	8.00	100.00	8.8	8.0	100.00	8.8
Total volatile matters	44.64	35.86	4.5.4 8.4.4	33.62 58.88 7.50	38.10 52.52 9.38	40.86 51.04 8.10	37.80 57.66 4.54	39.00 54.80 6.20	38.00 52.86 9.14	38.30 3.30	38.26 54.40 7.34	39.66 52.94 7.40	38.700 56.525 4.775	38.10	37.90	39.30 11.56
Total	60.00	00,001	8 .03	8.00	100.00		100.00	100.00	8.80	100.8	100.00	100.00	100.000	8.8	8.8	100.00
Character of the coke	Pulveru- lent.	'	Dense porons.	Very friable.	Dense perous.	Dense porous.	Dense porous.	Dense parous.	Dense porous.	Dense porous.	Spongy.	Dense spongy.	Dense porous.	Dense porous.	Spongy.	Spongy.
	Nearly white.	Lilac. grey.	Light grey.	Light brown.		flow- like- rey.	Purplish grey.	Dark purplish grey.	Irown-	Brown- ish-grey	Lilac- grey.	Grey. brown.	Lilac- grey.	Yellow- ish-grey	Brown- ish-grey	Lilac- grey.
Per centage of sulphur	not est	1.035	0.724	0.973	2. 350	2.430	1.670	1.867	2.210	2.164	2.631	2.727	1:4:1	1.30	3.483	1.381
Composition of the ash of	No. 1345	No. 1345 No. 1346														
Silica Alumina and iron oxide Lime, carbonate	5.38 0.32 0.28	2.20 a trace.														
Total	11.10	4.40														

No. 1360—"Coke, made from the No. 7 coal, in oven, by Mr. Bates, Willard, Carter county. Collected by A. R. Crandall."

A bright-looking coke somewhat dense.

# COMPOSITION, AIR-DRIED.

Hygroscopic moisture Volatile combustible matters Coke (dry)							•				•										2.46 1.84 95.70
Total	•		•	•	٠	•	•	٠	•	•	•		•	•	٠	•	•				100.00
Total volatile matters Fixed carbon											•										4.30 87.34 8.36
Total	٠		٠	٠	٠			٠				٠		٠				٠			100.00
Color of the ash		•	*		•					•		•		×					•	•	Lilac-grey
Per centage of sulphur	•						•			•	•	•	٠	,		٠	•				2.026

The proportion of sulphur has been but slightly reduced by the coking of this coal. It is probably mostly in combination with iron, as iron proto-sulphide, and may not seriously injure this coke as fuel for the smelting and working of iron.

IRON CARBONATE ORES AND FERRUGINOUS LIMESTONE OF CARTER COUNTY.

No. 1361—Ferruginous Limestone. Labeled "Limestone Ore, from Old Orchard Diggings, Boone Furnace property. Averaged by P. N. Moore."

A dull-looking, fine-grained or compact ferruginous limestone, of a light-grey color, varied in parts by infiltrated hydrated oxide of iron. Fracture somewhat hackley. Specific gravity = 2.879.

No. 1362—CLAY IRON-STONE. Labeled "Limestone Ore from drift at Old Orchard Diggings, head of Grassy Creek, Carter county. Undecomposed ore. Average sample from various parts of bed No. 1. Boone Furnace property. Collected by P. N. Moore."

Irregular nodules and masses of clay iron-stone; varying in color from light-grey to blackish; mixed with some hydrated iron peroxide.

No. 1363—CLAY IRON-STONE. Labeled "Kidneys in shale below the coal described, No. 1344, at Old Orchard Diggings, Boone Furnace property, &c. Shale, with the kidneys, four inches thick. Collected by P. N. Moore."

Irregularly shaped nodules of fine-granular clay iron-stone superficially coated with hydrated brown iron oxide.

No. 1364—CLAY IRON-STONE. Labeled "Limestone Ore (No. 1), Horsley bank, Boone Furnace property, &c. The undecomposed carbonate. Collected by P. N. Moore" (for a cabinet specimen).

A fine-granular ore, varying from light-grey to purplishgrey, and incrusted in parts with limonite.

- No. 1365—CLAY IRON-STONE AND LIMONITE MIXED. Labeled "Average sample of Limestone Ore (No. 1), Horsley bank, Boone Furnace property, &c. Collected by P. N. Moore."

  A mixture of fragments of clay iron-stone and limonite ores.
- No. 1366—CLAY IRON-STONE. Labeled "Blue Limestone Ore, from west bank of Tygert Creek, about two miles from Iron Hills, Carter county. Average sample by P. N. Moore."

Fragments of clay iron-stone nodules, invested externally with limonite layers.

No. 1367—CLAY IRON-STONE. Labeled "Lower Block Ore, on Dry Fork of Sinking Creek, Carter county. J. M. James' land (six inches of undecomposed siderite). Average sample, by P. N. Moore."

Compact clay iron-stone, with some little limonite.

No. 1368—CLAY IRON-STONE. Labeled "Foxden Ore. Means and Russel land, Cumming's branch of Everman's Creek, Carter county. Averaged by P. N. Moore."

The undecomposed carbonate covered with layers of limonite of various tints, some of which are ochreous.

No. 1369—CLAY IRON-STONE. Labeled "Grey Limestone Ore, Mount Savage Furnace. Average sample, by J. A. Monroe." Grey granular and oölitic carbonate, with more or less limonite ore.

No. 1370—CLAY IRON-STONE. Labeled "Lower Block Ore. Mr. Everman's Sammy's branch of Barrett's Creek, Carter county. Averaged by P. N. Moore."

Mostly dark-grey, fine-granular carbonate ore, with some incrustation of limonite.

SUMMARY OF THE COMPOSITION OF THESE CARTER COUNTY CLAY-IRON-STONE ORES, &c., DRIED AT 212° F.

	No. 1361	No. 1362	No. 1363	No. 1364	No. 1365	No. 1366	No. 1367	No. 1368	No. 1369	No. 1370
Iron, carbonate	24.408	61,220	62.662	65.018	44.242	27.511	62.321	46.893	30.708	47.391
Iron, peroxide		4.410	10.024	5.945	27.296	26.240	4.989	9.255	31.544	9.734
Alumina	. 560	2.260	1.600	1.060	1.500	9.021	7.901	5.703	1.779	4.197
Lime, carbonate	45.200	4.480	.240	2.720	6.58	2.320	12.000	12.460	2.730	5.220
Magnesia, carbonate	24.328	a trace.	2.838	9.038	1.046	2.838	.222	.250	. 144	7.893
Manganese, carbonate .	. 391	.150	3.251	2.332	.842	. 279	. 121	not est.	.060	.346
Phos'ic acid (anhy dr. ! .	.147	.313	.127	.255	.732	. 499	.684	. 478	.421	.121
Sulphuric acid (anhydr.)	- 439	not est.	.521	1.280	4.587	.116	. 206	a trace.	. 491	.151
Silica and insol silicates	2.420	21.200	13.720	10.260	11.100	25.180	10.740	23 510	25.430	20.230
KO 135; NaO 204	339	. 540		2.112						
Water and loss	1.768	5.367	3.017		1.95	6.005	.816	.951	6.523	4.717
Total	100.00	100,000	100.00	100.000	100.00°	103,000	100.000	100,000	100,000	100.000
Per century of inco						21. 608		29.116	36.627	60.
Per centage of iron	10.900	32 578	37.285	35-549	40.465	31.598	33.348	29.110	30.027	29.685
Per ct. of phosphorus .	0.064	0.136	0.055	. 111	. 321	. 208	. 298	. 427	. 184	. 052
Per centage of sulphur.	0.203		, 208	- 533	1.855	.046	, 082		. 196	. 060
Per centage of silica						23.80	8.980	20.860	10.560	19.760

<sup>\*</sup> This sample had in it visible fragments of pyrites, and hence the above may not be an exact determination of the average sulphur of this ore.

No. 1361 would be unobjectionable as flux for richer ores, were it not for its considerable proportion of sulphur. It would make good lime for agricultural uses; which would make a strong cement with sand for all building purposes, where its color would not be objectionable.

The Horsley bank ores Nos. 1364 and 1365, although rich enough in iron, also contain quite large proportions of sul-

phur, exceeding in this respect all these ores; many of which may be considered quite good of their kind, as may be seen on examination of this table.

LIMONITE IRON ORES OF CARTER COUNTY.

No. 1371—LIMONITE. Labeled "Limestone Ore from Horsley bank, Boone Furnace property. (A cabinet specimen.) Collected by P. N. Moore."

In irregular curved laminæ of various tints, from dark brown to red and light yellow; with some soft ochreous ore.

No. 1372—LIMONITE. Labeled "Average sample of Lambert Main Block Ore, Potato Knob Hill. From the stock pile, Iron Hills Furnace, Carter county. Collected by J. A. Monroe."

Ore varying from dense dark chocolate-brown, irregular laminæ and grains, to brownish-yellow soft ochreous.

No. 1373—Limonite. Labeled "Potato Knob Iron Ore. Average sample. Iron Hills Furnace, &c."

In nodules varying from one to six inches in diameter. Exterior of hard dark-brown limonite; interior nodules soft and porous, of yellowish and reddish-brown colors.

No. 1374—LIMONITE. Labeled "Main Block Ore, Stewart bank. Divide between Barrett's and Everman's Creeks, three miles west of Grayson, Carter county. Average sample."

The irregular laminæ and concretions varying in color from dark chocolate-brown or purplish to greyish-yellow.

- No. 1375—LIMONITE. "From Royster Hill Lambert bed. Iron Hills Furnace. The ochre from the lower part of the bed." Porous and showing a small oölitic structure. Color brownish and greyish-yellow.
- No. 1376—LIMONITE. Labeled "German Ore. Smith Hill. Taken from an imperfectly shown bed, possibly not fully representing the whole bed, except that the ore seems very uniform. None of the blue ore, or kidneys above the main bed, included in this sample. Iron Hills, Carter county. Collected by P. N. Moore."

Ore generally porous or ochrey, of a yellowish-brown color mottled with light-grey. Some few laminæ of hard limonite.

No. 1377 — LIMONITE. Labeled "Crown Ore. Smith Hill. Iron Hills, &c. Average sample, from upper part of the bed only, by P. N. Moore."

Composed of irregular laminæ of dense dark-brown limonite, with cavities and included soft ochreous ore.

- No. 1378—LIMONITE. Labeled "Lower Block Ore. Perry's branch of Tygert Creek, west of Olive Hill. Land of Tygert Valley Iron Company. Average sample by P. N. Moore." Fragments of dense limonite laminæ mixed with some small clay iron-stone nodules.
- No. 1379 LIMONITE. Labeled "Average sample of Lower Block Ore, from road on west side of Garvin's Hill, west of Olive Hill. Land of Tygert Valley Iron Company." Fragments of limonite laminæ and clay iron-stone nodules.
- No. 1380—LIMONITE. Labeled "Block Ore from Garvin's Hill, west of Olive Hill. Land of Tygert Valley Iron Company. Average sample."
- No. 1381—LIMONITE. Labeled "Main Block Ore; Old Mount Tom Ore, Carter county. Averaged by J. A. Monroe."

A very dense ore, in curved irregular laminæ of deep bluish and brownish colors, with some dark-brown softer ore between.

No. 1382—LIMONITE, &c. "Main Block Ore with associated overlying Kidney Ore, from Kibby Diggings. Divide between Lost and Tygert Creeks. Carter county. Averaged by J. A. Monroe."

Small nodules of time-granular grey carbonate ore, surrounded by curved irregular laminæ of dense limonite, frequently separated by soft ochreous ore.

No. 1383—LIMONITE. "Rough Ore, one hundred feet above the Foxden Ore (see clay iron-stones), on Means and Russel's land, Cumming's branch of Everman's Creek. Averaged by J. A. Monroe."

In irregular hard thin laminæ of dark-brown to brownishyellow colors; with some soft ochreous ore.

- No. 1384—LIMONITE. "Red Limestone Ore from Graham bank. Average sample from the stock pile, by P. N. Moore." In curved, irregular, hard laminæ; varying in color from yellowish and reddish-brown to deep brown and almost black, with soft, lighter colored ochreous ore incrusting and included.
- No. 1385—LIMONITE. "Yellow Kidney Ore, Mount Savage Furnace, Carter county. Average sample, by P. N. Moore." In irregular curved laminæ, involving nuclei of softer ore. Color varying from deep brown and red to yellowish.
- No. 1386 LIMONITE. "Main Block Ore, Stinson Creek. Mount Savage Furnace. Average sample, by J. A. Monroe." Curved irregular laminæ of dense limonite; generally dark colored, including light-grey nodules of porous carbonate of iron ore.
- No. 1387 LIMONITE. "Ore seventy-three feet above the subcarboniferous limestone. On Clark's branch of Tygert's Creek, two miles from Iron Hills Furnace. Average sample, by P. N. Moore."

Varying from dense, dark-colored limonite laminæ to soft ochreous ore.

As will be seen, on examination of the following table of their composition, these limonite ores of Carter county are generally good, and may be profitably worked with proper management in the smelting; although some of them contain too much sulphur and phosphorus to make very tough iron.

	8	COMPOSITION OF	TION	7	HESE (	ARTE	THESE CARTER COUNTY LIMONITES, DRIED	JNTY	LIMON	IITES,	DRIE	AT	212° F.			-	!
	No. 1371	No. 1371 No. 1372 No. 1374 No. 1375 No. 1376 No. 1378 No. 1379 No. 1379 No. 1380 No. 1381 No. 1382 No. 1383 No. 1384 No. 1385 No. 1385 No. 1387	No. 1373	No. 1374	No 1375	No. 1376	No. 1377	No. 1378	No. 1379	No, 1380	No. 1381	No. 1382	Vo. 1383	No. 13841	No. 1385	No. 1386	10. 1387
		T,			90	7	96.	1	9 93	. 050	71.503	61.316	51.623	71.680 6	66.200	59.347	52.238
Iron, peroxide	91.040	52.400 05.057	05.057	57.090	30. 405	/66./6		_	8.538	_		_	_	:	:	6.20	
Alumina	3.16	7.504	4.921	4.203	5.455	2.727	3.531	_	4.405	5.230	8.557	_	1.671	4.155	3.907	1.957	4.512
Manganese, brown oxide	a trace.			a trace.	. 120	a trace.	.320	380	a trace.	. 580	a trace.	a trace.	a trace.	3.8	o o o o o o o o o o o o o o o o o o o	830	059
Magnesia	910	. 155		086	3,5	965	.065	*254	.883	343	.054	-	.483	050	.345	2.027	9.
Phosphoric acid.	83	1. 224	.893	375	1.93	1.746	8	.038	.337	24.2	8 8	8 8	804	370	183	303	230
Sulphuric acid	not est.	208	8	.391	0.500	11.700	10.700	2.600	9 377	800	9.500	3.545	9.330	10.800	11.730	5.945	10.650
Silex and insoluble silicates.	.68	25.365	17.780	26.760	4.760		31.840 [	37.220	19.480	16.860	4.030	10.780	36.830	12.650	633	19.810	30.580
Moisture and loss	101.	8	•		.304			1				İ	1	1	3	1	
Total	100.00	100.000 100.000 100.635 100.00	100.635	0	100.000	100.760	100.103 100.000		00.00	100.510	100,510 100,000 100.000		100.326	100.159	000.001	100.000	100.119
								1				1					
Per cent. of Iron		57.148 36.722	45.959	39.963	26.799	40.290	36.815	29.816	44.736	41.965	50.051	48.585	36.136	90.176	46.340	45.347	36.566
Per cent. of phosphorus	900.	.534	196.	191.	·+36	.762	.344	.013		.367	.203	260.	SE0.	.o36	.057	990	.740
Per cent. of sulphur	:	,107	.241	.156	060.	<b>≯</b> Lo∵	890.	160.	90.	.335	.320	fo+.	.163	. I	.072	021.	160:
Per cent. of silica		net est. 23 980	15.960	22	, og6.0t	not est.	27.360	:	:	16.860	7.640	9.960	:	11.560	13.860	15.060	34.260
	1	-											-				

#### LIMESTONES OF CARTER COUNTY.

No. 1388—"Limestone used as a flux at Boone Furnace when in operation. Collected by P. N. Moore."

A hard, compact, light buff-grey limestone. Fracture somewhat conchoidal.

No. 1389—"LIMESTONE (sub-carboniferous) to be used as flux by the Iron Hills Furnace. Averaged by P. N. Moore."

A compact or fine granular limestone, of a light-grey color.

No. 1390—"LIMESTONE used as flux at Mount Savage Furnace.

Average sample, by J. A. Monroe."

A compact limestone of a dark-grey color, mixed with fragments of ferruginous sandstone and chert.

COMPOSITION OF THESE LIMESTONES, DRIED AT 212° F.

	No. 1388.	No. 1389.	No. 1390.
Specific gravity	2.624	2.700	not est.
Lime carbonate	97.720	95.150	75.750
Magnesia, carbonate	not est.	.245	- 575
Alumina, and iron and manganese oxides	. 300	1.390	6.403
Phosphoric acid (anhydrous)	.083	. 130	.057
Sulphuric acid (anhydrous)	not est.	a trace.	-775
Potash	.115	not est.	not est.
Soda	. 167	not est.	not est.
Silica and insoluble silicates	1.560	3.060	14.700
Soluble silica	. 120	not est.	*1.740
Total	100.065	99-975	100.000
Per centage of lime	54.723	53.284	42.420
Per centage of phosphorus	•.036	.056	.032
Per centage of sulphur	not est,	a trace.	.310

<sup>\*</sup> Water and loss.

Nos. 1388 and 1389 are very pure limestones, and very suitable for use as flux in the iron furnace; but No. 1390 is quite objectionable, because of its considerable proportion of sulphur, and its nearly fifteen per centage of silicious matters.

# PIG IRONS OF CARTER COUNTY.

No. 1391 — Pig Iron. "Foundry No. 2, made at Boone Furnace, Carter county, in 1870."

A brilliant grey iron; moderately coarse-grained. Yields to the file; but breaks readily under the hammer.

No. 1392—Pig Iron. "Foundry Iron No. 1, made at Boone Furnace in 1870."

Darker colored, somewhat finer-grained, and softer than the preceding; flattening somewhat under the hammer.

No. 1393—Pig Iron. "Hot Blast, No. 1 Foundry ("sow"), Iron Hills Furnace, Carter county. Collected by P. N. Moore."

Rather coarse-grained; with brilliant grains. Yields to the file, but is somewhat hard. Flattens but little under the hammer.

No. 1394—Pig Iron. "Hot Blast, No. 1 Foundry, Mount Savage Furnace. Collected by P. N. Moore."

A brilliant coarse-grained iron. Hard, but yields to the file. Extends but little under the hammer.

	No. 1391.	No. 1392.	No. 1393.	No. 1394.
Specific gravity	. 6.423	6.905	7.021	6.889
Iron	. 90.958	93.212	92.387	91.502
Graphite	. 2.164	2.940	3.340	2.670
Combined carbon	116	.060	.760	.030
Manganese	115		.056	. 123
Silicon	. 2.682	1.634	2.240	4.470
Slag	. 4.180	2.460	.620	1.160
Aluminum	. 479	.330	. 120	. 128
Calcium	not est.	not est.	.120	.144
Magnesium			.056	.112
Potassium			.080	.076
Sodium				.023
Phosphorus		.486	.836	.203
Salphur	. not est.	.079	.057	.041
Total	. 100.998	101.284	100.672	100.680
Total carbon	. 2.280	3.000	4.100	2.700

# SOILS OF CARTER COUNTY.

No. 1395—Soil. "From the farm of Jas. W. Scott, near Lower Tygert bridge, near Olive Hill, Carter county. Top soil in oak woods, sixty feet above the bed of the creek. Limestone slope southward. Drainage between the slope and the sandstone capping the hills. Sample to depth of six inches. Collected by Prof. N. S. Shaler."

Virgin soil. Soil of a greyish orange-buff color, with streaks and mottlings of dark-grey. Compacted into clods in the bag. The coarse sieve (289 meshes to inch) removed about six per cent. of ferruginous and decomposing cherty fragments.

No. 1396—Soil. Labeled "Sub-soil of the preceding, one foot below the surface, &c."

This sub-soil is of an orange-red, or bright red ochre color. Compacted into clods in the bag.

The coarse sieve removed from it a very small quantity of small fragments of weathered chert, &c.

No. 1397—"Soil from the farm of Jas. W. Scott (locality as above). Old field, in pasture for eighteen, and cultivated for five years. Slope from height of limestone bench and sandstone beyond. Northern exposure, thirty feet above Tygert Creek. Collected by N. S. Shaler."

Soil of a dirty-grey buff color. Sifted out about five per cent. of cherty and ferruginous small fragments, with the coarse sieve.

No. 1398—"Sub-soil of the next preceding, one foot below the surface, &c."

Sub-soil colored like next preceding; slightly more reddish. Sifted out, with the coarse sieve, about twenty-three per cent of small fragments, more or less rounded, of ferruginous sand-stone, iron ore, and weathered chert.

No. 1399—"Top Soil. Woods near Iron Hill, Carter county. From eastward slope, ravine to southward. Limestone above, twenty-five feet thick. Conglomerate still above. Oak and beech woods, about one hundred feet above Tygert Creek. Collected by J. A. Monroe."

Soil of a grey-buff color. Sifted out, with the coarse sieve, about sixteen per cent. of shaly ferruginous sandstone fragments.

No. 1400—"Sub-soil of the next preceding, taken eighteen inches below the surface, &c., &c."

Sub-soil of a lighter color than the surface soil and more adhesive. Contains fragments of sandstone.

No. 1401—"Top Soil, for six inches below the surface, from an old field on Riggs' farm at Iron Hills. From the slope of hill toward Tygert Creek. Limestone one hundred feet or more above, and sandstone above that. Woodland a few rods off to top of the hill. This field has been cultivated in corn for many years." Collected by J. A. Monroe.

Soil of a grey-buff color. Sifted out of it, with the coarse sieve, about twenty per cent of fragments of ferruginous sand-stone, &c.

No. 1402—"Sub-soil of the next preceding, taken eighteen inches from the surface, &c., &c."

Of a handsome yellowish-buff color. Compacted into friable lumps in the bag. Sifted out, with the coarse sieve, about ten per cent. of fragments of ferruginous sandstone and iron ore.

No. 1403—"Surface Soil, from woodland on farm of William Abbott, five miles west of Olive Hill, Carter county. One hundred and fifteen feet above the west branch of Tygert's Creek. Slope northwest. Limestone on top of the hill. Collected by A. R. Crandall."

Soil of a grey-buff color. The coarse sieve removed a considerable quantity of small ferruginous and cherty fragments. No. 1404—"Sub-soil of the next preceding. One foot from the surface, &c., &c. Collected by A. R. Crandall."

Of a buff color. Contains angular fragments of ferruginous sandstone.

No. 1405—"OLD FIELD SOIL. Farm of William Abbott, west branch of Tygert's Creek, &c. Field fifty-five feet above the bed of the creek; on bench of Waverly sandstone. Tops of the hills capped with limestone. Surface soil; has been cultivated sixty years; was once an orchard." Collected by A. R. Crandall.

Soil of a light grey-buff color; aggregated into friable clods in the bag. The coarse sieve removed from it less than two per cent. of small silicious sandstone, cherty, and ferruginous fragments.

No. 1406—"Sub-soil of the next preceding; one foot below the surface, &c." Collected by A. R. Crandall.

Sub-soil of a lighter and more clear buff color than the surface soil; contains less than two per cent. of small cherty and ferruginous gravel.

No. 1407—Soil from an old field on Widow Garvin's farm, four miles west of Olive Hill. Ten feet above the bed of Tygert's Creek. On Waverly sandstone; with limestone and coarse sandstone near the tops of the hills. Surface soil. Collected by A. R. Crandall."

Soil of a grey-buff color, contains about four per cent. of small rounded ferruginous sandstone and cherty fragments.

No. 1408—"Sub-soil of the next preceding, one foot to eighteen inches below the surface. Collected by A. R. Crandall."

Sub-soil of a lighter color than the preceding surface soil; in friable clods.

Sifted out, with coarse sieve, about eight per cent. of ferruginous, cherty, and sandstone fragments. No. 1409—Soil. Labeled "Sub-soil of bottom land, two feet from the surface; twenty-five feet above Little Sandy river, Grayson, Carter county. The surface soil was not collected on account of accidents affecting its composition." Collected by Prof. N. S. Shaler.

Sub-soil of a light buff-grey color; nearly white; in friable lumps. Seems to be mainly composed of fine grains of sand.

COMPOSITION, DRIED AT 212° F.

#### 

 Sulphuric acid
 ...
 not est.

 Potash (total obtained by fusion)
 ...
 ...

 Soda (total obtained by fusion)
 ...
 ...

 Silica (separated by fusion)
 ...
 84.000

 Loss
 ...
 ...

100.000

This sub-soil having been analyzed by fusion with the mixed alkaline carbonates, and not by digestion in chlorohydric acid, as the other soils of this county were treated, could not be tabulated with them.

The proportions of potash and soda given above appear large, as compared with those found in similar sandy soils by digestion in acids; but these represent the *total amount* of these alkalies, contained not only in the soluble portion of the soil, but also in the insoluble silicates; the process of J. Lawrence Smith for the separation of the alkalies from silicates, viz: fusion with a mixture of lime carbonate and ammonium chloride, having been employed in the above analysis.

COMPOSITION OF THESE  Extracted from 1000 parts of	F THESE	CARTE	'R COUN	E CARTER COUNTY SOILS AND SUB-SOILS, DRIED AT 21 of the air-dried soil, by dignition in water containing carbonic acid in solution.	S AND in water co	SUB-SOILS, DRIED	LS, DRI) rbonic acia	ED AT 212° in solution.	12° F.		
	No. 1395.	No. 1396.	No. 1397.	. No. 1396. No. 1397. No. 1398. No. 1399. No. 1400. No. 1401. No. 1402. No. 1405. No. 1406. No. 1407.	No. 1399.	No. 1400.	No. 1401.	No. 1402.	No. 1405.	No. 1406.	No. 1407.
Organic and volatile matters	0.500	0.420	00.500	0.370	lost.	0.350	1.120	0.320	0.700	0.340	8.8
Alumina, oxide of iron, and phosphoric acid	.030	010	010.	010	lost.	.020	lost.	.020	lost.	.020	.070
Brown oxide of manganese	.050	010.	% %	.030	lost.	.030	lost.	.020	lost.	.020	.290
Lime carbonate	.710	.130	99.	.330	lost.	.300	lost.	90.	lost.	040	.720
Magnesia	.040	010.	.050	.020	lost.	.020	lost.	.030	lost.	.020	8
Phosphoric acid	not est.	not est.	not est.	not est.	lost.	not est.	lost.	not est.	lost.	not est.	not est.
Sulphuric acid	a trace.	a trace.	a trace.	a trace.	lost.	a trace.	lost.	a trace.	lost.	a trace.	a trace.
Chorine	a trace.	a trace.	a tmce.	a trace.	lost.	a trace.	lost.	a trace.	a trace.	a trace.	a trace.
Nitric acid	not est.	not est.	not est.	not est.	lost.	not est.	lost.	not est.	lost.	not est.	not est.
Potash	8.	8	œ.	.050	lost.	.040	lost.	.040	lost.	.050	.050
Soda	.050	.030	.030	.040	lost.	010.	lost.	a trace.	lost.	.020	.020
Soluble silica	.070	80.	011.	.050	lost.	.030	lost.	.020	.030	.030	.020
ross ssor	<u>%</u>	:	.130	.120	lost.	.020	lost.	90.	lost.	: :	:
Total extract, dried at 212º F	1.600	0.770	1.660	1.020		0.820	2.870	0.570	1.180	0.540	2.070
Color of extract	Dark brown.	Brownish white.	Dark umber.	Brownish grey.	:	Yellow- ish-white	Umber (dark).	Yellow- ish-white	Brownish Brownish white,	Brownish white.	Dark umber.

GENERAL COMPOSITION OF THESE CARTER COUNTY SOILS, DRIED AT 3130 F

	CEN	EKAL C	GENERAL COMPOSIT	NO	OF THES	E CAR	HESE CARIER COUNTY		SOILS, D	DRIED A	A.T. 212° I	Ŧ.		
	No. 1395.	No. 1395. No. 1396. No. 1397.		No. 1398.	No. 1399.	No. 1400.	No. 1401.	No. 1402.	No. 1403.	No. 1404.	No. 1405.	No. 1406.	No. 1407.	No. 1408.
Organic and vol. matters.	3.110	*.800	2.250	1.815	4.165	2.200	3.925	3.315	4.685	2.625	2.860	2.000	3.740	3.900
Iron peroxide	7.405	17.360	4.777	6.409	7.595	8.406	6.637	8.375	4.013	5.410	4.540	5.890	6.115	5.600
Lime carbonate	.430	.270	88.	.680	.320	.155	.18	\$60.	601.	601.	.145	80.	.245	.330
Magnesia	575.	124	750.	.076	88.0	143	.051	.153	.050	190.	.035	101	.115	980
Sulphuric acid	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	90.	940.	not est.	not est.	Bot cst.	not est.
Soda	148	. 149	.132	. 151	.186	 	. 163	. 273	.032	.371	.111.	. 204	286	98.8
Soluble silica	- 1	\$60.	not est.	. 145	. 245	.160	.145	. 145	not est.	not est.	.230	050	.330	130
Sand and insol'ble silicates	87.630	74.840	91.600	90.515	85.465	87.340	88.140	87 740	89.515	89.940	91.240	91 575	89.390	91.215
water expelled at 380° F.		1.400	8 .	<u>ş</u> :	34:	.30g		. 158	99. 24.	.459	& ·			os +: -:
Total	100.393	100.000	100.692	100.681	100,000	100.000	100.538	100,000	100,000	100 000	100.123	100.569	101.294	100.483
Moisture lost at 2120 F	2.020	2.354	1.125	1.270	1.945	1.400	1.475	1.405	1.380	1.270	1.215	1.975	1.350	1.035
Potash in insol'ble silicates	+85·	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n st est.	not est.	not est.	not est.
Soda in insoluble silicates	. 165	not est.	not est.	not est.	not ext.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.
Character of soil Virgin soil Sub-soil.	Virgin soil		Old field.	Sub-soil.	Virgin soil	Sub-soil.	Old field.	Sub-soil.	Virgin soil	Sub-soil.	Old field.	Sub-soil.	Old field.	Sub-soil.

Although these Carter county soils cannot be classed with the naturally very rich soils, there is no apparent reason, in view of their composition, why they may not be made quite profitably productive, under proper culture and by the observance of the golden rule of agriculture viz: to restore to the soil in manures, &c., the essential ingredients which are removed from it in the crops. These soils are measurably deficient in humus or organic matters, and contain rather more than the normal proportion of sand and silicates. These defects may be remedied in some localities, where the sub-soil contains more clay, &c. (as is the case with No. 1396), by gradually bringing up the sub-soil, in the annual plowings, with the simultaneous use of clover and other green crops. It appears also from the analyses, that while lime and potash seem to be in sufficient abundance, phosphoric acid is rather deficient in most of these soils. The use of bone-dust, or other phosphatic fertilizers, would doubtless be beneficial.

The influence of cropping on the composition of the soil may be measurably observed by comparing the analyses of the virgin soils and the old field soils, as given above. In all the proportion of organic matters is found to be reduced, and that of the sand and silicates increased, in the old field, as compared with the virgin soil; and in most of them a reduction in quantity may be seen in the potash and phosphoric acid of the old field; showing the exhausting influence of cropping without the use of manures.

## EDMONSON COUNTY.

No. 1410—LIMONITE. Labeled "From Bythe Meredith farm. Collected by Prof. N. S. Shaler (Nolin)."

Composed partly of elliptical hollow concretions of dense dark reddish-brown laminæ, with some softer ochreous ore.

No. 1411—LIMONITE. Labeled "Proctor Ore Bank, Sycamore Creek. Collected by Prof. N. S. Shaler and J. R. Proctor."

Principally in dark brown dense laminæ, forming an irregular stalactitic, hollow columnar structure with septæ (or irregularly large cancellated), incrusted with some softer yellowish and brownish ochreous ore.

No. 1412—LIMONITE. Labeled "Frederick's Bank, Beaver Dam Creek. Two hundred feet above the limestone. Collected by Prof. N. S. Shaler. (Five feet ore. Uniform.")

Generally of a yellowish-brown color, porous and cellular; but with some dark hard laminæ, small whitish oölitic concretions some of which are hollow, and brownish and yellowish ochreous material. Contains some fossil shells, &c.

COMPOSITION OF THESE EDMONSON COUNTY LIMONITE ORES, DRIED AT 212° F.

										_		_				
														No. 1410.	No. 1411.	No. 1412.
Iron, peroxide	_		_			_	_				_			55.028	76.284	52.926
Alumina														1.006	2.361	4.792
Manganese, brown oxide .														.040	.030	.210
Lime carbonate			0	0		-	_		0	-	-	-		a trac :.	.180	.180
Magnesia							•	-	-		0.5			.108	.068	.425
Phosphoric acid	•	•	•	•	•	•	•	•	•	•	•	•		.312	1.055	-355
Sulphuric acid	•		•	•	•	•	•	•	•	•			•	.133	.151	
Water expelled at red heat.	•	•	•	•	•	•	•	•	•	•	•	•	•	8.300	12.000	. 143
Silar and insoluble silicator	•		•	•	•	•	•	•		•	•	•	•		1000000000000000000000000000000000000	10.400
Silex and insoluble silicates		•	•	•	•	•	•		•	•	•	•	•	35.180	7.951	30.580
Total	•					ૃ				•		٠	•	100.107	100.080	100.011
Iron, per centage			•	•				•			•		-	35.519	53 · 399	37.048
Phosphorus, per centage						•								.135	.460	. 154
Sulphur, per centage		•		•	•									.053	.059	.057
Silica, per centage			•										•	33.700	7.660	29.160

These are good iron ores. No. 1411 is more than usually rich in iron, but it contains more phosphorus than is desirable.

[See Appendix for other iron ores of this county.]

No. 1413—Coal. "From Tar Lick, Davis Creek, Edmonson county. Five and a half feet thick. Collected by Prof. N. S. Shaler."

A glossy splint coal, breaking into thin irregular laminæ, with tar (petroleum) and fibrous coal—the remains of reedy leaves—and more or less fine-granular pyrites between them.

No. 1414—Coal. "Found on Mill branch. Level of main Nolin coal. Collected by Prof. N. S. Shaler."

Splint coal. Separates under the hammer into thin irregular laminæ, with fibrous coal, containing fine-granular pyrites between.

- No. 1415—COAL. "Found on the surface. Has been longer exposed and more weathered than the preceding. Mill branch. Collected by Prof. N. S. Shaler."
- No. 1416—Coal. "From Knob Lick, Dismal Creek. Geological level of main Nolin coal. Collected by Prof. N. S. Shaler."

A weathered specimen of splint coal, incrusted with ochreous iron oxide on the surface. Separating into thin irregular laminæ, with fibrous coal between.

No. 1417—COAL "At Gross', one hundred and eighty feet above Bear Creek, Collected by Prof. N. S. Shaler and J. R. Proctor."

A splint coal, breaking into thin irregular laminæ, with fibrous coal and much fine-granular pyrites between.

No. 1418—COAL. "Shoal branch, Nolin coal. Collected by Prof. N. S. Shaler and J. R. Proctor."

Splint coal, breaking into thin laminæ, with fibrous coal and but little pyrites between them.

No. 1419—COAL. "Tar Lick Coal, branch of Davis. (Main Nolin coal.) Collected by J. R. Proctor. Five and a half feet thick."

A deep-black coal, with soft bituminous matter between the thin laminæ, and but little fibrous coal or pyrites. No. 1420—Coal. "From Mill branch of Bear Creek. Average sample, by P. N. Moore."

Much of it breaks into thin laminæ, with but little fibrous coal, and some fine-granular pyrites between.

COMPOSITION OF THESE EDMONSON COUNTY COALS, DRIED AT 212° F.

	No. 1413	No. 1414	No. 1415	No. 1416	No. 1417	No. 1418	No. 1419	No. 1420
Specific gravity	1.282	1.350	1.367	1.345	1.429	1.336	1.335	1.437
Hygroscopic moisture	2.30 32.10 65.60	3.60 33.00 63.40	3.20 33.80 63.60	2 60 33.80 63 6)	1,20 39.00 59.8.	3.66 35.14 61.20	4.06 33.24 62.70	4.06 32.00 63.94
Total	100,00	100.00	100-00	100.00	100.00	100.00	100.00	100.00
Total volatile matters	35.42 56.30 9.30	36.60 54.40 9.00	37.00 52.6, 10 40	36, 40 53, 14 10, 46	40.20 45.46 14.34	38.80 54.26 6 94	37.30 51.70 11.20	36.06 50.84 13.10
Character of the coke	Cellular	Spongy.	Moder- ately dense.	Spongy	Dense	Light cellular.	Spongy.	Light spongy.
Color of the ash	Light li- lac-grey		Lilac- grey.	Light- grey.	Dark greyish- purple.	Lilac- grey.	Light lilac- grey.	Grey- lilac.
Per centage of sulphur	1.059	y. 101	2.923	2.425	8.685	2.706	1.670	4.938
Per centage of phosphoric acid	not est.	not est.	not est	not est.	0.178	not est.	not est.	not est.

These Edmonson county coals answer very well for the ordinary purposes of fuel, and those which do not contain an inordinate quantity of sulphur will doubtless answer well for the working of iron. No. 1417, however, contains more than eight per cent. of this ingredient, and more than fourteen percent. of ashes, containing a notable proportion of phosphoric acid. Yet even this impure coal contains more than eighty-four per cent. of combustible matters, including part of the sulphur (some of which, however, remains in the ashes combined with iron), and may answer for ordinary fuel.

[For other Edmonson county ores, see Appendix.]

CAST IRON from Baker Furnace. Some fragments from this old furnace, which had been exposed to the weather for twenty.

years, were collected by Prof. Shaler, for examination of its general quality.

It is a fine-grained, light-grey iron, which is more tenacious and extends more under the hammer than most samples of best pig iron. Possibly it has been improved in this respect by its long weathering in thin pieces. The analysis of a piece of the pig iron from this furnace will be found in the Appendix.

[For Nos. 1421, 1422, and 1423, see Barren county.]

#### FAYETTE COUNTY.

No. 1424—"Surface Soil to depth of one foot, of a field which has not been very long in cultivation, principally in hemp, of which it no longer produces very good crops. Blue-grass land, seven miles from Lexington on the Newtown Turnpike. Substratum, Lower Silurian blue limestone. Land of E. M. Coleman." Why is it not very good hemp land?

Soil of a light greyish-brown color. It all passed through the coarse sieve, of 289 meshes to inch, except a small proportion of shot-iron ore and irregular fragments of chert.

No. 1425—"Soil to the depth of four inches from an old field fifty years or more in cultivation almost without intermission, without manure of any kind, principally in hemp and corn, with occasionally small grain. Farm of R. Peter, formerly of the late Col. S. Meredith, on the Newtown road, six and a half miles from Lexington; blue-grass land. Sub-stratum, blue limestone of the Lower Silurian formation."

Soil of a warm grey-brown color; containing only a few small angular fragments of weathered and porous chert.

This field was selected by my son, Benj. D. Peter, for some experimental agricultural operations, which he has reported to Prof. Shaler.

COMPOSITION OF THESE FAYETTE COUNTY SOILS, DRIED AT 212° F.

	No. 1424.	No. 1425.
Organic and volatile matters	6.340	6.575
Alumina, and iron and manganese oxides	8.890	8.200
Limoe carbonate	-745	.440
Magnesia	. 366	, 221
Phosphoric acid	. 550	.316
Sulphuric acid	.065	.036
Potash	.100	. 247
Soda	.057	. 263
Sand and insoluble silicates	81.467	
Water and loss	1.556	. 362
Total	100.000	100.000
Potash in the insoluble silicates	0.905	1.256
Soda in the insoluble silicates	.844	. 101

The apparent paucity of potash in No. 1424 may account for its failure to produce good hemp crops.

As compared with the original virgin soil of the same locality, these soils contain much less organic matters (humus), and a smaller amount of potash, than that. These essential materials are especially influential in hemp production, as the presence of these and of lime seems to be necessary to a vigorous growth of this plant; the only kind of growth considered profitable by our farmers.

The current belief amongst our hemp-growers is, or has been, that this crop does not rapidly exhaust the soil, provided the hemp is spread for rotting on the field which produced it.

The rotting process does undoubtedly restore to the soil, in an available condition for plant nourishment, a considerable proportion of the fertilizing principles which had been withdrawn from it in the crop; but in the operation of braking the hemp, the hemp herds and rough tow being generally burnt on the spots where the process is performed, the alkaline and earthy ingredients of these become irregularly deposited, and much of the soluble fertilizing mineral matter of the ashes is liable to be washed down into the sub-soil, to become for the time unavailable; while a large quantity of vegetable matter, which ought to be employed in returning to the soil the humus, which has been destroyed during the growth of the crop, is converted into atmospheric gases by burning.

The adoption of some plan by which our hemp-raisers may restore the organic matter of the hemp herds, &c., to the soil, in the form of humus, would tend to retard the exhaustion of the hemp land. But there exists a prejudice among them that hemp herds are injurious to the land, which is probably not based upon fact.

The insoluble silicates left after thorough digestion of these soils in warm chlorohydric acid assisted by a little nitric acid, was found upon analysis by fusion, to contain quite a large proportion of alkalies. In both cases these silicates contained about five times as much potash as was dissolved out from the soils by the acids. This quantity of the alkalies, in combination in the insoluble silicates, so-called, is not immediately available for plant nourishment, but yet serves to prolong the fertility of the soil; for these silicates, although not easily decomposable by acids, are gradually decomposed by the atmospheric agencies, and especially under the influence of alkaline substances.

Hence the application of lime, for instance, to soil of this kind, which has been measurably exhausted of its immediately available alkalies, may, by partial decomposition of these silicates, bring more of these alkalies into a soluble condition, and thus temporarily increase its fertility.

These insoluble silicates, left after the acid digestion, when examined with the lens, exhibit small grains, which look like partly decomposed feldspathic mineral, sometimes of different tints, mixed with minute rounded or angular grains of hyaline and milky quartz, &c.

These facts, especially that of the existence of so much potash and soda in these insoluble silicates of the soil, throw some light on the origin of soils; as they tend also to aid us in scientific agriculture. No. 1426—Quicklime, obtained by the calcination of limestone of some of the fossiliferous layers of the blue limestone of the Lower Silurian formation. Cliff on Elkhorn Creek, northeast boundary of the above named farm. Also some milky calcareous spar, from a four to six feet wide vein at the same locality, which was mixed and calcined with the limestone.

This lime, not perfectly calcined, was used on the experimental field above mentioned.

Its composition was found to be as follows:

						5-5-5						0000		04/04/6	500			1000					
Lime																							68.804
Magnesia																							.241
Alumina, and iron	an	d i	ma	ng	gar	es	e	OX	id€	s .													4.565
Phosphoric acid																•							.415
Sulphuric acid																				•			.446
Carbonic acid							٠																11.450
Potash																							1.330
Soda																							.099
Silex and insoluble	si	lica	ate	s.																			6.130
Water and loss		•							•		٠		•			•				•	•		6.520
Total							•		٠											٠			100.000
												82	5 S										

This lime was not submitted to analysis until after it had been exposed to the air for a few days.

It will be seen from this analysis, that lime from these fossiliferous layers of our limestone may prove a valuable fertilizer, on fields which have been impoverished by too much cropping. For, not only will it, by its decomposing action on the insoluble silicates, render a new quantity of alkalies available for plant food, but its own considerable proportions of phosphoric and sulphuric\* acids, and of potash and soda, will greatly aid in the amelioration.

No. 1426—CALCAREOUS SPAR (above mentioned) from the vein, nearly vertical, in the blue limestone on North Elkhorn Creek, land lately belonging to R. J. Breckinridge's estate (Bradalbane).

Analyzed by my son, Alfred M. Peter, as was also the quicklime.

<sup>\*</sup>The considerable proportion of sulphuric acid given in the preceding analysis is probably partly derived from iron sulphide sometimes diffused in this limestone.

### COMPOSITION, DRIED AT 212° F.

Lime carbonate	96.610 = 54.101 per cent. of lime.
Magnesia, carbonate	.401
Alumina, and iron and manganese oxides	1.740
Phosphoric acid	.057
Sulphuric acid	
Potash	
Soda	.275
Silica and insoluble silicates	
Loss	.114
	100.000

This nearly opaque, milky calc. spar is much stained superficially with iron oxide, &c. The analysis shows a much smaller amount of phosphoric acid than is contained in the limestone layers; but the proportion of alkalies, if no error is made, is quite considerable.

#### WATERS OF FAYETTE COUNTY.

As is well known, the spring and well waters of this blue limestone region are what are denominated "hard waters," containing a considerable quantity of dissolved carbonates of lime and magnesia, &c.

As a type of these limestone waters, that of a remarkable spring, the "Big Spring," on the writer's farm, about six and a half miles from Lexington, on the Newtown Turnpike, was selected for chemical analysis.

This "Big Spring" is a perennial stream of considerable force, boiling up in the bottom of a sink-hole, which is some fifty to sixty feet deep, and flowing through underground channels and caverns a considerable distance, to be discharged into the North Elkhorn Creek.

The water was taken after the long dry season of our late summer and autumn, and was remarkably clear; as it always is except after heavy rains. The temperature of it was noted during one of our late protracted cold spells; and when the temperature of the atmosphere was at zero and only ten degrees above, it maintained that of fifty-three or fifty-four; very little below the mean of the temperature of this region.

The analyses of this water and of the waters of the bored wells given below, were made by my youngest son Alfred

Meredith Peter, under my inspection, as a chemical exercise, and were very carefully and faithfully performed.

The results show that the hard waters of our springs and wells might not only be fertilizers, when used for irrigating growing crops, but that, as was first noted by the celebrated Boussingault, they may supply to growing animals necessary earthy salts which may be deficient in their food. That, especially, they may supply lime to animals fed on Indian corn, which food is found to be somewhat deficient in this ingredient.

#### COMPOSITION OF THE BIG SPRING WATER IN 1000 PARTS.

No. 1427.																								Held in solution by free carbonic acid.
Lime, carbonate																								0.2027
Magnesia, carbonate .																								.0227
Iron, carbonate																								.0027
Manganese, carbonate																								.0003
Alumina																			•					.0012
Phosphoric acid																-0								10001
Silica		•	٠	٠	٠			٠		٠	٠	٠	٠	•	٠		٠	٠	•	•	٠	٠	٠	1100.
Total of sediment fo	rm	iec	ic	on	bo	oili	ing		•	•	•	•	٠	٠	٠	*	•	٠		٠	٠	٠	٠	0.2308 Contained in the boiled water.
Lime, sulphate	100	5 <u>2</u> 70		20	121	12	002	7727			0		-2		2			32	102			20		
Potassium, chloride .				Ī	÷	-		_		-	-	-	-				-	-				-		.0012
Sodium, chloride																								_
Magnesium, chloride.																								
Silica																								
Organic matters																								
Lithia																								
Total saline matters																								0.2733

The total saline matters amount to about sixteen grains to the wine gallon of water. They are doubtless derived from the soil and the limestone rock.

As was stated in the previous volumes of Kentucky Geological Reports, the water obtained in this region by boring into the limestone substratum is always more or less salt, and is frequently accompanied with gas (carburetted hydrogen), the flow of which, however, is not very durable. During the late very dry season a number of borings were made in this neighborhood (near Lexington), with the same results; the water smelling strongly of petroleum, and sometimes of sulphuretted hydrogen, being always more or less brackish, and there being generally a temporary emission of gas.

The waters of three of these bored wells were analyzed by my son (A. M. Peter), with the following results, viz:

No. 1428—"Water from a bored well of Mr. Sutton's, about ninety-eight feet deep, on the Leestown road, near the Scott county line."

A weak sulphur water.

No. 1429—"Water from a bored well of Mr. Edward P. Gains, about one hundred feet deep, on the Georgetown Turnpike, about nine miles northwest of Lexington, near Donerail."

The water rose about thirty feet in the well. Specific gravity = 1.035.

No. 1430—"Water from a bored well, about ninety-six feet deep, on the farm of Mr. Price McGrath, two and a half miles from Lexington, on the Newtown Turnpike."

The water rose to within about twenty-eight feet of surface. Gas was evolved in considerable quantities during the boring.

# COMPOSITION OF THESE WELL WATERS.

Held in	solution	by	free	car	bonic	acid.

	_		-		Hei	<b>a</b> 1	a s	olu	цоп	4 0	y 11	-	ca	rDO	סומכ	ac	ıd.		
																N	No. 1428.	No. 1429.	No. 1430.
Lime, carbonate					_	_	_									Γ	0.1008	0.0104	0.171
Magnesia, carbonate .	-	- 0		٠.			-			•	-	•		•		١	.0882		.005
Iron, carbonate												•	:: :-			1	.0042	.0008	.006
Manganese, carbonate											-					١.			.000
Phosphoric acid	-				0 E		-				-	-				1	a trace.	Acceptance from the transfer of the	.000
Silica		•															.0078		.001
Total sediment on be	oili	ing								•							0.2010	0.0168	0.1850
Line sulphete																Π		2 6462	
Lime, sulphate			٠	•		٠		•	•	•	•	•	٠		•	١.		0.6263	0.030
Magnesia, sulphate	•	٠	•	•		٠		•	•	•	•	•	•	•	•	1	0.0541		
Potash, sulphate	•	•	•	•	•	•	•	•	•	٠	•	٠	٠	•	•	ı	.0355		
Soda, sulphate	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	1	.0600		
Soda, carbonate	٠		•	•	•	•	•	•	•	•	•	•	٠	•	•	1	. 1448		
Calcium, chloride.			•			•	•		•	•		•	•			١.		3.0246	-579
Magnesium, chloride.		•		•	•	•	•	•	•	•	•	•	•		•	ŀ			.783
Sodium, chloride																	1.9409	34.4313	
Potassium, chloride		•	•	•				•	•	•	•		•			J٠		.1883	.1120
Magnesium, bromide.						•	•	•	•		•	•	•		•	١.		.0157	a trace
	- 23															١.		.0096	a trace
Magnesium, iodide	•											333		-			a trace.	.0181	
Magnesium, iodide Lithium, chloride		•	•	•	•	•	•	•	•	•	•	•	૾ૼ	•	-	L		.0101	a trace

The water from Mr. Sutton's well smells strongly of hydrosulphuric acid; which was not estimated, because this could only be done correctly at the well. All these waters contain, in addition, a little organic matter, and a little silica in the boiled water.

The amount of saline matters in Mr. Gains' well water is remarkable, being about five ounces and a half to the wine gallon. The saline matters in quantity and in kinds resemble those of the oceans; and doubtless had their origin in the ancient sea under which our rock strata were deposited.

Another well bored by Mr. Wm. Adams, on his farm next adjoining that of Mr. McGrath, gave water at the depth of about seventy-eight feet; which rose fifty feet in the bore. Much gas was blown out during this boring also.

The water of this well contained 0.54 of saline matter in the thousand of the water; which, tested qualitatively, was found to contain sulphuric, carbonic, and phosphoric acids, chlorine, lime, magnesia, potash, iron oxide, and a trace of lithium. It doubtless resembles that of Mr. McGrath, but is weaker. It, like that, smells strongly of petroleum.

Mr. Jno. Keiser bored to the depth of about two hundred and sixty feet, on an elevated ridge on his farm, about six miles from Lexington, on the Newtown Turnpike, and obtained only a very small quantity of brackish water, which gradually rose to within sixty feet of the surface. Some of the borings, taken at various depths, were preserved for examination. They indicate the usual layers of limestone, with thin marly shales and occasional silicious beds, of the formation in this region.

#### FRANKLIN COUNTY.

No. 1431—"Green Marly Shale from below the Arsenal at Frankfort. Bed about eight inches thick (Upper Cambrian Group). Collected by Prof. N. S. Shaler."

A friable shale of a greyish-green color.

No. 1432—"MARLY SHALE. Same locality as the preceding, but lying above that. Collected by N. S. Shaler."

Quite friable. Of dull olive and brownish colors.

No. 1433—"MARLY SHALE. Used as a paint at Frankfort, &c. Sent by Mr. James L. Sneed for analysis."

Of an olive-grey color, with some brownish-yellow mixed.

No. 1434—"MARLY SHALE. From Armstrong farm, Bridgeport. Geological position Cincinnati Group, just below the
silicious mudstone. In same position as the marl near Newport. Collected by Prof. N. S. Shaler." Used for paint.
Said to be good for polishing iron, &c."
Of a handsome light olive-grey color.

COMPOSITION OF THE FIRST TWO OF THESE MARLY SHALES, DRIED AT 212° F.

	No. 1431.	No. 1432.
Alumina, and iron and manganese oxides	10.415	15.395
Lime, carbonate	1.440	*.875
Magnesia	.800	2.298
Magnesia	-435	.460
Sulphuric acid		.570
Potash	3.488	3.565
oda	.042	.318
Water expelled at red heat	5.350	6.400
ilex and insoluble silicates	77.380	70.060
Total	100.088	99.941
Per centage of potash in the silicates	4.991	3.565
Per centage of soda in the silicates	.654	.430

<sup>\*</sup> Lime

These marly shales are remarkable for their large per centage of potash; which probably may make them valuable for application to exhausted land of a light and sandy nature. A previous moderate calcination with lime intimately mixed, might, if practicable, make them more available in this respect by setting free more or less of the potash locked up in the insoluble silicates. It will be seen that No. 1431 contains in

all, as much as 8.479 per cent. of potash, and No. 1432 a total amount of 7.130 per cent.

These, and similar marly shales, have been used as pigments; for which purpose they are quite appropriate, if of an agreeable tint, as they will not decompose the oil with which they are mixed, are not readily altered by atmospheric agencies under such conditions, and contain nothing of a poisonous nature. Their use for scouring or polishing depends on the very fine silicious sand contained in them.

COMPOSITION OF THE LATTER TWO OF THESE FRANKLIN COUNTY MARLY SHALES, DRIED AT 212° F.

																									No. 1433.	No. 1434.
Silica																									50.360	52.060
Alumina																									16.816	18.831
fron and mang	an	es	e	ox	ide	25.																			6.997	9.200
Lime																									8.736	3.666
Magnesia																									.936	1.210
Magnesia Phosphoric acid	١.																								.217	.319
Sulphuric acid																									2.280	.920
Potash (total)																									3.623	5.402
Sulphuric acid Potash (total) Soda (total)																									1.731	.720
Carbonic acid																								1		7.672
Water and loss			٠		٠		•	•	•	٠	•	•	•	•	•	•	•	•	•	٠	•	•	٠	3	8.304	7.0/2
Total	•	•			٠				•			•	٠	•	•	•		٠	٠		٠	٠			100.000	100.000
Per centage of	pł	109	sp	ho	rus	<del>-</del>	•			•	•				•	•			•		•	•		•	. 095	0.139
Per centage of	su	ılp	h	ır,						•										•			•		.912	. 368

Although the sulphur and iron in these marls are calculated in these analyses as sulphuric acid and iron oxide, severally, a portion of each, not determined, is combined as iron sulphide. These two analyses are tabulated separately from the first two of similar marls of this county, because in these latter analyses the method of *complete* decomposition by fusion was employed, while the first two were analyzed by digestion of the marls in acids, and the subsequent fusion of the insoluble silicious residue for the determination of the total amount of the alkalies. The remarks appended to the first two apply equally to these.

No. 1435—"Water from a bored or driven well, near the Kentucky river. Water stands about thirty-four feet from the surface of the ground, which is twelve to fourteen feet above low water level in that river. The height of the well water is affected by that of the river. Used in the steam boiler of the Frankfort Cotton Mill Company."

The sample of the water, together with some of the white powdery sediment and hard scale of the boiler, were sent to the laboratory by Mr. Milton McGrew, President of the company.

Nothing had been added to the water in the boiler, and the sediment and scale had been taken out of the boiler after running with this water for two weeks.

# COMPOSITION OF THE WELL WATER IN 1000 PARTS.

Held in s							•									•						-			
Free carbonic acid																									not est.
Lime carbonate																									0.2493
Magnesia, carbonate																									.0032
Silica			•		•	•		•		•	•	•	•		•	•	•	•			•	•	٠		.0005
Sediment on boiling	 •	•	•	•	٠	•	•	٠	٠	٠	•	•	٠	٠	•	٠		9.5	٠	•		•	•		0.2530
				c	on	tair	ned	l io	th	e b	oil	ed	wa	ter											
Lime sulphate																									0.1100
Calcium chloride											٠														.0254
Magnesium chloride																									.0174
Sodium chloride																									.0460
Potassium chloride																									.0142
Soda carbonate																									.0413
Nitric and phosphoric a																									a trace.
Silica																									.0006
																									0.2549

Total saline contents of the water, 0.5079 to the thousand parts. The fresh water gives a slight alkaline reaction with reddened litmus; the soda, stated as carbonate above, is doubtless present in it as bi-carbonate.

On examination of the white powdery boiler sediment, it was found to be mainly lime carbonate, with about five per cent. of magnesia carbonate, two to three of lime sulphate, more than one per cent. of alumina and iron oxide, with a trace of phosphoric acid, a little silica, and traces of the alkalies.

The hard boiler scale, on the contrary, was found to be mainly lime sulphate, with small proportions of lime and magnesia carbonates, and traces of silica, phosphoric acid, &c.

It is evident that the hard scale, which is the most injurious to the boiler, may be prevented by the addition to the water of enough carbonate of soda, say in the form of cheap soda ash, to decompose the lime sulphate. This would probably cause the sediment to be wholly powder.

No. 1436—Sulphur Mineral Water from a bored well, ninetysix feet deep, at Fleetwood Farm of Col. J. W. Hunt Reynolds, near Frankfort.

The water stands at about twenty-five feet from the bottom.

#### COMPOSITION OF THIS WATER.

											In 1000 parts.	In a wine gallon (231 cubic inches),
Free hydrosulphuric acid gas Free carbonic acid gas	:				•		:	:	:		0.0343 parts.	1.9981 grains, 16.1730 ''
Hel	ld i	n s	olu	tio	n t	у	the	fr	ee	carb	onic acid.	
Lime carbonate		:	:	:	:	•	:	:	:	:	.1397 parts. .1029 '' marked traces.	8.1350 grains, 6.0030 '' marked traces.
Total sediment on boiling	•	•	٠	•	٠	٠		•	•		0.2426	14.1380
Potash sulphate	•	•	: : : :	•	• • • • • •	•		•	•		.2535 parts. .1057 '' 1.0152 '' .0798 '' .0713 '' .0228 ''	14.7800 grains. 6.1670 '' 59.2140 '' 4.6580 '' 4.1620 '' 1.3330 '' 2.0000 ''
Bromine, iodine, and lithium											marked traces.	marked traces.
Total											1.8250 parts.	106.4420 grains.

A very good saline sulphur water, which may be useful in cutaneous and parasitic diseases, granular sore eyes, some forms of neuralgia and rheumatism, &c., &c., when employed externally or internally under the advice and direction of a physician.

This water was analyzed by the writer, for Col. Reynolds, before the reörganization of the Geological Survey; but it has been reëxamined recently in this laboratory, and, in addition to the ingredients reported to him, notable quantities, not quantitatively estimated, of iodine and lithium, were observed in it. The water acquires a yellowish tint on standing in bottles; doubtless owing to the formation of sulphuretted sulphide of sodium by the decomposing influence of the atmospheric oxygen on the hydrosulphuric acid.

#### FULTON COUNTY.

No. 1437—Soil. Labeled "Sub-soil of an old tobacco field. The soil proper has been washed away. Field about one hundred and fifty feet above the Mississippi river, four miles east of Hickman. Collected by Prof. N. S. Shaler."

This sub-soil is of a brownish dark-buff, or light yellowishbrown color.

## COMPOSITION, DRIED AT 212° F.

										- 32						1000	- )-3									٦	
Organic and volatile	mat	te	rs					•				23								•					×	11.	2.250
Alumina, and iron a	nd n	na	ng	an	es	e	oxi	de	s.																•	٠. ا	6.005
Lime carbonate																										.	.230
Magnesia																											.414
Phosphoric acid																										.	.172
Sulphuric acid																											not est.
Potash																										. [	.159
Soda																										. [	.072
Sand and insoluble s	ilica	ite	5 .																							. !	90.490
Water expelled at 38	oo l	F.						•		•	•	•		•	•		•	•			•	٠	•	٠	•		.650
Total	K 5	٠	٠	:*	.•	•	٠	٠	٠	٠		•3	•	•	٠	•	٠	•		ė	٠	٠	•	•		(*)	100.442
Hygroscopic moistur	e, p	er	ce	nt		•	•				•	•		•	3.5	•	•	٠		·		•	:				2.250
Potash in the insolub	ole s	ili	cat	es	, F	er	C	ent		•				•				•	•				•	·	e.	•	1.479
Soda in the insoluble	sili	ca	tes	. 1	De	гс	en	t.					्	82			29			12			_	_			1.306

It will be seen that in this sub-soil, which contains a very large proportion of fine sand and insoluble silicates, and which 80

only gave up 0.159 per cent. of its potash after long digestion, with heat, in chlorohydric acid, there is yet a reserve supply of that alkali of more than nine times that quantity, locked up in the insoluble silicates. This potash, although not immediately available for the use of plants, will doubtless be gradually brought into an available condition, under the slow but certain action of the atmospheric agencies and under that of humus, &c.

No. 1438—MINERAL WATER. "Chalybeate water, sent by Mr. B. R. Walker, from Nick Combs' Spring, four miles southwest of Hickman, Fulton county."

This chalybeate water contains free carbonic acid and 0.302 of saline matters in the one thousand of water. This consists of iron, manganese, lime and magnesia carbonates, with some lime and magnesia sulphates, &c. The quantity sent was too small for a thorough analysis.

It is probably a valuable chalybeate water.

No. 1439—"Indurated Silicious Clay. From the bluffs, one hundred feet above low water mark, Hickman, Fulton county. Tertiary formation. Collected by Prof. N. S. Shaler."

Of a light-grey color, with ferruginous infiltrations. Breaks readily, with an irregular fracture. Adheres slightly to the tongue. Is somewhat plastic when powdered and rubbed up with water. When calcined, is of a light buff color.

No. 1440—"SILICIOUS CONCRETION or soft sandstone from the Bluff at Hickman, fifty feet above low water. Tertiary. Collected by Prof. N. S. Shaler."

A whitish, porous, and friable silicious rock or concretion; adheres to the tongue. Only slightly plastic when powdered and rubbed up with water. Burns of a light buff color.

No. 1441 — "SILICIOUS CONCRETION or soft sandstone, from Chickasaw Bluff, eight miles south of Hickman. Tertiary. Bed ten feet thick. Collected by Prof. N. S. Shaler."

A light-grey or dove-colored soft and porous silicious rock, adhering to the tongue. Scarcely at all plastic when powdered and rubbed up with water.

No. 1442—"SOFT SANDSTONE. Chickasaw Bluff, near the base, eight miles south of Hickman."

A dull light-yellowish-grey porous soft sandstone; adheres strongly to the tongue. Composed of minute rounded quartzose grains, with a whitish cement.

COMPOSITION OF THESE FULTON COUNTY SOFT SANDSTONES AND SILI-CIOUS DEPOSITS, DRIED AT 212° F.

	No. 1439.	No. 1440.	No. 1441.	No. 1442.
Silica	74.960	81.060	89.160	94.060
Alumina, and iron and manganese oxides	18.350	13.609	7.809	3.129
Lime carbonate	.560	.560	.380	. 380
Magnesia	. 309	.139	.086	.173
Phosphoric acid	.051	.051	.051	.051
Sulphuric acid	. 501	.844	.707	.981
Potash	.230	.231	.115	.230
Soda	. 124	.021	.080	.124
Water expelled at red heat	5.800	3,600	2.400	1.600
Total	100.885	100.115	100.788	100.728

These silicious deposits do not contain enough mineral fertilizing ingredients to make them valuable for application to the soil, nor enough alumina to constitute good plastic clay. Yet they may be made useful in tempering clay which contains too much alumina, or for the formation of common glass and for scouring purposes. Some of them are plastic enough to enable them to be moulded, and the silicious material is fine enough, in some, to permit them to be used as "Bath Brick" for household scouring. Common brick could probably be made out of No. 1439.

Some of these layers, in which the proportions of alkalies, lime, magnesia, and iron oxide are small, may perhaps be manufactured into a kind of fire-brick.

Part of the sulphur which appears in the above summary of analyses as sulphuric acid, is doubtless in combination with some of the iron in the sandstone, in the form of iron sulphide:

the oxidation of which may account for a portion of the excess in the total.

No. 1443—"CLAY from the foot of Grand Chain, Illinois. Post Tertiary. Collected by Prof. N. S. Shaler."

Of a light-grey-dove color, with brownish incrustations. Fracture large conchoidal-hackly; quite porous; adheres strongly to the tongue; grinds easily into a tough plastic mass with water. Calcines of an orange-buff color; but fuses before the blow-pipe. Specific gravity, in its porous state = 1.764. Contains minute glimmering scales of mica.

	COMPOSITION, I	DRIED AT 212° F.
Silica		
Alumina, and iron and manga	nese oxides	20.309
Lime carbonate		
Magnesia		
Sulphuric acid		1.188 = .475 per cent, of sulphus
Phosphoric acid		051
Potash		
Soda		
Water expelled at red heat, an	d loss	5.219
		100.000

This clay, which was collected for comparison with the Fulton county tertiary deposits, would prove of no especial value as a fertilizer, except on very sandy soils to improve their consistence. It would probably answer for common pottery or bricks; but is too fusible for fire-brick. It compares pretty well with No. 1439.

### GRAYSON COUNTY.

No. 1444—CLAY IRON-STONE "From three miles south of Litchfield. A six inch layer, on the land of Jno. H. Higden, in the carboniferous limestone. On the old Brownsville road. Collected by Prof. N. S. Shaler."

Fine granular, or compact. Dark grey.

COMPOSITION DRIED AT 2120 F.  ${60.466 \atop 6.536}$  = 33.630 per cent. of iron. Iron, peroxide . . . . . . . . . . . . . . . . . . 7.179 Lime carbonate......... 4.050 Magnesia, carbonate . . . . . . . . . . . . . . . . 6.378 a trace. Phosphoric acid . . . . . . . . . . . . . . . . . .102 = 0.035 per cent. of phosphorus. .054 = .022 per cent. of sulphur. Sulphuric acid. . . . Silica and insoluble silicates . . . . . . 14.450 = 11.900 per cent. of silica. .785 Water and loss . . . . . . . . . . 100,000

Quite a good ore of its kind.

No. 1445—LIMONITE IRON ORE. "From north side of Grindstone branch of Rock Creek. Hill below Owen Whittrie's. Grayson county. Collected by P. N. Moore."

A porous and cellular limonite, varying in color from dark brown and steel black to reddish-brown and ochreous.

COMPOSITION, DRIED AT 212° F. 27.192 = 19.344 per cent. of iron. Manganese, brown oxide. . . . . . . . . . . a trace. .410 Lime carbonate . . . . . . . . . . . . . . . . . . .317 .249 = 0.109 per cent. of phosphorus. .103 = .041 per cent. of sulphur. Water expelled at red heat . . . . . . . . . . 5.600 Silica and insoluble silicates . . 61.730 = 25.500 per cent. of silica. Moisture and loss . . . . . . . .100 100,000

This ore is too poor in iron and too silicious to be of much value.

[See Appendix for other Grayson county iron ores.]

No. 1446—MARLY SHALE. "From Sunset Lick, a mile and a half west of Litchfield. Geological position the carboniferous formation. Collected by Prof. N. S. Shaler."

A friable marly shale of a greyish and brownish-olive color. This marl, when analyzed by digestion in acids, &c., gave the following results, dried at 212° F., viz:

Alumina,																							19.133
Lime																							. 269
Magnesia				. :																		. 1	-353
Phosphori	c ac	id																				- 1	.353
Sulphuric	aci	d.																	•			.	.027
Potash .																						. [	2.910
Soda																						. 1	.052
Water ext	elle	d	at	Te	d	h	eat				- 3			3.3	2								6.230
Silica and	ins	olu	Ы	e	si	lic	ate	s								•	•	•	•		•		71.580
Total .																						. [	100.821

The silica and insoluble silicates, when sintered with lime carbonate and ammonium chloride, &c., &c., yielded 1.205 per cent of potash, and 0.55 per cent. of soda, in addition to that given above as extracted by digestion in acids. So that the total amount of potash in the marl appears to be 4.115 per cent. and that of soda 0.602 per cent.

Some of the same marly shale, from this locality, subsequently collected by Mr. P. N. Moore, was analyzed by fusion with the mixed alkaline carbonates; *sintering* with lime carbonate and ammonium chloride, &c., &c., and gave the following results, viz:

Total									•					•		•		٠		•	•		•			•					101.258
Water, Silica.																															60.060
Water,	&c	٠,	ex	pe	lle	d :	at	rec	I h	nea	t.			•				•	•	•				•		•			•	-	6.000
Soda.									•			•		•	•	•		•	•		•			•		•				٠.	. 783
Potash																														.	4.625
Sulphur	ic	ac	id																		•					•				- [	. 204
Phospho	ori	C	ıci	d.																	•			•						. [	
Magnes	ia		٠												•		•	•	•	•			•	•	•	•				- 1	1.158
Lime .									•			•	•	•	•			•		•	•			•	•	•	•		•	- 1	. 538
Iron an	d 1	ma	ng	an	es	e c	xi	de	5 .	•	•		•	•		•	٠	•	•	•	•		•	•	•		•		٠	٠.	13.480
Alumin	a .		٠	٠	٠	•		•	٠			•		•	•	•	٠	•	٠	•	٠	٠	٠	•	•	٠	•	٠			14.130

The apparent excess in the total may be partly due to oxidation of combined iron and sulphur in the marl, and probably, also, to an over-estimation of the water.

Its considerable proportion of *potash* might make it useful as a fertilizer on impoverished land, were this alkali all in an available condition. But the analyses show that a great portion of it is in firm combination, in the silicates insoluble in acids; only to be released, and made available for plant growth, by the slow process of weathering, under the influence of atmospheric agencies, *humus*, &c. Whether lime could be profitably employed to decompose these silicates and set free the alkalies, is yet to be tried.

The remarks given under the head of marly shales of Campbell and Franklin counties, as to their use as "mineral paint," &c., apply to this marly shale also.

No. 1447—"SOFT SANDSTONE; a micaceous, uncemented sand rock, from Horse Branch, on the Elizabethtown and Paducah Railroad. Border of Grayson and Ohio counties. Very friable. Can be shoveled like sand. Collected by Prof. N. S. Shaler. Geological position carboniferous."

Of a light drab, or grey-buff color, consisting of small quartz grains, mostly rounded, some spangles of mica, some few grains of blackish and greenish ferruginous mineral, and a fine powder, somewhat ferruginous, which can easily be washed out from the quartz sand, &c., by water. Water disintegrates the lumps.

This soft sand rock, dried at 212°, gave the following results, on analysis by acid digestion, &c.:

																			1	
Sand and insoluble silicates .			 											•	٠					87.700
Alumina, colored with iron oxid	de .		 																	7.040
Lime (estimated as carbonate)																			-	. 100
Magnesia																				. 245
Phosphoric acid																				
Sulphuric acid																				
Potash																				
Soda			 																	.401
Water, &c., expelled at red hear	t		 																	3.000
Loss	•	•		•	•	•	•	•	•		•	•	•	•	•	•	•	•		. 120
Total		•		•	•	•		•	٠	•	•		•			•		•		100.000
			_		 		_	_	_											

This would undoubtedly answer well for the manufacture of common glass. Its considerable proportion of potash, nearly one per cent. extracted by acids, has probably been mainly derived from the mica which it contains, while the phosphoric acid, also considerable for a sand, has doubtless been mostly extracted from the dark greenish mineral. This sand would prove a useful addition to heavy clay soil. No doubt analysis by fusion would show that it contains a much larger proportion of potash than digestion in acids demonstrates.

No. 1448—COAL. Labeled "Tar Lick Coal, Dismal Creek, Grayson county. Average sample, by P. N. Moore."

Mostly in thin laminæ, with some bituminous matter, fibrous coal, and fine-granular pyrites between them. Generally of a deep-black color, with occasional ferruginous stains.

No. 1449—Coal. "Gravelly Lick, Miller's Fork of Bear Creek. Average sample, by P. N. Moore."

Splitting into thin laminæ, with a little fibrous coal and finegranular pyrites between.

No. 1450—COAL. "Near the School-house, on Brushy branch of Calloway Creek, W. B. McGrew's. Collected by P. N. Moore."

Much weathered.

No. 1451—Coal (impure) "Copperas bank, branch of Hunting Fork of Rock Creek, above the conglomerate. Collected by P. N. Moore."

Mostly in thin laminæ, some of which are shaly. Some ferruginous incrustation.

No. 1452—Coal. "L. Higdon's, Pearson's branch of Rock Creek. Below the conglomerate. About fifteen feet above the limestone. Collected by P. N. Moore."

A jet-black coal; generally breaking into thin laminæ, some of which are somewhat shaly. Not much fibrous coal or granular pyrites apparent. Some ferruginous incrustation.

No. 1453—Coal (impure) "From Gum Spring Fork of Cane Camp Creek, Nolin Furnace property. Sample from above the slate parting only. Collected by P. N. Moore."

A much weathered coal, in thin laminæ, much tarnished with ferruginous and aluminous incrustations.

No. 1454—COAL (impure) "From same locality as preceding. Sample from below the slate parting only. Collected by P. N. Moore."

In thin laminæ, some shaly; weathered dull and stained with ferruginous and clayey incrustation.

COMPOSITION	OF THESE	GRAYSON	COUNTY	COALS.	AIR-DRIED.
-------------	----------	---------	--------	--------	------------

	No. 1448.	No. 1449.	No. 1450.	No. 1451.	No. 1452.	No. 1453.	No. 1454
Specific gravity	1.305	1.395	1.346	1.378	1.364	1.446	1.512
Hygroscopic moisture	4.70	4.14	6.26	3.50	3.60	6.50	4.40
Voj. combustible matters. Coke	63.90	30.52 65.34	32.44 61.30	33.40 63.10	35.80 60.60	29.10 64.40	25.86 69.74
Total	100.00	100.00	100.00	100.00	100.00	100.00	100.00
Total volatile matters	36.10	34.66	38.70	36.90	39.40	35.60	30.26
Carbon in the coke Ashes	52.20 11.70	50.08 15.26	53.80 7.50	47.50 15.60	49.40 11.20	49.60 14.80	40.14
Total	100.00	100.00	100.00	100 00	100.00	100.00	100.00
Character of the coke	Spongy.	Dense spongy.	Light friable.	Light spongy.	Light spongy.	Friable.	Friable.
Color of the ash	Light brownish grey.	Brownish grey.	Greyish- salmon.	Lilac- grey.	Lig'-t chocolate	Light brownish	Nearly white.
Per centage of sulphur	1.945	3.565	1.476	2.041	3.158	0.818	0.777

No. 1455—"Coal, remarkable for being found in the sub-carboniferous limestone; about seventy-five to a hundred and twenty feet below the Chester Group. Collected by C. J. Norwood."

A much weathered specimen; splitting easily into thin laminæ, with very little fibrous coal or pyrites between. Some little ferruginous stain.

# COMPOSITION—SPECIFIC GRAVITY = 1.338.

Hygroscopic moisture Volatile combustible matter														•		•									4.24
Volatile combustible matter	S	•			•	•	•	•	•	•	•	•		•	•	•		•	•	•	•			•	30.82
Coke (light friable)		•	•		٠	•	•	•	•	•	•	•	٠	•	•	•	•	•	•	•	•				64.94
Total		•			٠															•					100.000
Total volatile matters																							-		35.06
Carbon in the coke																			•					•	55.52
Ashes (brownish salmon-gre	ey)	)		•	•		•	•	•	•	•	•	•	•	•	•		•	•		•	•		•	9.42
Total					2			::4				•						•							100.00
Per centage of sulphur								•							-					-				<del>-</del>	2.892

Interesting only because of its unusual position.

# GRAYSON SPRINGS MINERAL WATERS.

These waters were mostly collected and tested qualitatively, at the springs, by Mr. Jno. H. Talbutt; who spent several days in this work and in the evaporation of a quantity of some of the principal ones, for the purpose of determining the more rare ingredients. The quantitative analyses were performed at our chemical laboratory in Lexington.

No. 1456—"Sulphur Water from the Centre Spring, a natural spring, the most popular of the Grayson Springs."

Inclosed in a "gum" three feet deep and one and a half feet in diameter. Flows in a perennial stream, of about half an inch diameter. Gas bubbles up frequently, in moderate intermittent bursts. The water is of nearly a constant temperature of 61° F.; clear, depositing in its channel a dark-grey slimy sediment; and on the gum an incrustation varying in color from blackish and brownish to greenish and pinkish.

The spring is about two hundred yards southeast from the hotel. Has a reputation as diuretic, aperient, &c., &c. Reaction of the recent water is neutral with litmus paper, but when it has been partly evaporated it is slightly alkaline.

No. 1457—Sulphur Water from the Moreman Spring.

A natural spring, inclosed in a sycamore "gum" (twenty-two inches deep by eleven in diameter). Stream constant the VOL. I.-CHEM. 7.

year round, through a three-quarter inch hole. Bubbles of gas rise intermittently. Sediment in the channel of overflow, whitish; that at the bottom of the gum greenish-black, and slimy. Temperature of the water 66° to 67° F., nearly constant.

Considered one of the best of the waters for cutaneous diseases. Acts pretty constantly as aperient. Reaction of the recent water, neutral.

No. 1458—SULPHUR WATER of the McAtee\* Sulphur Spring.

A natural spring (said to have two sources, one warm the other cold), located at the base of the hill, farthest of all from the house, nearest to the creek; near the bath-house. Included in a wooden box, fourteen by twenty-two inches, and twenty inches deep. The flow is about sufficient to fill a half inch pipe. There is a slight intermittent evolution of gas. Temperature, said to be invariable, at 60° F. The sediment in the box is dark green, with much pinkish; slimy. The incrustation on the box, greenish of various tints and shades. This water is not quite so strong as that of the "Center Spring."

No. 1459-Sulphur Water of the "Stump Spring."

A natural spring, included in a sycamore "gum," twelve inches in diameter and twenty deep. The flow is about a quarter to half inch in diameter. There is a slight evolution of gas in bubbles. Temperature of the water 64° F., said to be invariable. The sediment in the gum is blackish and slimy. The incrustation very slight, and nearly black. The taste of the water is sweetish-brackish. Reaction with litmus papers, neutral.

No. 1460-Sulphur Water of the "Jar Spring."

A natural spring, nearest to the house (near the Stump and Big Gum Springs), included in a gum twelve inches in diameter

<sup>\*</sup>Called by Dr. Owen "Macatine." Volume 1, Kentucky Geological Reports, page 270.

and twenty-six deep. Flow of water from quarter to half an inch in diameter. Slight evolution of gas in bubbles, smelling strongly of sulphuretted hydrogen, as do all the others. Temperature of the water 63° F., said to be constant. Taste sweetish. Reaction, neutral. The sediment is dark-colored; slimy. The incrustation on the gum whitish, with greenish and purplish tints.

# No. 1461—SULPHUR WATER from the "Eye Spring."

A natural spring, included in a "gum" ten to eleven inches in diameter and twenty deep. The flow of water is about a quarter of an inch in diameter. Temperature of the water, 66° F., said to be invariable. (The temperature of the atmosphere, at the time of observation, was 86° F.) Very little evolution of gas bubbles. The sediment in the gum is dark, and slimy. The incrustation on the gum dark green, yellowish, and purplish, and dirty-whitish. Taste brackish. Reaction, neutral.

No. 1462—Sulphur Water from the "White Sulphur Spring," near the "Big Gum," and between it and the Moreman Spring, to the left of the walk.

Flow about quarter to half an inch in diameter. A slight intermittent evolution of gas bubbles. Temperature 62° F., said to be invariable. Incrustation whitish. Sediment greenish near the gum. Tastes and smells stronger of sulphuretted hydrogen than any of the other springs. Reaction, neutral. Water not at present used.

# No. 1463—Sulphur Water from the "Hymenial Spring."

A feeble spring, situated about ten feet from the "Center Spring." Temperature of the water 65° F., said to be invariable. Sediment greenish-black, with pinkish portions, and slimy. Incrustation on the "gum" dark-green and dirty-white. Reaction, neutral.

No. 1464—Sulphur Water from the "Rock Spring."

The original spring of the group. Situated at the base of the hill. Flows out from the rock in a constant stream, which might fill an inch pipe. Temperature 58° F., said to be invariable. A whitish scum on the water in the channel of out-flow; no gas bubbles evolved. Sediment bluish-blackish. Reaction, neutral. Not very strong in sulphuretted hydrogen.

No. 1465 — Sulphur Water from an Artesian Well, one thousand feet deep, and six inches in diameter, completed in 1865.

Bored for "oil" on Hunting Fork, a tributary of Rock Creek, near Mr. H. Haynes', six miles from Grayson Springs, on the property of the Boston Kentucky Central Rock Oil Company, H. W. Fuller, President. At first the water spouted twenty feet above the surface of the ground, from the two-inch tube. The tube is now out, and the hole has been widened for six feet down and cased with an eight-inch square wooden box. The water now flows out in a six-inch stream. Temperature 61.5° F. Gas is evolved constantly in large bubbles. The incrustation on the boxing, &c., is blackish, and is to be seen in the channel of the stream for half a mile down. The water is clear and colorless, and gives an alkaline reaction. A salt water stream is said to enter the well about one hundred and fifty feet below the surface.

COMPOSITION OF THESE SULPHUR WATERS OF GRAYSON COUNTY IN 1000 PARTS.

Name of spring	Centre.	More- man.	McAtee.	Stump.	Jar.	Eye.	White Sulphur.	Hyme- nial.	Rock.	Artesian
	No. 1456	No. 1457	No. 1458	No. 1459	No. 1460	No. 1461	No. 1462	No. 1463	No. 1464	No. 1465
Specific gravity of water	1.0022	1.0011	1.0015	1.0016	not est.	not est.	not est.	not est.	not est.	not est.
Free carbonic acid gas . Free sulphuretted hydro- gen gas	0.1950	0.1234	0.1500	0.1650	0.2020	not est. 0.0239	not est. 0.0270	not est.		not est. 0.0380
Lime carbonate Magnesia carbonate Iron, and manganese carbonates and phosphates Silica Organic matters and loss	.0027	0. 1952 . 0512 . 0048 . 0094 not est.	0.1806 .0002 .0078 .0028 .0022	o. 2002 a trace. .0066 .0008 .0268	0.1632 .0345 .0072 .0032 .0271	0. t872 .0042 .0096 .0036 .0096	0.1832 .0018 .0096 .0104 .0090	0. 1525 not est.	o. 1660 .0118 .0072 .0022 .0304	0.1360 .0228 .0106 .0260
Total sedi'nt on boiling	0.1785	0.2606	0.1914	0.0342	0.2352	0.2132	0.2140	not est	0.2176	0.1992
Lime sulphate Magnesia sulphate		0.454I .3768	0.4528 .4616 .0024 .0126	0.6291 .6093 .0023 .0374	0.5078 .5781 .0045	0.6683 -7542 .0017 .0147	0.6505	0.9001 .8835 .0085	o. 5946 .4704 .0011 .0288	1.3044 .8778 not est. not est.
alumina sulphates and phosphates Sodium sulphide Soda combined with or-	.0034	.0007	.0192 not est.	not est. not est.	traces.	traces.	traces. .0257	traces. .0220	traces. .0059	traces.
ganic acids	.0044	.0066	.0200		.0760	.1059				
Silica	.0034	.0029 not est.	.0060 notest.	.0022 .0200	. 2029	.0058	.0 := 8	.0032 not est.	.0048	not est.
Total saline matters .	2.0748	1.1609	1.3252	1.5740	1.6260	1.7960	1.7470	1.9974	1.4800	2.7084
Lithium, iodine and bro- mine	traces.	traces.	traces.	traces.	not est.	not est.	not est.	not est	not est.	not est.
Temperature of spring, F.	610	1.6°, 67°	60°	640	6	66°	12	65°	530	610,650

The small quantities of lithium compound, indicated in the above table, were detected by means of the spectroscope, after proper treatment of the saline residuum obtained by the evaporation of from ten to twenty litres of the water. The bromine and iodine traces could only be observed by the appropriate tests after a similar evaporation.

The organic matters recorded in the table are composed of apocrenic and crenic acids and the singular substance called Barégine, from the fact that it was first observed in the sulphur water of the celebrated Barège Springs of the Pyrenees.

This Barégine is found in solution in many of the sulphur waters of the world; more especially in the thermal waters.

On evaporation of such waters they assume a yellowish tint and leave a yellowish-brown residue, which, on calcination, gives out ammoniacal fumes and the odor of burnt horn; leaving a very large proportion of ash, mainly silicious. This organic matter, approaching to the nature of the albuminoid or gelatinous principles, is what is called Barègine.

By exposure of these waters to the air this dissolved nitrogenous matter undergoes a change; becomes less soluble and forms a sediment, or deposit, in the spring and its channel, of a slimy nature, which is called *glairine*, and which is usually combined with other precipitated materials from the water, such as iron and manganese sulphides, lime and magnesia carbonates, free sulphur, &c., &c., and probably changes, by gradual decomposition, into *crenic* and *apocrenic acids*, &c.

Glairine, with crenic and apocrenic acids, and other substances mentioned above, were abundantly found in the unctuous slimy sediment of these Grayson sulphur springs. Generally more of the latter than of the crenic.

This sediment was collected by Mr. Talbutt from the bottom of the water in the "gum" usually, from the following springs, viz: "Centre," "Moreman," "McAtee," "Stump," and "Hymenial," and brought to the laboratory for examination, in close bottles, with some of the water of the spring included.

On examination, some weeks afterward, the supernatant water was found to be glairy in all except that from the Stump Spring. In those from the Centre and Moreman springs the water over the sediment was of a dirty-olive green color, of a sulphurous and putrescent odor, glairy, and as thick as ordinary white of egg. When this was poured off and the sediment agitated with more distilled water, this also became glairy and colored, on standing; and the same result was obtained in a second and third operation of the kind; the quantity of the dissolved organic matter appearing gradually to be diminished. The "Centre" sediment gave the most of this glairy material; that of the "Moreman," "McAtee," and "Hymenial" gave less, and that of the "Stump," although it colored the water slightly, did not make it glairy or communi-

cate to it the semi-putrescent, sulphurous odor, so marked with the others.

The glairy colored solution, poured off from the sediment, was evaporated and analyzed. The dark brownish solid residuum, obtained by evaporation, presented the usual properties of glairine. It burnt with a burnt-horn, ammoniacal odor, leaving a large quantity, more than forty per cent., of whitish ash. This ash was largely silicious, but contained also alumina, iron and manganese oxides, lime, magnesia, and phosphoric and sulphuric acids. The glairley soluble matter also contained apocrenic acid.

The dark colored original sediments, which had thus been washed with water to remove some of the glairine, &c., were found to contain much apocrenic and crenic acids, especially the former, with alumina, iron and manganese oxides, lime, magnesia, phosphoric and sulphuric acids, sulphur, &c. Becoming somewhat charred when calcined and giving off the odor of burnt animal and vegetable matters. That from the "Centre" Spring giving more of the odor of burnt animal matter. Those of the others giving mostly the odor of burnt vegetable matter.

Doubtless the other sulphur waters of this locality also contain these remarkable organic ingredients, or most of them. What influence they have in therapeutic applications of these waters has not been determined. It is probable, however, that this decomposable organic material, from whatever unknown source derived, may, by reaction upon the dissolved earthy sulphates of the water, produce some of the sulphydric acid which it contains.

It may be interesting to append the chemical composition of glairine of three different varieties, as determined by J. Bouis. ("Comptes Rendus," XLI, page 116.)

											Carbon,	Hydrogen.	Nitrogen.	Ashes.
Glairine, pulpy, grey .		_								_	48.69	7.70	8.10	30.22
Glairine, fibrous, red.						٠		٠			44.06	6.69	5 · 57	35.00
Glairine, pulpy, green	•	•	•	•	٠	•	٠	•	٠		45.20	6.95	5.60	40.07

No. 1466—CHALYBEATE WATER, from the chalybeate well at Grayson Springs.

Well ten feet deep; walled up with rock, three feet square. Water about four feet deep in well. It is said that three streams of chalybeate and one of fresh water flow into it. A very slight occasional evolution of gas. Temperature of the water, 71° F. The water is raised with a wooden pump. The sediment or deposit, where the water flows from the pump and trough, is ferruginous, brownish-red. Reaction, neutral.

No. 1467—CHALYBEATE WATER, from a well near Grayson Springs; sent by Mr. Van Meter, proprietor of the springs, for examination.

This, like the preceding, deposited a flocculent light-brown ferruginous sediment in the containing bottle.

No. 1468—CHALYBEATE WATER, from "Indian Spring," a natural source, near Jones' Mill; head of Sunfish Creek, five miles from Paducah and Louisville Railroad. Sent for examination by Mr. H. Haynes.

This also deposited a brownish ferruginous sediment in the bottle.

COMPOSITION OF THESE CHALYBEATE WATERS, IN 1000 PARTS OF THE WATER.

																		No. 1466.	No. 1467.	No. 1468.
Free carbonic acid	÷	٠					21											0.207	not est.	not est.
Lime carbonate .	-					_	_				020				-		_	0.1251	0.2580	0.0076
Magnesia carbonate	е.																	a trace.	.0020	a trace.
Iron and manganes of alumina	e	аг	bo	na	tes	i a	nd	P	ho:	spl	nat	es,	w	ith	t	rae	ces			
Silica																		.0118	.0800	.0028
Total, held in so		io	n l	b <b>y</b>	ca	ırb	on	ic	ac	id			•	•	•	•	•	0.1391	0.3580	0.0237
Total, held in so	lu	_					S =	_				210					_			
Total, held in so	lu	•	:	:	•	:	:	•			•	:	•	•	:	•	<u> </u>	0.0110	0.3580 2.328 .741	0.0237 0.0692 a trace
Total, held in so  Lime sulphate  Magnesia sulphate Potash sulphate .		:	:	•	•	•	•	•		•	•	•	•		•	• • • •	- :	0.0110 a trace. a trace.	2.328	0.0692 a trace a trace
Total, held in so  Lime sulphate Magnesia sulphate Potash sulphate		•	: :	•	•	•	<u> </u>				:	•	•	•	•	• • • • •	- :	0.0110 a trace. a trace. a trace.	2.328 .741 .063	0.0692 a trace.
Total, held in so  Lime sulphate.  Magnesia sulphate  Potash sulphate.  Soda sulphate.  Sodium chloride.		•	: :	•	•		• • • • • • • • • • • • • • • • • • • •	• • • • •			:	• • • • •	•		:	• • • • • •	- : :	0.0110 a trace. a trace. a trace.	2.328 .741 .063	o.0692 a trace a trace a trace
Total, held in so  Lime sulphate.  Magnesia sulphate  Potash sulphate.  Soda sulphate.  Sodium chloride.  Potassium chloride		•			• • • • • • • • • • • • • • • • • • • •			• • • • • • •	•		: :	• • • • • •	•	•	: : :	• • • • • •	- : :	0.0110 a trace. a trace. a trace. .0081	2.328 .741 .063 1.130 .1510	0.0692 a trace a trace a trace .0423
Total, held in so  Lime sulphate Magnesia sulphate Potash sulphate		•			• • • • • • • • • • • • • • • • • • • •			• • • • • • •			: :	• • • • • •	•	•	: : :	• • • • • •	- : :	0.0110 a trace. a trace. a trace.	2.328 .741 .063	o.0692 a trace a trace a trace

From these analyses, which can only be considered approximative, it appears that the water from the well near Grayson Springs is the strongest and the most aperient. The small quantity of the water sent, and the alterations which always take place in waters of this kind, under the influence of the atmosphere, prevent these examinations from being entirely conclusive.

No. 1469—Soil. "Sample to the depth of eight inches from an old field, fifty years in cultivation, which has been lying uncultivated for the last fifteen years. Collected by C. Schenk."

Situated twenty-five hundred feet west of the twenty-first mile-post on the Louisville and Paducah Railroad; west of Big Clifty. Locality, six hundred and seventy feet to the right of that road and four feet above the level of the rail. Underlying rock, sandstone. Timber of the locality, mostly black oak, with some white and red oak; with a few poplars on the creeks. Undergrowth sumach, dogwood; much sassafras and persimmon. Rotation of crops: 1. Tobacco; 2. Corn; 1. Oats; sometimes with clover. No manure. Yield: of corn and oats, of each ten bushels to the acre. Soil of a yellowish light-umber color.

No. 1470—Soil. "Sub-soil of the preceding, taken at a depth of from eight to forty inches. Collected by C. Schenk."

Sub-soil of a dull-light-brick color.

No. 1471—"VIRGIN SOIL. Sample to depth of six inches. Collected by C. Schenk."

From a point two hundred feet east of the twenty-second mile-post, on above named railroad; two hundred and fifty feet to the right of the road, and four feet above the level of the rail. Underlying rock, sandstone. Has been two years in cultivation. Usual yield of this locality, according to report of the farmers, of corn and oats, each ten to twenty bushels, and of wheat five to ten bushels. It yields tobacco only when manured. Timber same as in preceding.

Soil of a greyish-brown or light umber color. The coarse sieve (two hundred and eighty-nine meshes to inch) removed from it a few rounded ferruginous particles only.

No. 1472—"Sub-soil of the next preceding; taken to the depth of from six to thirty-six inches. Collected by C. Schenk."

Sub-soil of a light greyish-buff color. Contains a few small rounded ferruginous particles.

No. 1473—"VIRGIN SOIL, three years in cultivation. Collected by C. Schenk."

Sample to the depth of seven inches, from a locality one thousand feet west of the twenty-sixth mile-post, on the Louis-ville and Paducah Railroad, and three hundred and sixty feet to the left of that road, at the level of the rail. Drainage slope = 1:150. Substratum, limestone. Timber, red, black, and white oak, with sugar-tree and poplar. Timber full of holes, except the poplar. Undergrowth, dogwood, sassafras, persimmon. Sometimes one hundred cords of wood to the acre.

Rotation of crops: two years in corn; yield, twenty-five bushels to the acre; one year in oats; same yield. New land here yields fifteen to thirty bushels of corn, twenty to thirty of oats, and eight hundred to a thousand pounds of tobacco, per acre.

Soil of an umber color; darker than the preceding virginsoil. It contains a few rounded ferruginous particles.

No. 1474—"Sub-soil of the next preceding, taken at the depth of from seven to thirty-six inches. Collected by C. Schenk."

Sub-soil of a light grey-buff color. Contains a few small rounded ferruginous particles.

No. 1475—Soil. "Sample to the depth of five and a half inches, of an old field, forty years in cultivation. Collected by C. Schenk."

Near the Grayson Spring Station, Louisville and Paducah Railroad, four hundred and fifty feet to the right of that road, 98

at a point five hundred and thirty feet east of the twenty-six mile-post. Fifteen feet above the level of the rail. Drainage slope = 1:30. Substratum, limestone. Rotation of crops: two years in corn, one in oats and clover (sometimes tobacco first). Field has been in grass for the last three years. Yield: corn, twelve to twenty bushels; wheat, eight; and oats, fifteen per acre.

Dried soil of a brownish-grey color. Sifted out very few small rounded ferruginous particles.

No. 1476—"Sub-soil of the next preceding, taken from five and a half to thirty-six inches below the surface. Collected by C. Schenk."

Sub-soil of a grey-buff color. Contains but few rounded ferruginous particles.

NOTE.—For the rest of this serial collection of soils, &c., made by Mr. Schenk, on and near the line of the Elizabethtown and Paducah Railroad, see Hardin and Ohio counties.

COMPOSITION OF THESE GRAYSON COUNTY SOILS, &c., DRIED AT 212° F.

	No. 1469	No. 1470	No. 1471	No. 1472	No 1473	No. 1474	No. 1475	No. 1476
Organic and volatile matters		3.375	4.85	3.200	4 950	3 350	4.500	3 275
Alumina, and iron and manganese oxides	7.215	10.990	5.515	7.497	6. 195	6.647	4.172	6.022
Lime carbonate	- 345	. 195	. 145	.045	- 340	.020	.220	.145
Magnesia	:240	.159	.140	.140	1 . 176	. 104	. 167	.125
Phosphoric acid	.076	. 166	.125	.093	.175	.093	.113	.093
Sulphuric acid	Not est		54,500,000	C 100 00 000	2000	0.00000010		
Potash	.243	.308	.112	. 105	. 327	. 105	. 120	.405
Soda	. 125	1 .104	.051	.044	.023	.670	.045	
Sand and insoluble silicates	80.850	84.490	88.79	87.565	86.780	88.965	90,640	89.580
Water expelled at 380° F	925	.425	1.325	.875	1.075	1.100	1.100	- 350
Loss	.131			.436	.009			.005
Total	100,000	100.212	101.053	100.000	100.000	100.454	to1.082	100.000
Moisture expelled at 212° F	2.025	2.925	2.125	2.700	1.950	1.650	1.775	3.500
Potash in the insoluble silicates	1.0395		1.602					. 828
Soda in the insoluble silicates	0.479		- 377					.624
Character of the soil	Old field	Sub-soil	Virgin soil.	Sub-soil	Virgin soil.	Sub-soil	Old field soil.	Sub-soil

Although these Grayson county soils cannot be classed amongst the naturally very rich soils, because they are rather too sandy; yet, if they are well drained, they may be made quite profitable with proper management and by the judicious why they are not at present more productive than is represented above. Their near vicinity to good markets should introduce a more scientific husbandry.

#### GREENUP COUNTY.

No. 1477—CLAY. Labeled "Fire-clay, Louder's land, near Kenton Furnace. Collected by P. N. Moore."

A compact, fine-grained, non-plastic clay-stone of a light-grey color; hardly adhering to the tongue; breaking readily into sharp angular fragments; fracture somewhat conchoidal. This, when reduced to powder, easily works up with water into a plastic mass, which is the case with the other samples of this kind described below.

No. 1478—"FIRE-CLAY, two feet above the limestone ore; head of Powder-mill hollow, two miles from Kenton Furnace. Collected by P. N. Moore."

An olive-grey shaly clay, breaking easily into layers, but not so easily across them; adhering to the tongue.

No. 1479—"CLAY, fourth above the limestone and limestone ore, on Pea Ridge. Thickness two to two and a half feet. Weathering white. Collected by J. A. Monroe."

A whitish clay, in soft friable lumps; colored with oxide of iron in the crevices.

No. 1480—"CLAY; thin bed, resting on limestone ore of Pea Ridge, near Hunnewell."

A soft friable plastic clay; colored olive-green and brownish and yellowish-grey.

No. 1481—"CLAY. Two and a half feet bed; second above limestone ore. Pea Ridge. Collected by J. A. Monroe."

Olive-brownish-grey. Harsh to the feei. Breaks in angular fragments.

No. 1482—"CLAY, fourteen inches thick. Third bed above the limestone ore at Pea Ridge. Collected by J. A. Monroe."

A brownish-grey compact clay, breaking into irregular layers, which are polished on their surfaces; adheres slightly to the tongue.

No. 1483—Clay. "Fire-clay. Thomas' bank. Average sample of upper layer; five feet above the cherty limestone. Head waters of Wing's branch of Shultz Creek. Collected by P. N. Moore."

A compact clay-stone of a light-grey color (yellowish and bluish); even fracture; soapy feel; not scratched by the nail; scarcely adhering to the tongue.

COMPOSITION OF THESE GREENUP COUNTY CLAYS, DRIED AT 212° F.

	No. 1477	No. 1478	No. 1479	No. 1480	No. 1481	No. 1482	No. 1483
Silica	49.680	62.920	66.560	47.060	67.700	55.560	47.560
Alumina	35.281	20.735	22.679	36.620	22.092	31.027	40.661
Iron oxide, &c		3.820	a trace.	a trace.	a trace.	a trace.	a trace.
Lime		.213	.157	.615	. 101	. 325	. 280
Magnesia	.136	2.281	.605	. 389	. 285	.403	.497
Phosphoric acid	.626	.371	. 563	.626	.498	.358	. 249
Sulphuric acid	not est.	not est.	a trace.				
Potash	. 193	.2.601	1.946	1.156	1.156	1.167	. 308
Soda		.659	.690	.234	. 268	.560	.409
Water expelled at red heat,	AMEDIAN	, ,,		3.	0.00000000		
and loss	13.660	6.400	6.800	13.300	7.900	10.600	10.036
Total	100.000	100,000	100.000	100.000	100.000	100.000	100.000

On submitting these clays to the action of the blow-pipe, No. 1480 was found to be most softened by the heat, while Nos. 1477, 1481, and 1483 were most refractory; the others occupied an intermediate position. They all burnt nearly white, but No. 1478 burnt of a light-buff color, and No. 1479, No. 1480, and No. 1483 acquired a very light pink tint on being calcined. They are undoubtedly all very good clays, and the more silica they contain, within certain limits, and the smaller their proportions of potash, soda, oxide of iron, lime, magnesia, and phosphoric acid, the better they withstand the melting influence of fire.

[See Carter county for other clays of this kind.]

No. 1484—"COAL, No. 1, used at Kenton Furnace. Average sample."

A brittle coal, breaking into irregular layers; fractured surface dark, glossy, asphaltum-like. Impressions of reedy leaves on the laminæ, and some fine-grained pyrites.

No. 1485—"COAL, average sample, from J. Thompson's bank, near Kenton Furnace. Bed sixteen inches thick. Collected by J. A. Monroe."

A brittle coal, breaking into thin irregular layers, which have much pulverulent mineral charcoal between them.

No. 1486—Coal, No. 3. "Average sample of the main coal of Raccoon Furnace. Below the shale parting."

A dark colored coal, breaking easily into thin layers. Separated by much fibrous coal, with some fine-grained pyrites diffused in it.

- No. 1487—Goal, No. 3. "Average sample of the upper part of the coal used at Raccoon Furnace. Mine one and a third miles east of southeast of the furnace. The upper twenty inches of the thirty-six inch bed. Collected by P. N. Moore." Much like the preceding.
- No. 1488—COAL. "Main coal, No. 3; lower part below the shale parting. Buffalo Furnace. Averaged by P. N. Moore."
- No. 1489—"MAIN COAL, No. 3; above the shale parting. Buffalo Furnace. Averaged by P. N. Moore."
- No. 1490—COAL. "Alcorn Creek coal; probably sub-conglomerate. Raccoon Furnace. Averaged by P. N. Moore."
- No. 1491—COAL, No. 1. "Hanna bank coal. Average of the upper portion of the bed, from the stock pile, by P. N. Moore."
- No. 1492—"Hanna bank coal, &c. Averaged from the lower part of the bed, from the stock pile, by P. N. Moore. Coals identified by Mr. Witherow."

- No. 1493—"COAL, probably No. 3; thirty feet below the Kidney ore, Laurel Furnace. Average from coal shed, by P. N. Moore."
- No. 1494—Coal, No. 6; from the hill back of Amanda Furnace. Average sample from all parts of the bed, by A. R. Crandall."

A bright, jet-black, splint coal, with but little fibrous coal between the layers. Some slight ferruginous external stain.

No. 1495—Coal, No. 6; from branch above the shops, Hunnewell Furnace. Averaged from the upper part of the bed only, by A. R. Crandall."

Splint coal. Has but little fibrous coal between the laminæ. Slight external ferruginous stain.

No. 1496—Coal, No. 3. "From drift near Pennsylvania Furnace. Averaged by P. N. Moore."

A glossy jet-black coal, with fibrous coal and very little appearance of pyrites between the thin laminæ.

No. 1497—Coal, No. 6. "From a new opening one mile above the shops at Hunnewell Furnace. (Old Greenup Furnace.) Average sample."

A glossy pitch-black splint coal; shows but little fibrous coal or pyrites.

[See Appendix for other Greenup county coals.]

COMPOSITION OF THESE GREENUP COUNTY COALS, AIR DRIED.

	No. 1484	No. 1485	No. 1486	No. 1487	No. 1488	No. 1489	No. 1490	No. 1491	No. 1492	No. 1493	1484 No. 1485 No. 1486 No. 1487 No. 1488 No. 1489 No. 1490 No. 1491 No. 1492 No. 1493 No. 1494 No. 1495 No. 1496 No. 1497	No. 1495	No. 1496	No. 1497
Specific gravity	1.316	1.345	1.250	1.430	1.374	1.389	1.374	1.389	1.393	1.289	1.335	1.365	.38	1.355
Hygroscopic moisture	32.90 62.28	3.08	34.80	36.52	36.26	33.76 63.34	3.3.3 8.8.3	93.76 64.34	33.90	34.96	33.62	35.60	8.99.30 20.30 08.30	3.80 37.70 58.50
Total	30.001	100.00	100.00	100.00	100,00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	00.00
Total volatile matters	37.72 \$5.18 7.10	37.94 6.66	39.4 7.98	40.80 47.80 22.30	39.46 47.54 13.00	36.66	35.20 52.20 12.60	35.66 33.44 10.90	37.10 56.70 6.20	39.06 55.54 5.40	37.66	39.90	39.80 53.14 7.06	47.20
Total	80.001	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.8	100.00	100.00	100.00	100.00
Character of the coke Fris	P e	Light spongy.	Dense.	Dense.	Spongy.	Dense.	Friable.	Spongy.	Spongy.		Dense.	Spongy.	Dense o	Spongy.
Color of the mah	Choco- late.	Lilac-	Lilac- grey.	Lilac- grey.	Dark lilac- grey.	Dark lilac- grey.	Lilac. grey.	Dark lilac- grey.	Lilac- grey.	Dark brick.	Light lilac- grey.	Grey- purple.	Lilac- grey.	Dark- brown purple.
Per centage of sulphur	1.40	+.77.+	1.331	5.934	3.647	116.4	2.507	4.633	0.746	1.590	1.318	5.363	2.264	4.213

These comparative analyses show how much the coal of a given bed may vary in its different layers in the proportion of sulphur, ashes, &c. These Greenup county coals are generally very good coals, well suited to the working of iron. Some of them, however, are rather too sulphurous for this purpose.

A certain correspondence, not perfect, is to be observed in these coals, between their specific gravity and proportion of ash, as is shown below:

Specific gravity.	Per centage of ash.	Specific gravity.	Per centage of ash.
1.250	7.98	1.355	11.03
1.289	5.40	1.365	9.86
1.292	6.20	1.374	12.60
1.300	7.06	1.374	13.00
1.316	7.10	1.389	10.90
1.335	9.00	1.389	12.00
1.345	6.60	1.420	12 20

No. 1498—LIMESTONE. "Average sample of the ferruginous limestone from Pea Ridge. Collected by J. A. Monroe."

A compact, or fine-granular, brownish-grey limestone. Non-fossiliferous. Varying in tint.

No. 1499—Limestone. "Sub-carboniferous; used as flux at the Raccoon Furnace. From the head of Old Town Creek."

A compact or fine-granular limestone, varying in color from light reddish-grey to darker greenish-grey. Contains chert.

No. 1500—LIMESTONE. "Sub-carboniferous. Average sample of the limestone used as flux at Kenton Furnace. Collected by J. A. Monroe."

A compact or fine-granular limestone, of a light-grey color.

No. 1501—LIMESTONE. "Ferruginous. Buffalo Creek, Boone Furnace."

A compact or fine-granular limestone; grey-buff, varying in tint.

COMPOSITION OF THESE GREENUP COUNTY LIMESTONES, DRIED AT 212° F.

	_	_	_		-	_	_				
								No. 1498.	No. 1499.	No. 1500.	No. 1501.
Specific gravity									2.680	2.700	2.770
Lime carbonate			•				-	88.140	88.150	92.050	60.750
Magnesia carbonate								.797	. 385	.220	25.656
Iron carbonate									1		3.420
Alumina							)				4.167
Iron peroxide	•			• •	•	•	}	3.760	.152	1.490	
Phosphoric acid					Ī	ċ	1	.178	.051	.128	.013
Sulphuric acid					-		1	.044	not est.	.199	.315
Potash					-	-	-	.269	not est.	not est.	not deter'd.
Soda					-	-		.240	not est.	not est.	not deter'd.
Silica and insoluble silicates	. I	1		: :	-	Ō		5.960	9.560	4.460	5.680
Loss								.612	1.702	1.453	
Total	•	. 2			•			100,00	100.00	100.000	100.001
Per centage of lime							•	49.358	49.359	51.548	34.020
Per centage of phosphorus						•		.077	0.022	.056	.005
Per centage of sulphur								.017	not est.	.079	. 126

These limestones are quite pure enough and quite good for use as flux in the iron furnace. No. 1501 is a magnesian limestone. The proportions of phosphorus and sulphur are low in all of them. Nos. 1499 and 1500 would yield a very pure white lime on calcination.

No. 1502—CLAY IRON-STONE. Labeled "Lower block ore, near the level of the limestone ore. Alcorn Creek, Raccoon Furnace."

A fine-granular, dark-grey ore; adhering slightly to the tongue.

No. 1503—CLAY IRON-STONE. Labeled "Blue kidney ore, locally replacing the main block ore; from drift one mile southeast from Laurel Furnace."

A fine-granular ore, of a grey color more or less deep; with very thin incrustation of limonite ore. Some portions adhere to the tongue.

No. 1504 — CLAY IRON-STONE. Labeled "Main block ore, Amanda Furnace. Averaged by P. N. Moore."

A dark-grey granular proto-carbonate ore, with some dense irregular laminæ of limonite ore.

No. 1505—CLAY IRON-STONE. Labeled "Conglomerate ore, on Darby branch of Clay Lick, Buffalo Furnace. Average sample."

Principally grey granular proto-carbonate ore, with some limonite.

No. 1506—CLAY IRON-STONE. Labeled "Lower block ore," Wo-mack's bank ore, Old Town Creek. Sample from ore weathered six months. Collected by P. N. Moore.

Mostly dense, dark-grey, fine-granular clay iron-stone, with some coarser grained and softer, with a little limonite.

No. 1507—CLAY IRON-STONE. Labeled "Grey ore, or main block ore, Baker bank drift, Laurel Furnace. Averaged by P. N. Moore, from the stock pile. Identified by Mr. G. Coxe."

Mostly proto-carbonate ore, containing many encrinital fossils, with some little limonite.

No. 1508—CLAY IRON-STONE. Labeled "Grey ore from under the hearth rock sandstone, near Raccoon Furnace. Collected by P. N. Moore."

Mainly brownish-grey fine-granular carbonate, with a whitish cement. Contains some little bituminous matter. Incrusted somewhat with reddish-brown limonite ore.

108

COMPOSITION OF THESE GREENUP COUNTY CLAY IRON-STONES, DRIED AT 212° F.

	No. 1502	No. 1503	No. 1504	No. 1505	No. 1506	No. 1507	No. 1508
Specific gravity	3.280	3.297			3.263		
Iron carbonate	54.773	78.722	33.321	30.516	44.678	55.258	64.624
Iron peroxide	8.648	. 204	21.270	14.271	6.500	13.468	4.044
Alumina	7.800	2.746	4.991	6.197	4.178	.670	4.414
Lime carbonate	3.780	2.250	.980	16.980	2.230	4.880	1.340
Magnesia carbonate	3.088	. 380	-439	.591	1.903	4.528	.836
Manganese carbonate	1.204	.421	a trace.	a trace.	a trace.	.660	not est.
Phosphoric acid	-447	. 505	.434	.614	. 204	. 368	.217
Sulphuric acid	. 298	1.160	1.208	2.330	.250	1.043	. 563
Silica and insol. silicates. Water, bituminous matters,	20.250	11.340	31.730	28.980	36.88o	15.660	20.310
and loss		2.272	5.627		3.177	4.065	3.650
Total	100.288	100.000	100.000	100.429	100.000	100.000	100.000
Per centage of iron	29.851	38.146	30.975	22.270	26.073	36.103	33.627
Per centage of phosphorus	. 195	.221	. 189	.267	.089	. 200	.095
Per centage of sulphur .	. 105	. 524	.483	.905	. 104	.416	. 225
Per centage of silica	18.560	9.700	29.520	27.360	34.360	13.360	14.440

Some of the carbonate ores, which contain a larger proportion of iron peroxide, will be found described with the limonite ores. Phosphorus is in rather large proportion in Nos. 1502, 1503, 1504, and 1507, and sulphur exceeds in 1503, 1504, and 1505. Possibly some of this latter may be driven off in the process of roasting the ore. No. 1505, which contains the smallest proportion of iron, having nearly seventeen per cent. of carbonate of lime, may yet be profitably smelted, especially mixed with richer ores.

No. 1509—LIMONITE "Limestone ore, Samuel Wamock's land, Tygert Creek. Bed one foot thick. Collected by A. R. Crandall. Not an average sample." Generally of a dark reddish-brown, varying to blackish and yellowish colors. In irregular laminæ. Adhering to the tongue.

No. 1510—Limonite. Labeled "Average sample of lower Block ore, from branch of Tygert Creek."

Varying in color, hardness, &c., from dark-brown, hard, irregular laminæ, to yellowish-red and brownish ochreous. Powder of a brownish-yellow color.

No. 1511 — LIMONITE (with some proto-carbonate ore); labeled "Limestone ore, Hood's branch of Tygert's Creek. Average sample. Used at Raccoon Furnace."

In irregular laminæ of various tints of yellowish and reddish brown, with some portions of clay iron-stone.

No. 1512—LIMONITE, &c. "Average sample. Poynter bank.
Raccoon Furnace."

Dark brownish-red fragments, mixed some of clay iron-stone.

No. 1513—LIMONITE. "Average sample of Two Lick Limestone ore," Kenton Furnace. Averaged by P. N. Moore, from the stock pile."

Generally of a dark-brown color, with incrustations of soft ochreous ore.

No. 1514—Limonite. Labeled "Lower block ore," from Louder bank. Averaged by P. N. Moore.

In irregular dark-brown laminæ, with softer ochreous and grey material intermixed and incrusting.

No. 1515—LIMONITE. "Average sample of Coon Fork Limestone ore; taken from the unburnt kiln at Kenton Furnace by P. N. Moore, and identified by Mr. Folson."

A dense, chocolate-red ore, scarcely adhering to the tongue. Contains some iron proto-carbonate.

No. 1516—LIMONITE. Labeled "Shover drift Limestone ore. Average sample, by P. N. Moore, Kenton Furnace." A dense, chocolate-red colored ore, with but little ochreous material.

No. 1517—LIMONITE. Labeled "Limestone ore. Powder Milli Hollow, Kenton Furnace."

In irregular masses and laminæ of a chocolate-brown color, with soft ochreous ore between.

No. 1518—LIMONITE. "Average sample of lower Block ore, from James Thompson's bank, Kenton Furnace. Collected by P. N. Moore."

Laminæ of dense limonite, with softer ochreous materialbetween, and some clay iron-stone in the interior.

No. 1519—LIMONITE. Labeled "Lower Block ore. Average sample from Allen bank, Kenton Furnace. Collected by P. N. Moore."

Irregular laminæ of hard dark brown limonite, with much brownish-yellow softer mineral between, and some whitish, clay-like substance, in the crevices.

No. 1520—LIMONITE, &c. "Main Block ore, locally changed to a very calcareous ore, Buffalo Furnace. Averaged by P. N. Moore."

Ore partly of yellowish-grey iron proto-carbonate of a crystalline-granular structure, not adhering to the tongue; in parts changed into dark reddish-brown limonite, which adheres to the tongue. Contains some small scales of mica and a few green specks (which may contain iron phosphide).

No. 1521—LIMONITE. Labeled "Main Block ore, Little Morton bank, Laurel Furnace. Averaged by J. A. Monroe."

In irregular curved laminæ of various thicknesses, differing in color, from dark clove-brown, almost black, to reddish and yellowish-brown; with nodules and incrustations of softer ochreous ore. No. 1522—LIMONITE, &c. "Average sample of Kidney ore, above the main Block ore. From the Buffalo Furnace stock pile. Collected by P. N. Moore."

Dense dark and light-brown limonite, with a little ochreous ore; mixed with compact or fine-granular grey clay iron-stone.

No. 1523—LIMONITE. "Main Block ore, Brushy Knob bank, Laurel Furnace. Average sample, from the stock pile, by P. N. Moore." (Determine only iron and silica.)

Varying from hard dark-brown laminæ to brownish-yellow ochreous ore.

No. 1524—LIMONITE. "Kidney ore, Osenton bank, Laurel Furnace. Averaged by P. N. Moore. Identified by Mr. G. Cox." (Determine only the iron and silica.)

Curved irregular laminæ of dense dark colored limonite ore, inclosing nodules of compact clay iron-stone.

No. 1525—LIMONITE. "Rough ore, Darby branch of Clay Lick Creek. The upper of two lower block ores, Buffalo Furnace. Average sample, by P. N. Moore." (Determine only the iron and silica.)

Yellowish-brown limonite, mixed with grey iron proto-carbonate ore. Both showing an oölitic structure.

No. 1526—LIMONITE. "Kidney block ore, or main Block ore.

McAlister Point, Buffalo Furnace. Averaged by P. N.

Moore."

Mostly in dark, purplish-brown, irregular, curved laminæ. (One small nucleus of partly decomposed clay iron-stone noticed.)

No. 1527—LIMONITE. "Rough block ore; below the main Block ore, at Raccoon Furnace. Averaged by P. N. Moore."

Mostly in irregular, curved laminæ, with some softer ochreous ore included. No. 1528—LIMONITE. "Lower Block ore, on J. Downie's land, Old Town Creek. Averaged by P. N. Moore."

Mostly porous, ochreous ore, with some dense limonite laminæ included.

No. 1529—LIMONITE. "Limestone ore; called slate ore. Ridge between Cane Creek and Wilson Creek, Hunnewell Furnace. Average sample, by P. N. Moore."

Mostly moderately dense, irregular laminæ, of a handsome brownish-purple color, with some ochreous ore.

No. 1530—LIMONITE. Labeled "Lime kidney ore, Brush Creek, Pennsylvania Furnace. Average sample, by P. N. Moore."

Principally in irregular curved laminæ, of a dark color; somewhat oölitic; inclosing, and incrusted with, some little undecomposed clay iron-stone.

COMPOSITION OF THESE GREENUP COUNTY LIMONITES, DRIED AT 212° F.

			Secretary Control of the Control of									•
	No. 1509 No. 1		No. 1511	No. 1512	No. 1513	No. 1514	No. 1515	510 No. 1511 No. 1512 No. 1513 No. 1514 No. 1515 No. 1516 No. 1517 No. 1518 No.	No. 1517	No. 1518	No. 1519 No.	No. 1520
Iron, peroxide	80.040 2.680 not est. a trace. 425 .115 .264 *.584 10.000 6.560	41.556 8.604 .180 not est. .882 .851 .00.100 38.160	60.576 15.623 2.860 a trace. .619 .632 not est. †7.040 12.650	54.703 17.758 2.300 .440 .340 .499 .128 .680 .128 .680	67.859 1.160 .980 .120 1.275 .143 not est. †12.903 15.560	54.530 1.380 1.380 0.040 1.823 .908 .336 .336 .28.360	46.984 7.890 5.580 1.572 21.240 2.904 371 not est. 7.860 7.860	72.957 1.660 .640 .380 .083 .500 .178 .178 .15.160	49.770 6.315 .640 .380 .115 .115 a trace. 9.020 33.200	\$0.006 8.317 a trace. .380 .201 .767 .356 .11.760 .28.820 .100.607	41.390 6.777 .180 atrace065 .579 .579 .154 .154	23.396 14.972 14.972 14.077 14.421 33.775 1968 1968 157 157 16.240
Per centage of iron	56.280	29.089	49.945	46.865	47.501	38.171	39.025	\$1.070	34.839	35.004	28.973	23.597
Per centage of phosphorus	.050	.358	.276	.055	.062	.428	.131	812.	.072	.339	.252	.224
Per centage of sulphur	.107	.3.0	not est.	.272	not est.	.134	not est.	170.	a trace.	.142	190.	.070
Per centage of silica	not est.	not est.	not est.	12.960	11.560	not est.	not est.	not est.	32.960	not est.	not est.	13.530
* Potash = 0.346; soda = 0.238.		7	† And loss.		-	Carbonates.						

COMPOSITION OF THESE GREENUP COUNTY LIMONITES, DRIED AT 212° F.-Continued.

14										
	No. 1521.	No. 1522.	No. 1523.	No. 1524.	No. 1525.	No. 1526.	No. 1527.	No. 1528.	No. 1529.	No. 1530.
Iron, peroxide.	68.928	56.279	1	67.984		64.577	36.985	44.876	57 - 551	60.206
Iron, carbonate	2.768	4.709	-700	deter d.	not deter d.	not est.	5.508	4.083	6.017	1.044
Manganese, brown oxide Lime, carbonate	2,50 0,89 0,89	n trace.	54 (R. 8	deter'd.		944.	.520	966.	250	.285
Magnesia	. 249	674. 108.	not deter'd, not	deter'd.	not deter'd.	.172	.367	991.	.057	191.
Combined water	11.100	*9.173	not deter'd, not	not deter'd, not		*11.250	8.330	9.850	10.30	. 9.500
Silex and insoluble silicates. Moisture, carb, acid, and loss.	15.240		not deter'd, not	not deter'd, not	not deter'd.	21.230	46.760	39.080	25.450	25.930
Total	100.644	00.001				100.000	100.000	100.000	100.518	100.000
Per centage of iron	48.249	44.896	39.788	47.589	29.792	45.204	25.889	31.413	40.285	42.144
Per ceniage of phosphorus .	800.	. 262	ot deter'd.	not deter'd, not deter'd, not deter'd	not deter'd.	.075	091.	190.	.025	0/0.
Per centage of sulphur	.299	. 104	not deter'd.	not deter'd. not deter'd. not deter'd	not deter'd.	.070	.046	.049	.042	.341
Per centage of silica	13.600	15.260	24.060	12.900	40.160	18.600	44.460	35.960	18.860	20.860

· And loss.

Although some of these ores contain too much phosphorus to make tough iron, they are generally good and profitable. The intelligent reader can estimate their relative value by this table.

[See Appendix for other Greenup county ores, &c.]

No. 1531—Pig Iron. "Hot blast, No. 1 Foundry. Probably made in 1872 or 1873, Buffalo Furnace. Collected by P. N. Moorc."

Quite a coarse-grained, brilliant, grey iron. Yields to the file; flattens a little under the hammer.

No. 1532—Pig Iron. "Cold blast, No. 1 Foundry, Buffalo Furnace. Collected by P. N. Moore."

A moderately fine-grained, dark-grey iron, which yields easily to the file.

No. 1533—Pig Iron. "Silver-grey hot blast iron. Made when working very hot, so that it is very cold-short. Buffalo Furnace. Collected by P. N. Moore."

A mottled, nearly white, silvery iron. Soft enough to yield to the file, but quite brittle. Scarcely flattening at all under the hammer.

No. 1534—Pig Iron. "No. 1 Foundry, hot blast iron, Kenton Furnace. Collected by P. N. Moore."

A moderately coarse-grained, grey iron. Hard, but yields to the file. Extends considerably under the hammer.

No. 1535—Pig Iron. "Hot blast, No. 1 Foundry iron; made at the fifth casting after thirty-six hours stoppage, on full burthen. The third casting gave grey iron. Collected by P. N. Moore."

A moderately coarse-grained, grey iron.

No. 1536—Pig Iron. "No. 2, Foundry iron; from Hunnewell" (formerly Greenup) Furnace. Collected by P. N. Moore."

A moderately coarse-grained, grey iron; very hard, but yields to the file. Extends considerably under the hammer.

Sodium . . . . . .

Phosphorus . . . .

Sulphur . . . . .

Total carbon . . . .

116

Total . . . . .

	No. 1531.	No. 1532.	No. 1533.	No. 1534.	No. 1535.	No. 1536.
Specific gravity	6.825	6.944	6.872	6.897	7.117	7.041
Iron	91.656	94 · 739	88.106	92.724	91.668	92.368
Graphite	2.790	3.620	1.950	3.320	2.950	3.690
Combined carbon	a trace.	.780	.570	.660	1	1
Manganese	.084	.056	.014	.612	.332	.020
Silicon	4.106	.877	7.317	2.090	3.817	2.515
Slag	.600	.120	.900	.300	1.200	1.130
Aluminum	.399	.060	.165	.442	.128	. 582
Calcium	.168	.104	.128	.184	.075	.048
Magnesium	.095	.082	.125	.190	.122	a trace.
Potassium	.086	.048	.048	.104	not est.	.056
O 11						

.004

.622

.046

101.298

3.980

not est.

100.667

.334

.041

2.950

.684

.026

a trace.

101.119

3.690

.041

.609

.037

101.173

4.400

.002

.768

.019

100.112

2.520

.016

.695

.150

100.845

2.790

COMPOSITION OF THESE GREENUP COUNTY PIG IRONS.

[See Appendix for other pig irons of this county.]

No. 1537—Soil. "Surface soil, from near the top of Pea Ridge; two hundred and fifty feet above the railroad at Hunnewell, one and a half miles southwest of hill to east. 'Coaled land.' Has a second growth of oak, with a few maples, hickories, pines, &c. Above the limestone of Pea Ridge. Collected by J. A. Monroe."

Soil of a dark yellowish-grey color. The coarse sieve (289 meshes to inch) removed from it some fragments of ferruginous sandstone.

No. 1538—Soil. Labeled "Sub-soil of the preceding, to eighteen inches below the surface, &c."

Of a brownish-buff color; containing nearly half its weight of irregular fragments of ferruginous sandstone, with ferruginous concretions.

No. 1539 - Soil. Labeled "Under clay to the two preceding, taken to three feet below the surface."

Clay of a brownish-buff color, with lighter colored portions intermixed. Contains a considerable proportion of fragments of ferruginous sandstone and ferruginous concretions, but not quite so much as the preceding.

COMPOSITION OF THESE GREENUP COUNTY SOILS, DRIED AT 212° F.

	No. 1537.	No. 1538.	No. 1539.
Organic and volatile matters	5.050	4.030	5.105
Alumina	6.831	9.595	9.223
Manganese, brown oxide	a trace.	.123	.091
Magnesia	.089	.223	.034
Sulphuric acid	.058	.017	.019
Potash	.217	.231	.312
Soda	Not estima	.097	. 120
Sand and insoluble silicates	86.505	84.565	84.695
Water expelled at 380° F	1.000	.685	.615
Loss	.079	.319	
Total	100.000	100.000	100.406
Moisture expelled at 212° F	1.650	1.775	2.150
Potash in insoluble silicates	Not estima	ted.	
Soda in insoluble silicates	Not estima	ted.	
Character of soil	Coaled land		Under clay

These soils are of medium good quality; they would be benefited by top-dressing with lime, and, if well drained, could be made quite productive by judicious management, the use of green crops, and other fertilizers. The surface soil is not as rich in the mineral fertilizers as the sub-soil and under clay.

## HARDIN COUNTY.

No. 1540—Soil. "Forty-five years in cultivation. Taken to the depth of eight inches. Collected by C. S. Schenk."

Farm of H. B. Helm; three thousand two hundred and fifty feet west from Elizabethtown, and sixteen hundred feet to the

right of the Elizabethtown and Paducah Railroad (facing Paducah), twenty feet above the rail. Slope 1:25. On lime-stone substratum. Timber: elm, sycamore, shell-bark hickory, hazelnut, sumach, sassafras, dogwood, &c. Rotation of crops: lately, two years in corn; one in oats, with three in clover, followed by two in wheat. Yield: of corn, thirty bushels; wheat, fifteen to twenty; of oats, twenty-five bushels to the acre. The land has been kept in good order and has had some straw manure.

Soil of a dark drab color. The coarse sieve (two hundred and eighty-nine meshes to inch) sifted out a little shot-iron ore and small fragments of ferruginous sandstone.

No. 1541—"Sub-soil of the preceding; one thousand feet to the right of the railroad, and three thousand four hundred feet from Elizabethtown, on the Elizabethtown and Paducah Railroad Twenty feet above the rail. Taken to the depth of from eight to twelve inches. Collected by C. S. Schenk."

Of a lighter color than the preceding; greyish-buff. Contains some fragments of chert and small quartzose and ferruginous concretions.

No. 1542—"Under Clay to the two preceding, taken at a depth of from twelve to thirty-six inches. Collected by C. S. Schenk."

Of a lighter color than the preceding, and more yellowish. Contains some small fragments of weathered chert and ferruginous sandstone, and small concretions of oxides of iron and manganese.

No. 1543—"VIRGIN SOIL, taken to the depth of eight inches. Farm of J. B. Bryan. Collected by C. S. Schenk."

Four thousand eight hundred feet west from Elizabethtown, on the Elizabethtown and Paducah Railroad, and twenty-eight hundred feet from the railroad. Thirty feet above the rail. Substratum, limestone. Timber: post oak, black and red oak, hickory, hazel, sumach, sassafras, and dogwood. The soil in 118

this neighborhood, cultivated carelessly, yields thirty-five bushels of corn to the acre.

Soil of a dark drab color. Contains a notable quantity of fragments of weathered chert and some of a fossil cyathophyllum.

No. 1544—"Sub-soil of the preceding, from the depth of from eight to thirty-four inches. The limestone rock is thirty-six inches below the surface. Collected by C. S. Schenk."

Color lighter than that of preceding; of brownish-buff. Contains fragments of chert, more or less weathered, and of fossils.

No. 1545—"Soil of an old field, over forty years in cultivation without manure. Collected by C. S. Schenk."

Seven thousand two hundred and sixty feet west of Elizabethtown, on the Elizabethtown and Paducah Railroad, one thousand one hundred and forty-three feet to the left of that road, and ten feet above the level of the rail. Slope = 1:70. Sample to the depth of eight inches. Timber: same as the preceding. Rotation of crops: wheat, oats, clover, &c. Yields, when well managed, thirty bushels of corn, fifteen to sixteen of wheat, and twenty of oats, to the acre.

Soil of a dark drab color. Contains only a few small fragments (chips) of flint.

No. 1546—"Sub-soil of the preceding, taken from eight to thirty-four inches from the surface. Collected by C. S. Schenk."

Sub-soil of a lighter and more yellowish color than the preceding; brownish-buff.

No. 1547—VIRGIN SOIL, taken to the depth of eight inches. Collected by C. S. Schenk."

Field seven thousand two hundred and sixty feet west from Elizabethtown, eight hundred and thirty-seven feet to the left of Elizabethtown and Paducah Railroad, and ten feet above the level of the rail. Slope = 1:65. Has been cultivated one year in corn, producing forty bushels to the acre; has been

resting five years. Had no manure. Substratum limestone, at the depth of ten feet.

Soil of a dark drab color; contains no gravel, and very few small fragments of weathered chert and decayed vegetable roots.

No. 1548—"Sub-soil of the preceding, taken at the depth of from ten to thirty-four inches. Collected by C. S. Schenk."

Sub-soil of a handsome brownish-salmon color.

No. 1549—"New Soil, to the depth of eight inches, farm of Daniel Klingclsmith's heirs. Collected by C. S. Schenk."

Eleven thousand three hundred and fifty feet west of Elizabethtown, on the Elizabethtown and Paducah Railroad, and two hundred and fifty feet to the north. Three feet above the level of the rail. Slope = 1:45. Substratum, limestone. Has been in cultivation five years. Rotation of crops: two years in corn; then one each in wheat, oats, and corn. Rented out land. No manure. Yields, of corn, thirty bushels; of wheat, twenty; and of oats, twenty-five bushels to the acre.

Soil of a brownish, dark-grey color. Contains no gravel.

No. 1550—"Sub-soil to the preceding, taken at the depth of from eight to thirty-six inches from the surface. Collected by C. S. Schenk."

Sub-soil of a greyish-buff color. Contains some fragments of weathered chert.

No. 1551—"Soil, taken to the depth of eight inches, from an old field long in cultivation; rented out, and supposed to be worn out. Collected by C. S. Schenk."

Land of heirs of Daniel Klingelsmith, thirteen thousand eight hundred and eighty feet west from Elizabethtown, on Elizabethtown and Paducah Railroad; fifty feet to the right, on a level with the rail. Slope = 1:15. Rotation of crops: corn, wheat, oats, clover. Yields, of corn, seventeen bushels; of wheat, twelve; of oats, fifteen to sixteen bushels to the acre. No manure.

Soil of a brownish drab color. Contains some few small fragments of much weathered chert.

No. 1552—"Sub-soil to the preceding, taken at from eight to thirty-nine inches from the surface. Collected by C. S. Schenk."

Color much like that of the preceding soil. No gravel or chert fragments sifted out.

No. 1553—"VIRGIN SOIL. Woodland. Farm of Hayden English, sixty feet west of the four mile-post, on the Elizabethtown and Paducah Railroad; four feet above the level of the rail. Collected by C. S. Schenk."

Sample taken to the depth of twelve inches. Slope = 1:15. Timber: scrub oak, black oak, and black jack, generally of small size. Undergrowth: small sumach, sassafras, &c. Yield of such land is, of corn, eleven bushels; of wheat, six; of oats, eleven bushels to the acre.

Dry soil of a grey-buff color.

No. 1554—"Sub-soil of the preceding, taken from twelve to twenty-six inches below the surface." Collected by C. S. Schenk."

Dry soil of a lighter color and more yellowish than the preceding.

No. 1555—"New Soil, five years in cultivation, from farm of J. English. Collected by C. S. Schenk."

Sample taken to depth of eight inches, at a point two hund-dred and seventy feet west of the six mile-post, on the Elizabethtown and Paducah Railroad; twenty-one hundred feet to the left of the railroad, and at a level of ten feet above the rail. Slope = 1:75. Timber: black, white, red, and post oak, hickory, chestnut, &c. Rotation of crops: two years in corn, one each in oats, wheat, and corn. No manure. Yield of corn, thirty; of wheat, twelve; and of oats, twenty bushels to the acre.

Dried soil of a drab color.

No. 1556—"Sub-soil of the preceding, taken at a depth of from eight to thirty-six inches. Collected by C. S. Schenk."

Dry sub-soil of a grey-buff color; lighter and more yellowish than preceding.

No. 1557—"Soil from an old field, forty-five years in cultivation. Snider's farm. Collected by C. S. Schenk."

Sample taken to the depth of eight inches, at a point thirteen hundred feet west of the six mile-post, on the Elizabethtown and Paducah Railroad, and twelve hundred and seventy feet to the left, at a level of ten feet above the rail. Slope 1:35. Section of the hole where the soil was taken: soil, eight inches; yellow clay, twenty-two inches; red clay, six inches. (The red clay land is considered best in this part of the State.) Roots penetrate to depth of eight feet, where the rock is found. Rotation of crops: corn, wheat, oats. Has been four years in pasture, and the last two years in grass. Yield: corn, twenty-two; oats, fifteen to sixteen; wheat, eight; potatoes, fifty-five; rye, ten bushels, and tobacco, eight hundred pounds to the acre.

Dried soil of a drab color.

No. 1558—"Sub-soil of the preceding, taken at a depth of from eight to thirty-six inches. Collected by C. S. Schenk."

Dried sub-soil of a brownish-orange color.

No. 1559—"Soil of an old field, forty years or more in cultivation." Collected by C. S. Schenk."

Sample taken to the depth of six inches, at a point two hundred and fifty feet west of the nine mile-post (Long Grove Station). Three hundred and fifty feet to the right of the Elizabethtown and Paducah Railroad, at a level of twelve feet above the rail. Slope = 1:19. Timber, much like that in preceding soils of this county. Rotation of crops, for the last nine years: four in corn, one in wheat, with three in clover and one in wheat. No manure. Yield: corn, twenty-two; wheat, eight; oats, fifteen bushels to the acre.

Dried soil of a yellowish umber-grey color.

No. 1560—"Sub-soil of the preceding, taken at from six to thirty-six inches from the surface. Collected by C. S. Schenk." Dried sub-soil of a dark grey-buff color.

No. 1561—"Soil of an old field, farm of E. Hansborough. Collected by C. S. Schenk."

Sample taken to the depth of five inches, at a point one thousand three hundred and twenty-seven feet west of the three mile-post; eight and a quarter miles from Elizabethtown, on the Elizabethtown and Paducah Railroad; one thousand three hundred and fifty feet to the left of that road, and level with the rail. Slope = 1:24. Timber much like that on the preceding soils. Substratum limestone, at depth of forty-five inches. Rotation of crops: corn, wheat, oats, clover. No manure. Yield: corn, thirty; wheat, eighteen; oats, thirty; potatoes, forty bushels; tobacco, eight hundred to one thousand two hundred pounds to the acre. One of the best farms in this locality. Land kept in good order.

Dried soil darker than the next preceding, of a brownishumber dark grey color.

No. 1562—Sub-soil of the preceding. Sample taken from five to forty-five inches below the surface. Collected by C. S. Schenk."

Dried sub-soil of a light brick-red color. Somewhat adhesive.

No. 1563—"Soil of an old field, forty years in cultivation, without manure. Collected by C. S. Schenk."

Sample taken to the depth of ten inches, at a point two hundred feet, to the right of the seven mile-post, Elizabeth-town and Paducah Railroad; level five feet above the rail. Substratum limestone. Slope = 1:50. Rotation of crops: corn, wheat, oats, clover. Land kept in good order. Yield of corn, twenty-five; of wheat, twelve; of oats, twenty bushels to the acre.

Dried soil of a yellowish-umber color.

No. 1564—"Sub-soil of the preceding, taken at a depth of from ten to thirty-eight inches. Collected by C. S. Schenk."

Dried sub-soil of a light yellowish-brick color. Somewhat adhesive.

No. 1565—"VIRGIN SOIL, Woodland, on Hanson Duncan's farm. Collected by C. S. Schenk."

Sample taken to ten inches in depth, at a point seven hundred and sixty feet east of his house; about eighty feet below the Elizabethtown and Paducah Railroad at East View. Rock substratum—limestone.

Dried soil of a yellowish light-umber color.

No. 1566—"Sub-soil of the preceding, taken at a depth of from ten to forty-six inches. Collected by C. S. Schenk."

Dried sub-soil of a light yellowish-brick color.

No. 1567—Soil from an old field, twenty-four years in cultivation. Collected by C. S. Schenk."

Sample taken to the depth of eight inches, at a point twelve hundred feet, north 50° east from Hanson Duncan's house; one hundred and seventeen feet below the railroad at East View Station. Slope = 1:26. Substratum limestone. Rotation of crops: 1. corn, 1. rye, 3. clover, 1. wheat. No manure. Yield: corn, thirty-five; wheat, seventeen; rye, six to seven bushels to the acre.

Dried soil of a yellowish light-umber color.

No. 1568—"Sub-soil of the preceding, taken at a depth of from eight to forty inches. Collected by C. S. Schenk."

Dried sub-soil of a light yellowish-brick color.

No. 1569—"VIRGIN SOIL, one year in cultivation, from sand land on Hanson Duncan's farm, near East View. Collected by C. S. Schenk."

Sample taken to the depth of four inches, at a point four hundred and twenty feet west of his house. Height level with

the roof of his house. Slope = 1:7. Substratum limestone. Timber about the same as described above. Land not much cultivated; considered too poor except for peaches, apples, &c.; but tobacco yields six hundred pounds to the acre.

Dried soil of a yellowish umber-grey; lighter colored than the preceding sample.

- No. 1570—Sub-soil of the preceding, taken at a depth of from four to thirty-six inches. Collected by C. S. Schenk."

  Sub-soil of a light yellowish-brick color.
- No. 1571—Soil from an old field, sixteen years in cultivation, on Hanson Duncan's farm, near East View. Collected by C. S. Schenk."

Sample taken to depth of six inches, at a point seven hundred and fifty feet, north 20° east from his house. Height, six feet above his house. Slope = 1:7. Substratum sandstone. In some years it has yielded eleven bushels of corn to the acre. Is now in orchard. Produces good peaches.

Dried soil of a yellowish light umber-grey color.

No. 1572—Sub-soil of the preceding, taken at a depth of from six to thirty-four inches. Collected by C. S. Schenk."

Sub-soil of a light brick-color, varying in intensity. Contains many angular fragments of soft, friable, ferruginous sandstone.

Note.—For a continuation of this serial collection of soils, made on or near the line of the Elizabethtown and Paducah Railroad, by Mr. C. S. Schenk, see Grayson and Ohio counties.

COMPOSITION OF THESE HARDIN COUNTY SOILS, &c., DRIED AT 212º F.

No. 1552.	3.150 11.900 .175 .321 .108 a trace. .150 .150 .700	2.200	not est.	not est.	Sub-soil.
No. 1551.	3.535 8.784 .230 .152 .156 a trace. .159 .026 .86.215 .800	1.650	0.864	.444	Sub-soil. New soil. Sub-suil. Old field. Sub-soil
542. No. 1543. No. 1544. No. 1545. No. 1546. No. 1547. No. 1548. No. 1549. No. 1550. No. 1551.	2.750 8.870 .245 .284 .134 a trace. .399 .054 86.640 .850	1.875	not est.	not est.	Sub-soil.
No. 1549.	6.865 .495 .501 .108 attace. .209 .079 .079 .079 .079	1.650	not est.	not est.	New soil.
No. 1548.	3.035 11.624 .110 .267 .216 a trace. .256 .160 83.925 .600	1.800	not est.	not est.	Sub-soil.
No. 1547.	3.300 7.705 .295 .339 .156 a trace. .193 .027 86.815 1.050 .120	1.500	not est.	not est.	Virgin soil.
No. 1546.	2.025 9.190 .195 .140 .125 a trace. .327 .037 86.840 .725 396	1.700	not est.	not est.	Sub-soil.
No. 1545.	3.100 6.905 .245 .258 .204 a trace. .33 87.465 1.100 382	1.325	0.977	0.280	Sub-soil. Old field, Sub-soil
No. 1544.	2.500 9.705 .145 .240 .125 a trace. .462 .635 .85.925 .850	1.650	0.798	0.406	Sub-soil.
No. 1543.	2.950 5.786 .195 .375 .375 .375 .375 .376 .376 .900 .186	1.125	0.617	0.188	Virgin soil.
	2.650 10.775 .110 .158 .115 a trace. .265 .330 84.740 .750 .407	2.140	not est.	not est.	Under clay.
No. 1540. No. 1541. No. 1	2.600 8.617 .195 .431 .123 a trace. .002 86.975 .925	1.575	not est.	not est.	Sub-soil.
No. 1540.	3.675 5.790 .160 .250 .160 a trace. .154 .109 88.590 1.235	1.510	0.803	.467	Old field soil.
	Organic and vol. matters Alumina, and iron and manganese oxides Lime carbonate Magnesia Sulphuric acid Sulphuric acid Fotash (ext'ed by acid) Soda (extracted by acid) Sand and insol. silicates Water expel'd at 380° F. Loss Total	Hygroscopic moisture .	Potash in insol. silicates	Soda in insol, silicates.	Character of soil

THESE HARDIN COUNTY SOILS, &c., DRIED AT 212º F.-(Continued.)

Organic and volatile matters . 1.950   1.956   No. 1556   No. 1556   No. 1556   No. 1561   No. 1561   No. 1561   No. 1563   No. 1564   No. 1564   No. 1565   No. 1565   No. 1564   No. 1565   No. 1565	COMPOSITION OF THESE HARDIN	TON OF	THESE	HARDI		COUNTY SOILS, &c.,		DRIED AL	212	F.—(Continued.)	- Inapur		
1.950   1.990   2.185   2.135   2.100   2.935   2.625   3.525   3.215   3.785   3.080     2.926   8.344   5.692   9.476   6.329   12.798   7.388   10.445   6.790   15.763   6.564     3.167   2.24   2.70   2.20   2.20   1.94   0.95   3.12     3.167   2.24   3.13   2.208   1.140   2.400   1.485   3.215   3.215   3.280     3.167   2.20   1.400   2.400   1.485   2.650   1.385   2.450   1.00.001     3.183   2.200   1.400   2.400   1.485   2.650   1.385   2.450   1.00.001     3.185   2.200   1.400   2.400   1.485   2.650   1.385   2.450   1.00.001     3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.180   3.180     3.180   3.18		No. 1553	No. 1554	No. 1555	No. 1556	No. 1557	N. 1558	Vo. 1559	Vo. 1560	Vo. 1561	No. 1562	Vo. 1563	Vo. 1564
5-926         8.344         5-692         9-476         6.359         12.798         7.388         10.445         6.790         15.763         6.564           130         .080         .270         .220         .220         .190         .120         .370         .620         .445           167         .204         .271         .220         .194         .196         .190         .189         .120         .421           167         .204         .213         .208         .050         .194         .095         .189         .120         .095           167         .093         .124         .190         .122         .144         .123         .124         .120         .123           .005         .126         .093         .122         .221         .221         .399         .220         .421         .123           .005         .120         .037         .045         .045         .025         .140         87.765         77.375         87.975           .000         .000         .000         .000         .000         .000         .000         .000         .000         .000         .000         .000         .000         .000         .000	ters .	1.950	1.990	2.185	2.135	2.100	2.935	2.625	2.525	3.215	3.785	3.080	2.785
1. 136	Alumina, and iron and manganese oxides	5.926	8.344	5.692	9.476	6.359	12.798	7.388	10.445	6.790	15.763	6.564	10.763
1. 163		167	204	213	.134	.05°.	.194	.095			.095		. 124 . 1790
505 S. 1120 S. 037 S. 045 S. 240 S. 9.790 S. 165 S. 140 S. 1755 S. 17.575 S. 975		a trace.	a trace.	1 trace.	a trace.	_	a trace.	a trace.	_	=	.421	•	212.
. 1.585 2.200 1.400 2.400 1.485 2.650 1.385 2.450 1.1400 1.515 1.255 1.255 1.1400 1.00.000 1.	· ·	200.	SS 1120	.037	.045	89.790	.033	88.090	85.140	87.765	77.375	87.975	84.290
100.000         100.019         100.107         100.000 <t< td=""><td>Water expelled at 380° F</td><td>.935</td><td>577</td><td>1.425</td><td>.329</td><td>.950</td><td>.975</td><td>1.150</td><td></td><td>1.400</td><td>.201</td><td>022</td><td>6 .  </td></t<>	Water expelled at 380° F	.935	577	1.425	.329	.950	.975	1.150		1.400	.201	022	6 .
1.585 2.200 1.400 2.400 1.485 2.650 1.385 2.450 1.600 3.860 1.300 1.140 not est. not est. not est. not est. not est373 not est339 not est731 .420 not est731 Sub-soil. Old field. Sub-soil.		100.000		100.107	100.000	100.000				100.152	100.000	100.000	100.305
1.140         not est.         not est.         0.560         not est.         0.675         not est.         1.148         .974         not est.           .641         not est.         not est.         .373         not est.         .339         not est.         .731         .420         not est.           Virgin         Sub-soil.         New soil.         Sub-soil.         Old field.	:	1.585	2,200	1.400	2.400	1.485	2.650	1.385	2.450	1.600	3.860	1.300	1.375
.641 not est. not est. not est373 not est339 not est731 .420 not est. Virgin Sub-soil. Old field. Sub-soil. Old field. Sub-soil. Old field. Sub-soil. Old field.	licates	97	- 11	not est.	not est.	0.560	not est.	0.675	not est.	1.148	.974	not est.	not est.
Virgin Sub-soil. New soil. Sub-soil. Old field. Sub-soil. Old field. Sub-soil. Old field. Sub-soil. Old field.	cates	149.	- 11	not est.	not est.	.373	not est.	.339	not est.	.731	.420	not est.	not est.
soil.		Virgin	u	New soil	Sub-soil.	Old field	Sub-soil.	Old field.	Sub-soil.	Old field	Sub-soil.	Old field.	
	:	soil.											

	No. 1571. No. 1572.	2.165 2.575 2.775 2.740 6.900 .045 .045 .067 .067 .102 a trace135 .045 .045 .045 .045 .045 .045 .045 .04	0.800 2.075	.236 .165 Old field. Sub-soil.
SOILS, &c., DRIED AT 2120 F(Continued.)	No. 1570.	2.225 7.015 .080 .104 .134 a trace. .202 .076 89.855 .450	00.1 1.900	Sub-soil.
T 212 F	No. 1569.	2.600 4.465 .176 .176 .147 a frace. .212 .055 91.790 .775	1.225	.444 Virgin soil.
DRIED A	No. 1568.	2.575 5.828 .236 .078 .112 a trace. .183 .053 90.470 .475	2.360 not est.	not est. Sub-soil.
SOILS, &c.	No. 1567.	3.050 5.550 .305 .240 .102 a trace. .173 a trace. .89.290 1.100	r.690	not est. Old field.
COUNTY	No. 1566.	4.400 6.395 .270 .205 .045 a trace. .202 .050 .88.425 .650	1.800 not est.	not est. Sub-soil.
HARDIN COUNTY	No. 1565.	3.215 5.365 .445 .168 .172 a trace. .188 .041 87.940 1.525 .841	1.890	.350 Virgin soil.
COMPOSITION OF THESE		Organic and volatile matters	Hygroscopic moisture	Soda in the insoluble silicates

For the other soils of this series, collected along the line of the Elizabethtown and Paducah Railroad by Mr. C. Schenk, see Grayson and Ohio counties. The remarks appended to the Grayson county soils will apply to these with some obvious local variations.

#### HENRY COUNTY.

No. 1575—Galena. "From Roberts' lode, north opening. Carefully averaged, by Prof. N. S. Shaler."

Cubical and granular galena, disseminated in white, compact, baryta sulphate; with some zinc blende (zinc sulphide).

The galena was selected from the mixed lumps, simply for assaying to determine the presence or proportion of silver.

No. 1576—GALENA "From Roberts' lode, south opening, &c.

Like the preceding; but containing a larger proportion of galena. The galena was selected from the lumps for analysis.

Fused with the usual flux of carbonate of soda, nitrate of potash and salt; the former, No. 1575, gave 72.70 to 76.585 per cent. of lead; the latter, No. 1576, gave about seventy-one and a half per cent. This does not of course represent all the lead existing in the selected galena, but is supposed to contain all the silver.

The well washed lead buttons were dissolved, severally, in dilute nitric acid; and to the very much diluted solutions a solution of lead chloride was added.

The former, No. 1575, gave a faint precipitate of silver chloride on standing—not enough to justify its extraction; the latter gave no sensible precipitate of the silver chloride. These ores seem, therefore, to be too poor in silver to pay for its extraction.

Another specimen of lead ore, from an unopened lode, on Mill branch of Six Mile Creek, contained so small a proportion of galena to the baryta sulphate that it was not thought proper to analyze it.

No. 1577—Marly Shale or indurated marl. "Cut of the Cumberland and Ohio Railroad, Eminence, Henry county. Collected by Prof. N. S. Shaler."

An olive-grey, indurated marl; containing nodules of chætetes, and portions of other Silurian fossils.

## COMPOSITION, DRIED AT 212° F.

											3	-5			- 53	7.5	. 350							1	) -: H:-V:-U:-V
Silica					٠	•														•				.	23.700
Alumina				٠																				. [	7.146
Iron and mangan	ese	0	xie	des	s .																			. [	11.040
Lime carbonate.														2										.	44.560
Magnesia																								. [	.310
Phosphoric acid.																								. 1	1.164
Sulphuric acid .																								. 1	.961
Potash			_				12			-				-											2,100
Soda	-								2	-			-	_	_	4	_	_	_		_			_	.623
Water expelled at	re	d	he	at	, a	nd	1 1	055											•				•		8.396
Total																								-	100,000

The large proportions of lime, potash, phosphoric acid, &c., in this marly shale, would doubtless make it valuable as a top-dressing on exhausted light soils; but it is not rich enough in the mineral fertilizers to justify much expenditure for transportation.

## HOPKINS COUNTY.

No. 1578—Coal. "Mr. Wm. Mills' coal, just partially opened. Nortonsville, Hopkins county. Collected by C. J. Norwood. (Probably not a fair average sample.")

Generally a jet-black, glossy coal; breaks in part in thinlayers, with some compressed fibrous coal between. Some thin laminæ of pyrites apparent. (Specimen seems to contain an inordinate proportion of pyrites.)

No. 1579—Coal. "St. Charles Mines. Average sample, by C. J. Norwood." (Coal D.)

A jet-black, glossy coal; iridescent in parts. Some fibrous coal between the laminæ, and but little appearance of pyrites.

COMPOSITION OF THESE HOPKINS COUNTY COALS, AIR-DRIED.

	No. 1578.	No. 1579.
Specific gravity	 1.448	1.322
Hygroscopic moisture	 30.00	3.20 35.90 60.90
Total	 100.00	100.00
Total volatile matters	 15.50	39.10 54.00 6.90
Character of the coke	 Spongy.	Light spongy.
Color of the ash	 Dark grey- purple.	Light lilac- grey.
Per centage of sulphur	 7.280	2.759

No. 1579 is a very good coal, containing but little earthy matter and a moderate proportion of sulphur. The other exceeds the average proportions of these; but is not probably a fair sample. It is well known that coal beds vary greatly in their different layers; and this may prove to be a good coal when the bed is fairly opened.

No. 1580—"LIMONITE, ochreous, from near St. Charles Mines, Mr. Norton's land. On the working coal. Collected by C J. Norwood."

Flat kidney-form concretions, of a handsome brownish-yellow color, of different shades. Easily scratched with the nail; adheres to the tongue.

## CHEMICAL REPORT.

## COMPOSITION, DRIED AT 212º F.

										0,5-3	30.3																		· ·
Iron peroxide.																												. [	50.850
Alumina																													5.462
Manganese ox	ide .																											. I	a trace.
Lime carbonat	e				•	•					•																	. 1	3.129
Magnesia											•			•			•					•	•					. 1	1.546
Phosphoric aci	d	•					•		•				•	•						•		•		•		•		î.	.198
Sulphuric acid		-	-	-	-			-	-	-	0			-	-	-	2			-	- 20	-	-		-			- 1	. 189
Water expelled	l at i	ed	h	eat		-			-					Ī	-	-					-	0		-	•		-	- î l	10.530
Silica and inso	luble	si	lic	ate	ς.		•	•	•	•	•	•	•	•		•	0		•	•	-	0		•	•	•	•	: 1	27.680
Loss																													.416
2033		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠,	.410
Total	• •	•	•		•	•		•	•	٠	٠	٠	•	•	•														100,000
Per centage of	iron		•					•				•		•	•				C 7-53	- 476									35 · 595
Per centage of	sulp	hu	г.														•												.075
Per centage of	silic	a .										•													•			_	22,220
Per centage of	pho	spl	hoi	rus			•							•		•	•	•									•	-	.086

This is rich enough to be smelted for iron, and might make a good ochre pigment on grinding.

# KENTON COUNTY.

No. 1581 — "SILICIOUS GRIT at first toll-gate, two miles from Covington, on Lexington Turnpike. Collected by Prof. N. S. Shaler."

A brownish-grey, ferruginous impure sandy mass.

No. 1582—"SILICIOUS GRIT from same locality as preceding. Used for moulding sand. Collected by Prof. N. S. Shaler."

An impure, reddish-brown friable sandy mass; infiltrated with iron oxide; varying in tint from grey to deep brown. The sand grains are rounded.

COMPOSITION OF THESE KENTON COUNTY GRITS, DRIED AT 212° F.

																						No. 1581.	No. 1582.
Silica																						77.460	75.700
Alumina, and iro	n	an	d	ma	m	zai	nes	se	0	ĸi	de	s.										16.500	15.793
Lime carbonate.																						.480	.660
Magnesia																						.121	.214
Potash																						.828	.847
Soda																				•			.762
Phosphoric acid	•	•								•				•	•	•				•		not est,	.639
Sulphuric acid .		•			•					•							٠.				•	not est.	not est.
Water expelled a	1	ed	l h	ea	t.					•			•	•		•			٠	•	•		5.100
Total																						100.469	99.716

The amount of alkalies contained in these impure sands is somewhat remarkable. They exist in them, however, mostly in the silicates which are insoluble in acids; and were separated in the analyses, by the process of fusion with the mixture of lime carbonate and ammonium chloride, &c., according to the method of J. Lawrence Smith. Notwithstanding the unavailable condition of these alkalies, these sands might prove useful additions to heavy clay soils, more especially because of their notable proportion of phosphoric acid. For this purpose, however, they could only be employed in the close vicinity of their beds, as they would not pay for long transportation.

No. 1583 -- "Clay, supposed to be in the Cincinnati Group of the Lower Silurian formation. Lexington Turnpike, two miles south of Covington. Top section just below that of the preceding grits. Collected by Prof. N. S. Shaler."

A laminated or shaly clay of handsome light-buff and bluishgrey colors, alternating.

No. 1584—CLAY. "Clay-pit at brick-yard. Head of Russel street, Covington. Average of the nine-feet section. Collected by Prof. N. S. Shaler."

A yellowish ferruginous clay; mottled with light bluishgrey; containing fine silicious grains. No. 1585—MARLY SHALE. "Junction of the Ohio and Licking rivers, twelve feet above low water mark. Cincinnati (Hudson River) Group. Collected by Prof. N. S. Shaler."

A fine-grained, dark-grey shale; dull; adhering somewhat to the tongue.

No. 1586—Marly Shale. Labeled "Fine shales, between impure limestone; five feet above low water mark. Whitehall. No fossils. Collected by Prof. N. S. Shaler."

A soft friable shale; dark-grey in the fresh fracture; adhering to the tongue.

COMPOSITION OF THESE KENTON COUNTY MARLY CLAYS AND SHALES DRIED AT 212° F.

	No. 1583.	No. 1584.	No. 1585.	No. 1586.
Silica	56.400	68.360	43.461	47.160
Alumina, and iron and manganese oxides	29.971	22.256	21.000	22.850
Lime carbonate	.760	1.000	27.040	20.140
Magnesia	1.514	1.181	.680	.840
Phosphoric acid	.166	.258	.607	.128
Sulphuric acid	not est.	not est.	not est.	not est.
Potash	3.538	2.139	2.447	2.301
Soda	. 551	.906	.915	1.590
Water expelled at red heat	7.100	3.650	3.850	5.200
Total	100.000	99.750	100.000	100.209

These marly shales would undoubtedly be valuable for topdressing poor light soils in their vicinity, notwithstanding most of their alkaline ingredients are in a state of combination which renders them, for the present, unavailable for plant nourishment. The gradual action of the atmospheric agencies and of humus, as well as that of the lime, will eventually bring them into a soluble state. The latter two may be considered the best for this purpose.

No. 1587—Limestone. Labeled "Blue argillaceous limestone. Low water mark. Whitehall, near Covington. Collected by Prof. N. S. Shaler."

A fine-grained, dark-grey limestone. Not adhering to the tongue.

## COMPOSITION, DRIED AT 2120 F .- SPECIFIC GRAVITY = 2.720.

Lime carbonate	64.240 = 35.974 per cent	. of lime.
Magnesia carbonate	6.152	
Alumina, and iron and manganese oxides	4.960	
Phosphoric acid		
Sulphuric acid	not est.	
Potash	643	
Soda		
Silex and insoluble silicates	23.860	
	100.306	

This limestone, like most of the layers of the Lower Silurian limestone (or blue limestone, so-called), is, in consequence of its large proportions of alkalies and phosphoric acid, peculiarly suited to agricultural purposes. The use of this lime, in the calcined state, upon our old fields, if properly managed and applied just before the clover crop, in a rotation, would doubtless be quite beneficial in restoring fertility.

#### LAWRENCE COUNTY.

No. 1588—"COAL. No. 3, "From McHenry's coal bank, six miles south of Louisa. Average sample, by A. R. Crandall."

A jet-black coal, with very little fibrous coal and no appearance of pyrites.

No. 1589—"COAL. No. 1, from F. Swetman's bank, Brushy Creek. Collected by A. R. Crandall."

A jet-black coal, with some little external earthy or ferruginous staining, and but little fibrous coal or pyrites.

No. 1590—Coal. No. 1, "From near Henderson, Boggs' Mill, Cane's Creek. Collected by A. R. Crandall."

Rather a dull-black coal, breaking into thin laminæ, with fibrous coal between, but with little appearance of pyrites. Some external ferruginous stain.

No. 1591—Coal. No. 3. "Holbrook's coal, Brushy Creek. Collected by A. R. Crandall."

Rather a dull-black coal, breaking into thin laminæ, with fibrous coal between, but with little appearance of pyrites.

No. 1592—Coal. No. 3. "Mr. Boggs' bank, one mile from mouth of Cane's Creek. Upper portion of the coal. Collected by A. R. Crandall."

A jet-black coal, with some fibrous coal between the laminæ, but with little appearance of pyrites.

No. 1593—Coal. No. 3. "Mr. Boggs' bank, &c., &c. Lower portion of the coal. Collected by A. R. Crandall."

Breaking into thin laminæ, with fibrous coal between. Some external ferruginous incrustation.

COMPOSITION OF THESE LAWRENCE COUNTY COALS, AIR-DRIED.

	No. 1588	No. 1589	No. 1590	No. 1591	No. 1592	No. 1593
Specific gravity	1.316	1.281	1.376	1.349	1.350	1.284
Hygroscopic moisture	4.60 35.70 59.70	5.10 35.30 59.60	3.30 35.16 61.54	2.10 33.90 64.00	2.50 38.56 58.94	2.50 39.00 58.50
Total	100.00	100.00	100.00	100.00	100.00	100.00
Total volatile matters	40.30 53.28 6.42	40.40 57.80 1.80	38.46 47.84 13.70	36.00 56.00 8.00	41.06 51.44 7.50	41.50 54.76 3.74
Total	100.00	100.00	100.00	100.00	100.00	100.00
Character of the coke	Spongy.	Light spongy.	Dense spongy.	Friable.	Light spongy.	Spongy.
Color of the ash	Light lilac-grey	Light grey-buft.	Dark lilac-grey	Yellow- ish-white		Brownish grey.
Per centage of sulphur	1.080	0.736	2.109	0.736	3.785	1.066

With one or two exceptions, as is readily to be seen, these are remarkably good and pure coals, which will compare favorably with the best Ohio and Indiana coals.

It is interesting to notice in the above table the nearly constant relation of the specific gravity to the relative proportion of ash, to-wit:

```
In No. 1589 the specific gravity is 1.281; per centage of ash = 1.80.
     1593 " "
                      1.284; "
                         1.316;
     1592 " "
                                          ..
 ..
                        1.350;
                                                7.50.
           **
                 46
                                          **
     1591
                         1.349;
                                                8.00.
                         1.376;
```

This relation of the specific gravity to the proportion of the ash is not constant in coals generally.

No. 1594—Red Hematite "Found on top of hill near Louisa, Lawrence county. By A. R. Crandall."

Nodular lumps, of various sizes, of very hard, dense, dark colored ore, with hardly any soft ochreous material. Powder of a brownish-red or maroon color.

```
| Some converse conve
```

The red hematite is an exceptional ore in the coal measures, but is found in abundance in the Clinton Group.

# LIVINGSTON COUNTY.

No. 1595—Galena. "From Royall Mines, Mineral Point, Cumberland river. Taken one hundred and twenty-five fect from the surface; sloping away from the river. Collected by Prof. N. S. Shaler."

The galena is mingled with colorless and violet-colored fluor-spar.

No. 1596—GALENA. "From same mines, taken forty-five feet from the surface, &c., &c."

The galena, separated from the gangue, of both these samples, was reduced by the usual flux and tested for silver. No. 1595 gave a button of lead weighing 79.34 per cent. of the weight of the galena, and No. 1596 one which weighed 79.052 per cent.

These were severally dissolved in diluted nitric acid and tested for silver by the addition of the watery solution of lead chloride to the diluted nitrate of lead solution; and in neither case was more than a minute trace of silver chloride obtained. So that these galenas cannot be profitably worked for the extraction of silver.

### LYON COUNTY.

No. 1597—"LIMONITE iron ore from old Suwannee Furnace, Big Showing. Sub-carboniferous. Collected by P. N. Moore."

A dense, dark-brown limonite, in irregular laminæ, with a small amount of investing soft ochreous ore.

No. 1598—LIMONITE. "Old Suwannee Furnace. Bank close to the furnace. Sub-carboniferous. Collected by P. N. Moore."

A dense, dark-brown ore, in irregular laminæ, with some brown hematite and soft ochreous ore. Some cherty nodules.

No. 1599—"LIMONITE, with occasional thin layers of brown hematite. Old Suwannee Furnace property. Railroad cut. Sub-carboniferous formation. Average sample of the ore in the railroad cut. Collected by P. N. Moore."

A dense, dark-brown limonite, with thin incrustations of brown hematite and some soft ochreous ore.

No. 1600—Limonite. "Old Suwannee Furnace property. Iron Mountain bank. Sub-carboniferous. Average sample, by P. N. Moore."

Generally in dark-brown irregular laminæ, with some yellowish and brownish ochreous ore, and occasional small nodules of chert.

COMPOSITION OF THESE LYON COUNTY LIMONITES, DRIED AT 212° F.

	No. 1597.	No. 1598.	No. 1599.	No. 1600.
Iron peroxide	59.370	70.518	66.117	69.392
Manganese, brown oxide	.000	.045	.170	a trace.
Lime carbonate	.170	.090	.090	.140
Magnesia	.100	a trace.	a trace.	a trace.
Phosphoric acid	. 179	.275	.434	. 303
Sulphuric acid	.508	.113	.213	a trace.
Water expelled at red heat	8.400	9.850	9.800	9.550
Silica and insoluble silicates	30.000	18.910	22.330	20.500
Moisture and loss		.009		
Total	100.439	100,000	100.218	100.055
Per centage of iron	41.559	49.363	46.819	48.574
Per centage of phosphorus	.077	.120	.189	. 144
Per centage of sulphur	.212	.045	.083	
Per centage of silica	26.800	18.160	21.160	19.660

In volume 4 of Reports of Kentucky Geological Survey, old series, may be found the amount of the analyses of other materials from this old furnace, beginning at page 209.

Quite rich ores, and very good, except those which show a large proportion of sulphur or phosphorus.

For an account of the analysis of the water contained in the interior of a geode of "pot ore," see the Appendix.

### MENIFEE COUNTY.

- No. 1601—Coal. "Sub-conglomerate, forty feet above the subcarboniferous limestone. Hawkins' Creek, near the line of Powell county. Menifee county. Average sample, collected by A. R. Crandall."
- No. 1602 Coal. "Sub-conglomerate, forty to forty-five feet above the sub-carboniferous limestone, near the mouth of Glady Creek, on Ledford's land. A thin bed. Collected by A. R. Crandall."

No. 1603—BITUMINOUS SHALE. "Sub-conglomerate (mistaken for coal). Twenty to twenty-two feet thick; immediately above the sub-carboniferous limestone. Average sample, by A. R. Crandall."

A friable shale, resembling some kinds of cannel coal, of a dull brownish-black, with some thin ferruginous incrustation. Fracture irregular; sub-conchoidal.

COMPOSITION OF THESE COALS AND THE SHALE, AIR-DRIED.

	No. 1601.	No. 1602.	No. 1603.
Specific gravity	1.319	not est.	not est.
Hygroscopic moisture	33.06	2.66 34.04 63.30	2.80 15.20 82.00
Total		100.00	100.00
Total volatile matters	36.00 56.60 7.40	36.70 50.24 13.06	18.00 24.30 57.70
Total	100.00	100.00	100.00
Character of the coke, &c	Dense.	Dense.	Pulverulent
Color of the ash	Light brownish- grey.	Dark lilac-grey.	White.
Per centage of sulphur	0.997	4.092	not est.

Some of the sub-conglomerate coals are found to be quite good. The bituminous shale described above, however, hardly contains enough combustible matters (having only eighteen per cent.) to make it available for fuel.

Samples of various rocks and minerals were brought to the laboratory by Mr. J. M. Vanarsdall, from this county, from the vicinity of Glady Creek; consisting of iron ores, pyrites, marly clay, zinc sulphide, &c., with some small globules of a white metal which he obtained from the ashes of the furnace of the

so-called "James Kirk's silver mine." The metal contained tin and copper, and the furnace was probably used by counterfeiters, who, selecting out-of-the-way regions for their operations, seem frequently to conceal the character of them by the pretense of working a silver mine.

This county has not as yet been thoroughly examined by the Geological corps; and doubtless contains much more mineral wealth than is indicated by these few analyses here reported.

### MONTGOMERY COUNTY.

No. 1604—"QUICKLIME. Star Lime Company's lime. Burnt at (or near) Mt. Sterling. Obtained from Williamson & Bro., Lexington."

Not remarkably white, presenting an oölitic structure in some of the pieces.

### COMPOSITION.

Lime																								•			.	98.301
Magnesia .																			•	•							.	.092
Magnesia . Alumina, an	d i	ro	n a	and	d ı	na	ng	an	es	e d	xi	de	s .														.	-747
Phosphoric a	CIC	ı.																						•				.023
Sulphuric ac	id																									×	. ]	not est.
Potash			×																					•			. [	.012
Soda																												110.
Silica and in	sol	uł	ole	si	lic	ate	25				•			•	•	٠	•				•	•			•	•		.814
Total						٠																					. [	100.000

This analysis, made by the youngest son of the writer (Alfred M. Peter) under his inspection, indicates a degree of purity which fits this lime for all purposes of construction, except, perhaps, for the whitest finishing coats in plastering.

## MUHLENBURG COUNTY.

No. 1605—LIMONITE Labeled "Iron ore from near No. 4 entry. Airdrie Furnace. Averaged by P. N. Moore."

A porous, yellowish, and deep brown ore.

No. 1606—LIMONITE. "Iron ore from Jerry M. Hope's land, near Muddy river. Average sample, by P. N. Moore, of the surface limonite from the upper part of the bed."

A cellular limonite (fossiliferous), of a bright yellowish-brown color externally, with darker, hard, curved laminæ included.

No. 1607—LIMONITE. "Ore from the lower and middle parts of the bed. Jerry Hope's land, &c., &c. Average sample, by P. N. Moore."

A porous, brownish-yellow, fossiliferous ore.

No. 1608 — LIMONITE. "Martin ore from near Greenville. Average sample, by P. N. Moore."

A cellular limonite, with ochreous incrustation, &c.

No. 1609—"ROASTED ORE from the Airdrie Furnace stock pile. Has been weathered seventeen years since roasting. Collected by P. N. Moore."

Apparently a "Black-band ore," so-called, originally. The roasted ore is of a dark, reddish-brown color, varying to lighter tints. Some portions are cellular, as though they had been fused.

COMPOSITION OF THESE MUHLENBURG COUNTY LIMONITE IRON ORES,. &c., DRIED AT 212° F.

	No. 1605.	No. 1606.	No. 1607.	No. 1608.	No. 1609.
Specific gravity	3.246				3.652
Iron peroxide	63.048	60.492	46.865	69.546	59.810
Alumina	5.290	7.075	5.930	3.914	2.972
Brown oxide of manganese	.090	.360	.103	.230	.720
Lime carbonate	.680	1.980	2.535	.480	*2.263
Magnesia	.930	1.550	1.073	.921	4.270
Phosphoric acid	.147	.083	.179	.115	.223
Sulphuric acid	.112	.185	.059	.216	.065
Water expelled at red heat	12.430	12.530	9.550	11.250	. 200
Silex and insoluble silicates	17.250	15.560	33.530	12.730	29.880
Moisture and loss		.185	.175	. 598	
Total	100.077	100.000	100.000	100.000	100.403
Per centage of iron	44.133	42.344	32.806	48.822	41.867
Per centage of phosphorus	.064	.035	.078	.050	.097
Per centage of sulphur	.044	.074	.024	.086	.026
Per centage of silica	16.500	13.660	32.860	11.300	25.260

<sup>·</sup> Lime.

These Airdrie Furnace limonites are all good and profitable ores, which would yield a good quality of iron if properly smelted, as they contain but a moderate proportion of the injurious ingredients, phosphorus and sulphur. Although it is probable that the "roasted ore" was from the so-called "Black-band ore" (bituminous clay iron-stone), it is properly tabulated with these limonites. The analyses of other similar iron ores from this region are detailed in the previous volumes of Kentucky Geological Reports. (See volume 1, pages 345 and 346, and volume 4, page 229.)

No. 1610—Clay Iron-stone. Bituminous. So-called "Black-band" ore. From the Airdrie Furnace stock pile; weathered seventeen years. Not roasted. Collected by P. N. Moore."

A shaly ore, varying in color, in layers, from nearly black to dark grey-brown.

No. 1611 — CLAY IRON-STONE. Bituminous. Labeled "Slate iron ore, from Buckner Furnace. Weathered thirty years. Average sample, by P. N. Moore."

A Black-band ore, of a dark umber-brown color, varying in tint. Shaly, and containing carbonaceous matter.

No. 1612—CLAY IRON-STONE "From the lower part of the bed at Jerry Hope's bank, near Muddy river. Collected by P. N. Moore."

A rough, greenish and brownish, fossiliferous and silicious carbonate ore.

COMPOSITION OF THESE CLAY IRON-STONES, DRIED AT 212º F.

												No. 1610.	No. 1611.	No. 1612.
Specific gravity											•	3.376	not deter'd.	not deter'd.
Iron carbonate											_	47.810	42.950	26.643
Iron peroxide				 - 12								9.054	29.618	18.374
Alumina												5.205	2.454	6.548
Lime carbonate												3.740	2.490	13.430
Magnesia carbonate												7.180	4.828	5.698
Manganese carbonate												.797	1.083	a trace.
Phosphoric acid												. 179	.083	.211
Sulphuric acid												. 237	1.596	. 185
Silica and insoluble silicates												17.010	9.030	22.230
Water, bituminous matter, as												8.788	5.868	6.681
Total		٠	•		•	•	٠	•	•	•	٠	100.000	100.000	100.000
Per centage of iron		•				•	•		•			29.418	36.916	27.136
Per centage of phosphorus.		•			•		•				•	.078	.035	.092
Per centage of sulphur	•	•1			•				•	•	•	.094	.638	.074
Per centage of silica				 -							_	12.900	6.220	20.660

These clay iron-stones are not very rich in iron, except the one (No. 1611) from Buckner Furnace, and this has a large proportion of sulphur. The others are probably too poor in iron to be separately smelted with profit; but they might be mixed with richer ores with advantage. Other analyses of the so-called Black-band ores of this region are to be found in volume 1, Kentucky Geological Reports, pages 346 to 350. It will be seen, by reference, that these vary in their proportion of iron from 31.17 to 36.80 per cent. of the ore.

[No. 1314—"LIMESTONE from Barren river, near the mouth of Jasper Creek. Used formerly as a flux at Airdrie Furnace." (See Butler county.)]

No. 1613—Clay "From Ross coal mines, Owensboro Junction. (Fire-clay below the coal in the lower drift.) Collected by C. J. Norwood."

A dark-grey, soft, shaly clay.

#### COMPOSITION, DRIED AT 212° F. Alumina, and iron and manganese oxides . . . . . . . 203 .255 .179 Sulphuric acid . . . . . . . . 3.282 == 1.312 per cent. of sulphur. 2.000 Soda . . .425 4.195

100.000

Much of the sulphur and iron doubtless exist in the clay, not as sulphuric acid and iron oxide, but in combination, as iron sulphide. The considerable proportions of potash, lime, magnesia, and iron oxide may prevent this from being a very refractory clay; although it may very well answer for the manufacture of stone-ware and ordinary fire-bricks.

No. 1614—Pig Iron. (Silver-grey.) "An old sample, from a former smelting at Airdrie Furnace. Collected by P. N. Moore."

No. 1615—Pig Iron. (Silver-grey.) "From a former smelting, Airdrie Furnace, &c."

No. 1616—"Pig Iron (silver-grey,) &c., &c., as above.

No. 707—(See volume 3 Kentucky Geological Reports (old series), page 340, for an analysis of a somewhat similar pig iron from this furnace, made when the furnace was in blast.)

COMPOSITION	OF T	THESE	AIRDRIE	FURNACE	PIG IRONS
COMITONIA	<b>U</b> .			I CILLIANCE	TIO THOUSE

												No. 1614.	No. 1615.	No. 1616.	* No. 707.
Specific gravity	•	•				•	•		•			6.826	6.826	7.782	7.007
Iron								•				86.636	85.455	86.842	88.426
Graphite	•		*	•	٠	٠	٠	٠	٠	٠	•	.900	.480	.740	1.360
Combined carbon .					•	•	٠	•	•	٠	٠	2.080	1.560	1.460	.190
Manganese			•	٠	•	•	•		٠	٠	•	. 202	.696	.355	.980
Silicon				•		•	•		•	•	•	7.704	7 - 747	8.614	6.216
Slag	•		•	•	•	•	•	•	•	•	•	2.260	3.460	2.360	3.090
Aluminum			٠	•	•	•		•	•		•	.123	.098	.054	.099
Calcium					•		•			•		.045	.089	.112	not est.
Magnesium												.035	.017	.056	. 309
Potassium						•					•	not est.	not est.	not est.	.059
Sodium				•								not est.	not est.	not est.	.091
Phosphorus												.235	.443	.123	. 209
Sulphur	•	•	٠	•	•	•	•	•	•	٠	•	. 104	.122	.122	219
Total			٠	•	•	•		•	•	•	•	100.334	100.167	100.836	101.250
Total carbon									_		_	2.980	2.040	2.200	1.550

<sup>\*</sup> Of old series of Reports.

The analyses of these samples of the pig iron of old Airdrie Furnace show inordinate proportions, in all of them, of silicon, slag, phosphorus, and sulphur; which caused the very bad quality of the iron, as they all tend to make it brittle, whether hot or cold. But the examination of the ores, limestone, and coals of the neighborhood of this furnace, shows that, with due care in the selection of these materials, and a proper management of the furnace, as good iron could be produced by it as by any using pit coal or coke for fuel.

It appears that, in its early working, the limestone used for flux was very sulphurous, containing much pyrites; that the manager had too strong a preference for the so-called "Blackband" over the limonite ores, which former frequently contain much sulphur and phosphorus; and that, moreover, the blast was too slow and too hot—conditions which all tended to the production of impure iron.

An account of the examination of some of the coke used formerly in this furnace is appended, as follows:

No. 1617 — Coke. "Airdrie Furnace coke, weathered sixteen years; made from the No. 12 coal. Collected by P. N. Moore."

## COMPOSITION, AIR-DRIED.

Hygroscopic moisture (expelled a	t 21	120	F.	) .																7.50
Moisture, &c., expelled at red hea	ıt .			<i>'</i> .															. [	4.2
Dry coke					•			•				è	•	•	•					88.30
Total	•					•	•	٠	•		•	÷	•	•				٠		100.00
Total moisture and volatile matte	r .							٠												11.7
Fixed carbon																			.	82.9
Ashes, of a light yellowish-grey of	olo	r .						•			.3	•		•	•					5 - 4
Total	•			•	•	•	•	•	٠	•	٠	•	•	٠	•	•		٠		100.0
			_	_		_		_			_	_			_	_	_	_		

The ash of this coke was also analyzed.

### COMPOSITION OF THE ASH.

Per cent. o the coke.																									
0.40								_			les	xic	0	ese	ane	nga	nar	d n	ın	n a	OI	l ii	d	an	mina,
.3.																									ie .
. 13		•				•																		٠.	gnesia
.0																					١.	cic	a	ic	gnesia sphor
4.3	•					•						•	•			s .	tes	ica	si	le	ub	ol	150	in	d and
.00			٠	•	٠			•	•	٠		•	•		•	•	•			•		•			d and
5.40																									otal

The analysis of the coal of which this coke was made is given in the following (Nos. 1618 and 1619):

- No. 1618—Coal. "No. 12 of Owen. Airdrie Furnace, near No. 4 entry. Average sample, by P. N. Moore."

  A deep-black coal, with some thin shaly laminæ.
- No. 1619—COAL. "No. 12 of Owen. From the old stock pile, at the entrance of the drift; where it has been weathered for sixteen years. Average sample, by P. N. Moore."

  Like the preceding, but altered somewhat by weathering.

No. 1620—Coal. "Average sample of the lowest division of the bed at Paradise mines. Airdrie Furnace. (No. 11 of Owen.) By P. N. Moore."

A bright, deep-black coal; with but little fibrous coal between the layers, but containing small bright crystals and incrusting scales of iron pyrites.

No. 1621—COAL. "Average sample of the middle stratum of same beds of Paradise mine. By P. N. Moore."

A pure looking, deep-black coal, with shining fracture; showing less fibrous coal and iron bi-sulphide than the preceding.

No. 1622—COAL. "Average sample of the upper stratum of Paradise mine, &c. By P. N. Moore."

Like the two preceding; having a shining fracture, like that of asphaltum. Very little fibrous coal or pyrites to be seen in it.

No. 1623—COAL. "From Muddy river coal mine. Averaged by P. N. Moore."

A deep-black, glossy coal, with but little fibrous coal or pyrites apparent in it. Like the Paradise mine coal.

COMPOSITION OF THESE AIRDRIE FURNACE COALS, AIR-DRIED.

	No. 1618.	No. 1619.	No. 1620.	No. 1621.	No. 1622.	No. 1623.
Specific gravity	1.278	1.332	1.331	1.326	1.274	1.221
Hygroscopic moisture	3.60 31.40 65.00	4.70 30.60 64.70	4.20 36.10 59.70	4.10 35.90 60.00	3.60 38.70 57.70	3.80 32.70 63.50
Total volatile matters	35.00 58.50 6.50	35.30 58.80 5.90	40.30 50.50 9.20	40.00 53.60 6.40	42.30 53.70 4.00	36.50 58.60 4.90
Character of coke	Dense spongy.	Dense spongy.	Spongy.	Spongy.	Spongy.	Dense spongy.
Color of ash	Lilac- grey.	Light lilac-grey	Dark lilac-grey	Dark lilac-grey	Light lilac-grey	Brownish salmon- grey.
Per centage of sulphur	1.438	1.455	4 · 573	4 · 394	3.158	1.923

It appears that the No. 12 coal contains the least sulphur, while the No. 11 coal of the Paradise mine is quite sulphurous, the upper stratum being the least objectionable in this respect. They are all very good coals for ordinary uses, and might be measurably purified from sulphur by careful coking, and thus probably made available in the iron manufacture. The coal of the No. 12 bed of Owen is, however, preferable for this purpose.

No. 1624—Coal. "Ross coal mine. Owensboro Junction. Top bench; above the clay parting. From the upper drift. Average sample, by C. J. Norwood." (Coal A.)

A jet-black coal, with fibrous coal between its thin laminæ, and but little apparent pyrites.

No. 1625—Coal.. "Mercer coal mines. Louisville and Paducah and Southwestern Railroad. Collected by C. J. Norwood." (Coal D.)

A jet-black coal, with shining pyrites, and some fibrous coal between the laminæ.

No. 1626—Coal. "Upper seam of the old drift. Muhlenburg coal mines. Collected by C. J. Norwood." (Coal A.)

A glossy, pure-looking, pitch-black coal; with very little fibrous coal or pyrites apparent. Some little incrustation of lime sulphate in the seams.

No. 1627—Coal. "Muhlenburg mines. Main working bed, near Mercer Station, Louisville and Paducah and Southwestern Railroad. Collected by C. J. Norwood." (Coal B.)

Like the next preceding, but has a little more fibrous coal than that, and some thin pyritous and lime sulphate incrustations.

No. 1628—Coal. "Muhlenburg mines (John Pollock, Superintendent), near Mercer Station, &c., &c. Taken from head of main entry. Average sample, by C. J. Norwood."

A pure pitch-black looking coal; beautifully iridescent on some of the seam faces. But little fibrous coal or pyrites apparent, but some slight lime sulphate incrustation.

No. 1629—"FIBROUS COAL OR MINERAL CHARCOAL. "From above the main working. Thickness from one half to one inch. Muhlenburg mines, &c. Collected by C. J. Norwood."

A very soft, friable mass of carbonaceous matter. Some in light powder, but much in the form of charred, fibrous, reedy stems, &c.

No. 1630 — Carbonaceous Mud or Clay. "Filling cavities occurring in the bituminous shale overlying the coal. Muhlenburg mines. Collected by C. J. Norwood."

A brownish greyish-black indurated mud, or carbonaceous clay.

COMPOSITION OF THESE MUHLENBURG COUNTY COALS, &c., AIR-DRIED.

	No. 1624	No. 1625	No. 1626	No. 1627	No. 1628	No. 1629	No. 1630
Specific gravity	1.407	1.358	1.297	1.332	1.280	1.503	
Hygroscopic moisture Vol'ile combustible matters	4.16 37.44 58.40	3.60 34.00 62.40	3.10 40.68 56.22	1.52 40.00 58.48	2.98 43.08 53.94	1.20 7.50 91.30	3.56 13.68 82.76
Total	100.00	100.00	100.000	100.00	100.00	100.00	100,001
Total volatile matters Carbon in the coke	41.60 49.80 8.60	37.60 50.60 11.80	43.78 50.66 5.56	41.52 50.92 7.56	46.06 50.22 3.72	8.70 86.48 4.82	17.24 6.82 75.94
Total	100.00	100.00	100.000	100.00	100.00	100.00	100.00
Character of the coke	Light spongy.	Light spongy.	Spongy.	Spongy.	Spongy.	Powdery.	Powdery.
Color of the ash	Light lilac-grey	Lilac- grey.	Lilac- grey.	Lilac- grey.	Lavendar grey.	Dark- brown.	Brownish grey.
Per cent, of sulphur	2.727	4.032	2.779	2.840	3.125	3.431	1.983

These coals are generally of very good quality, although some of them contain a little more than the usual proportion of sulphur. Some of this, however, is in combination, in the form of lime sulphate. To ascertain how much was in this state, coals Nos. 1626 and 1629 were boiled in solution of soda carbonate, &c., &c., and the proportions of lime sulphate ascertained. The quantity in No. 1626 was only 0.168 per cent., while No. 1629 was found to contain 3.632 per cent. of this substance. In addition, No. 1629 was treated with bisulphide of carbon, by the method of displacement, and was thus found to contain a certain amount of uncombined sulphur. It is probable that in other coals free sulphur may be found, especially in those which have much fibrous coal between their laminæ.

The fibrous coal above described is remarkable for the large proportion of carbon it contains. The carbonaceous mud, on the contrary, contains but little combustible matter. It would be a bituminous shale if indurated.

### OHIO COUNTY.

No. 1631—Coal. "Rockport mines, one and three quarter miles east of Rockport. Average sample, from along the entry. Collected by C. J. Norwood." (Coal D.)

Rather friable. Pitch-black, with some incrustations of shining pyrites in the seams, and some fibrous coal between the laminæ.

No. 1632—Coal. "Same locality, &c. Average sample, by C. J. Norwood." General average of the mine. (Coal D.)

A pitch-black coal, with fibrous coal between the layers; some infiltration of lime sulphate in the seams, and but little pyrites.

No. 1633—COAL. "Same locality, &c. Averaged by C. J. Norwood." (Coal D.)

Much like the preceding.

## COMPOSITION OF THESE OHIO COUNTY COALS, AIR-DRIED.

	No. 1631.	No. 1632.	No. 1633.
Specific gravity	1.421	1.332	1 . 334
Hygroscopic moisture	3.50 35.00 61.50	3.00 36.20 60.80	3.00 33.50 63.50
Total	100.00	100.00	100.00
Total volatile matters	52.50 9.00	39.20 53.70 7.10	36.50 55.10 8.40
Character of the coke	Light spongy.	Light spongy.	Light spongy.
Color of the ash	Light brownish- grey.	Light lilac-grey.	Lilac-grey.
Per centage of sulphur	3.139	2.837	3.332

These coals are all of very good quality.

[See Appendix for other Ohio county coals.]

No. 1634—"VIRGIN SOIL from woodland, on Mr. Miller's land, fifteen hundred and twenty feet north to east from Horse Branch Station (Louisville and Paducah Railroad). Collected by C. S. Schenk."

Slope 1:16. Depth of sample six inches. Substratum sandstone. Timber: white and black oak, some chestnut, hickory, and poplar. Undergrowth: sassafras, dogwood, and small trees of above named kinds. The new land is said to produce of corn, forty to fifty bushels; wheat, twenty to thirty; oats, forty to fifty; and of tobacco, one thousand pounds to the acre.

Dried soil of a dark brownish-grey color. No gravel.

No. 1635—"Sub-soil of the preceding, taken at depth of from six to thirty-six inches. By C. S. Schenk."

Sub-soil of a light grey-buff color. No gravel.

No. 1636—"Soil of an old field, forty years in cultivation. Level table land, owned by Mr. Miller, sixteen hundred feet north 20° east, from Horse Branch Station, &c. Collected by C. S. Schenk."

Sample taken to the depth of seven and a half inches. Substratum sandstone. Rotation of crops: tobacco two years, corn three years (in some cases corn until it fails to produce it), then wheat and clover, or oats and clover or grass. Yield of corn. twenty to thirty bushels; oats, twenty to thirty-five bushels; tobacco, six hundred pounds per acre. Never plowed over six or seven inches deep. Good quality of table-land; nearly as good as the valley land.

Dried soil of a greyish light-brown color. Contains a few small fragments of ferruginous sandstone.

No. 1637—"Sub-soil of the next preceding, taken to the depthof from seven and a half to thirty-six inches. Collected by C. S. Schenk."

Dried sub-soil of a yellowish-grey color. Contains nogravel.

VOL. I.-CHEM. II.

COMPOSITION OF THESE OHIO COUNTY SOILS, DRIED AT 212° F.

	No. 1634.	No. 1635.	No. 1636.	No. 1637.
Organic and volatile matters	4.100	3.500	3.550	3.350
Alumina, and iron and manganese oxides	3.032	7.047	4.066	6.475
Lime carbonate	. 170	.095	.095	.095
Magnesia	. 131	.258	. 104	. 171
Phosphoric acid	.093	.093	.124	. 140
Sulphuric acid	Not estima			
Potash	.125	.273	.333	.269
Soda	a trace.	.144	.012	.230
Sand and insoluble silicates	92.455	88.841	91.990	89.515
Water expelled at 380° F	.900	.915	.775	-775
Total	101.066	101.165	101.049	101.020
Hygroscopic moisture	1.175	2.400	1.450	2.575
Potash in the insoluble silicates	1.273	1.470	.939	1, 107
Soda in the insoluble silicates	.814	.617	.511	. 290
Character of the soil	Virgin soil.	Sub-soil.	Old field soil.	Sub-soil.

The old field soil seems to have been naturally richer than the woodland soil, if no mistake has been made in the labels. The considerable proportions of potash and soda in the sandy portion (insoluble silicates) tend to give durability to the soils. With proper culture and the due application of fertilizers, this land may be made quite productive, if well drained

For the analyses of other soils of this serial collection, made by Mr. C. S. Schenk along the line of the Elizabethtown and Paducah Railroad, see Grayson and Hardin counties.

## APPENDIX.

#### BOURBON COUNTY.

No. 1638—"LIMESTONE (magnesian). From Cane Ridge; five miles east of Paris. Used for the foundation of the Bourbon county Court-house at Paris. Sent by Mr. James Stevenson."

A somewhat porous, fossiliferous, ferruginous, magnesian limestone, of a light grey-buff color, containing small specks of hydrated oxide of iron. Specific gravity = 2.58 to 2.60 (in the lump).

				α	M	PO	SIT	ric	N,	, I	RI	ED	AT 212° F.
Lime carbonate													79.140 = 44.318 per cent. of lime.
Magnesia carbon													
Alumina													
Iron peroxide .													
Phosphoric acid													.511
Sulphuric acid .													
Potash													
Soda													.252
Soluble silica													.110
Insoluble silica .													
Loss													.640
													100,000

The magnesian limestones are believed to withstand the atmospheric agencies generally better than the pure limestones. The iron in this rock is all in the state of peroxide, which is also favorable to its durability.

Whether its small cavities or pores may retain enough water to cause disintegration by freezing was not ascertained. It would calcine into lime good for ordinary building purposes or for use on the soil as a fertilizer.

## COALS FROM THE STATE OF OHIO.

For the purpose of comparing our Kentucky coals with some of the best of those of our neighboring States, some of these, collected by Messrs. P. N. Moore and A. R. Crandall, were submitted to analysis, as follow:

No. A. 1—"COAL from Jackson county, Ohio. Star Furnace coal. Averaged by A. R. Crandall."

A glossy, jet-black splint coal; breaking into thin laminæ, with fibrous coal between.

No. A. 2—" COAL. Hocking valley, Athens county, Ohio. Average sample from the whole thickness of the bed. Taken from the pillar, three hundred yards. By A. R. Crandall."

A pitch-black, glossy coal, iridescent on some of the faces; having very little fibrous coal, and no pyrites apparent.

No. A. 3—"COAL. Hocking valley, &c., &c. Average sample from the stock pile, from the whole thickness of the bed. By A. R. Crandall."

Like the preceding, but brighter, and showing less fibrous coal.

No. A. 4—Coal. Hocking valley, &c., &c. Average sample from the upper twenty-eight inches. Taken from two rooms. By A. R. Crandall."

Breaks into thinner laminæ than the two preceding, with more fibrous coal between. Some little shining pyrites in thin crusts.

No. A. 5—"COAL. Hocking valley, &c., &c. Average sample from the middle part (twenty-six inches), taken from two rooms. By A. R. Crandall."

In thicker laminæ than preceding, with much less fibrous coal, and no appearance of pyrites between them. Handsomely iridescent on many of the seam faces.

No. A. 6—"COAL. Hocking valley, &c., &c. Average sample, from the lower part (eighteen inches) of the bed. Taken from two rooms. By A. R. Crandall."

Resembles the preceding, but shows some bright pyrites in places.

No. A. 12 — "COAL. Sheridan coal mines, Lawrence county, Ohio. Collected by P. N. Moore."

A pure, pitch-black coal; with very little fibrous coal and some fine-granular pyrites, between the laminæ.

COMPOSITION OF THESE SELECTED OHIO COALS, AIR-DRIED.

	А. 1.	A. 2.	А. 3.	A. 4.	A. 5.	A. 6.	A, 12.
Specific gravity	1.361	1.322	not det'd.	1.346	1.303	1.312	1.322
Hygroscopic moisture Vol'ile combustible matters Coke	4.54 29.68 65.78	3.60 33.42 62.98	4.20 36.68 59.12	3.26 33.76 62.98	3·74 36.32 59·94	4.40 35.08 60.52	3.46 36.64 59.90
Total	100.00	100.00	100.00	100.00	100.00	100.00	100.00
Total volatile matters Carbon in the coke	34.22 57.06 8.72	37.02 55.82 7.16	40.88 54.16 4.96	37.02 54.42 8.56	40.06 55.74 4.20	39.48 55.20 5.32	40.10 53.80 6.10
Character of the coke	Pulveru-		Spongy.	Dense,	Dense spongy.	Dense spongy.	Light spongy.
Color of the ash	Nearly white.	Brownish grey.		Light lilac-grey	Light lilac-grey	Light lilac-grey	Light lilac-grey
Per centage of sulphur	0.756	0.862	1.692	2.247	1.299	1.659	1.947

These are remarkably good coals, and are acknowledged to be amongst the best of the country.

The sample A. 2, taken from the pillar, seems to show the effect of exposure to the atmosphere, which is generally believed to cause a diminution of the proportion of sulphur.

A correspondence may be observed between the proportion of ash and the specific gravity, as follows:

```
has specific gravity = 1.303, and ash per cent. =
A. 5
                            1.312, "
            has
                                                           5.32
                                      ..
                                           ..
                       ..
A. 2 and A. 13 have "
                                                    6.10 and 7.16
                             1.322,
                             1.346, "
           has "
                       ..
                                            ..
            has ''
                      . .
                              1.361,
A. I
```

### COALS FROM THE STATE OF ILLINOIS.

No. A. 7—Coal. "Mine near Murphrysboro, Jackson county, Illinois. Block coal. Big Muddy coal. Average sample, by P. N. Moore."

A glossy, jet-black splint coal. It has some fibrous coal between the laminæ; with occasional scales of bright pyrites, and some slight lime sulphate incrustation in the seams.

No. A. 8—"COAL. Big Muddy coal. Mine near Murphrysboro, Illinois. Average sample, by P. N. Moore."

Like the preceding. Some fine-granular pyrites with the fibrous coal between the laminæ, and occasional lime sulphate incrustation in the seams.

COMPOSITION OF THESE ILLINOIS COALS, AIR-DRIED.

	No. A. 7.	No. A. 8.
Specific gravity	1.310	1.310
Hygroscopic moisture	32.04	3.44 31.86 64.70
Total	100.00	100.00
Total volatile matters	58.58	35·30 59·54 5·16
Total	100.00	100.00
Character of the coke	Light spongy.	Spongy.
Color of the ash	Lilac-grey.	Lilac-grey.
Per centage of sulphur	2.472	1.376

These are also remarkably good coals, containing only a moderate proportion of sulphur, which is partly in the form of iron sulphide and partly in that of lime sulphate.

## COALS FROM THE STATE OF INDIANA.

No. A. 9—"Indiana Block Coal. From near Brazil, Clay county. Upper seam. Average sample, by P. N. Moore."

A pitch-black splint coal, breaking easily into thin laminæ, with fibrous coal (mineral charcoal) and some fine granular 158

pyrites between them. A few bright scales of iron pyrites and some slight lime sulphate incrustation in the seams.

No. A. 10—"Indiana Block Coal. Mine near Brazil, Clay county. Lower seam. Average sample, by P. N. Moore."

Like preceding, but little appearance of pyrites or lime sulphate.

No. A. 11—"Indiana Block Coal. From mine near Brazil, &c. Lower seam. Average sample, by P. N. Moore."

Resembles the others. Shows occasional bright scales of pyrites and lime sulphate incrustation.

COMPOSITION OF THESE INDIANA COALS, AIR-DRIED.

	No. A. c.	No. A. 10.	No. A. 11.	No. A. 11 (repeated).
Specific gravity	1.313	not est.	not est.	
Hygroscopic moisture	2.70 36.38 60.92	2.68 36.32 61.00	2.40 35.10 62.50	2.52 35.48 62.00
Total	100.00	100.00	100.00	100.00
Total volatile matters	39.08 55.64 5.28	29.00 53.58 7.42	37.50 53.50 9.00	38.00 53.06 8.94
Total	100.00	100.00	100.00	100.00
Character of the coke	Spongy.	Dense spongy.	Dense.	
Color of the ash	Lilac-grey.	Light lilac-grey.	Lilac-grey.	
Per centage of sulphur	1.664	1.802	2.373	

These are remarkably good coals, as is well known by experience, especially in their use in the smelting of iron. Their high reputation and successful application to this industry make the comparison of their composition, with that of our Kentucky coal, an object of interest; and as we could find in

the excellent reports of the Chief Geologist of Indiana, Prof. E. T. Cox, no statement as to the amount of sulphur which they contain, an ingredient of great and evil influence in iron smelting, these block coals were examined especially for this determination.

It will be seen on reference to the preceding table that this ingredient exists in them in average proportion. Doubtless to the existence of the sulphur in this fuel may we attribute the fact, given by Prof. Cox, on page 70 of his First Annual Report, 1869, that "the general character of the iron made in Clay county is red-short, &c." This, however, may be measurably corrected, and indeed does not prevent the iron from being very good and profitable for many industrial purposes.

It is very probable that all the sulphur which exists in these coals in the free, or uncombined, condition, will be volatilized and burnt out at the upper part of the furnace, long before it encounters the heat necessary to cause its combination with the iron of the ore with which it is mixed. This would be the case also with the second atom of sulphur of the bright pyrites of the coal, the bi-sulphide of iron; so that only that portion of the sulphur which would remain in the resulting iron protosulphide could vitiate the cast iron product. Hence we can understand, how a coal which gives a considerable per centage of sulphur in its ultimate analysis, may yet be quite available for the smelting of tough iron.

## CALIFORNIA ADOBÉ SOIL.

An opportunity having occurred for procuring a specimen of this remarkably fertile soil, it was analyzed for comparison with our Kentucky soils, with the following results.

No. A. 12—" Address Soil taken at three inches below the surface. Valley of the Sacramento river. Solano county, California." Collected by Robert Peter, jr.

Dried soil of a light-umber color; adhering in clods, which are easily crushed in the mortar. The powder (unground) passed wholly through fine bolting-cloth, leaving only a few vegetable fragments.

#### COMPOSITION OF THE AIR-DRIED SOIL.

													No. A. 12.	No. 1329.
Organic and volatile matters													7.740	7.615
Alumina, and iron and manganese oxides												. 1	11.117	12.085
Lime carbonate												. !	.790	.990
Magnesia		٠		٠		•					•	. ]	1.596	.520
Phosphoric acid				•				○				.	.093	.483
Sulphuric acid							•					.	.082	a trace.
Potash				٠								.	.727	.726
Soda			60									.	.983	a trace.
Sand and insoluble silicates												. 1	74.070	75.590
Water and loss		•	•	•	•	•	•	•	•	•	•		2.802	1.891
Total		•		•	•	•	٠	•	•		•		100.00	100.000
Potash in the insoluble silicates					•		•		•	•		•	0.814	2.731
Soda in the insoluble silicates	<del>-</del> -						•					-	0.903	.929

It will be seen above that this adobé soil resembles in composition the peculiar rich soil found locally in Campbell county, Kentucky, No. 1329, which is also like the adobé in being a sticky clay when wet, and hard and cloddy when dry. The California soil exceeds our Kentucky soils in soda, the latter has more phosphoric acid.

## LYON COUNTY.—(Continued.)

No. 1639—"Water taken from the interior of a geode of iron ore—pot iron ore. Suwannee, Lyon county. Summit Cut ore bank. Sent by A. L. Anderson, Esq."

The water had a strong astringent taste; and had deposited much ferruginous sediment in the bottle. It was analyzed by my youngest son, Alfred M. Peter, in my laboratory.

## COMPOSITION IN 100 PARTS OF THE WATER, APART FROM THE SEDIMENT.

																								i
									*:		•		•	•				٠			•			0.2435
									•			٠		٠	•		•							.4981
				•3					•													•		.1004
																•						•		. 1209
						•					٠	•												.0609
																•	•		•					.0257
	٠	•																						.0651
												v				23				្ន				.0353
		٠	•			•	•			•	•	•	•				٠		٠			•	٠	.0028
•													•					•		٠		•		1.1227

The analyses of some other samples of water, from the pot ore of Trigg county, are given in volume 4, page 260-1, of Kentucky Geological Reports.

## EDMONSON COUNTY.—(Continued.)

No. 1640—LIMONITE. "Old Nolin Furnace bank, near the furnace ore. Bank about a quarter of a mile north of the furnace. Davis' branch of Nolin river. Average sample, by P. N. Moore."

Generally of a brownish-red color. A porous ore, with some whitish portions.

							CC	MC	PO	SI	LIC	N,	D	R	RIED AT 212° F.
Iron peroxide .						•					•		•		. 27.340= 19.138 per cent. of iron.
Alumina															
Manganese oxide															. not det'd.
Lime carbonate															
Magnesia															
Phosphoric acid															. I.068 = .497 per cent. of phosphorus.
Sulphuric acid .								٠.							. not det'd.
Water expelled at															
Silica and insolub	le	: 5	ilie	cat	es										. 51.230
Manganese oxide,	, :	alk	al	ies	, s	ul	рh	ur	ic	ac	id,	&	c.		
															100,000

This ore is too poor in iron to be valuable. It is probable that its phosphorus is somewhat over-estimated.

No. 1643—Pig Iron. "From old Nolin Furnace. Cold blast." Furnace long since out of blast.

A fine-grained grey iron, which yields easily to the file, and extends considerably under the hammer. Seems to be tougher than usual cast iron.

								C	OM	IPC	SI	TIC	ИC		-SF	EC	:11	FI	С	GF	LA	VITY = 7.113.
Iron Graphite . Combined	ca	rb	on	•	:	:	•	:	:		:	:	•	:	:	:	0 9	•	•	•	:	$\left\{\begin{array}{c} 3.100 \\ .700 \end{array}\right\} = 3.800 \text{ total carbon.}$
Silicon . Phosphorus		•	•	:	:	:	•	:	:	:		:	:	:	:	•			:	•	:	.493 including that in the slag.
Sulphur . Undetermin																						.012
	-		- 6	•									-			-			-	_		100.000

This appears to be a remarkable instance of cast iron remaining tough although it contains a considerable proportion of phosphorus, which is believed to render it "cold-short," or 162

brittle at the ordinary temperature, in quantities even less than one per cent. Possibly the quite small per centage of silicon, which also renders iron brittle, may have something to do with this apparent anomaly.

The phosphorus in the above analysis was first determined as phosphate of bismuth, by the process of Chancel; but not satisfied with this determination, this phosphate, after solution in chlorohydric acid, was decomposed by sulphydric acid, and the separated phosphoric acid re-determined by means of the magnesia mixture, in the usual way; and this without any material alteration in the result obtained.

## GRAYSON COUNTY.—(Continued.)

No. 1641 — "LIMONITE. "Nolin Furnace ore bank, on the Brownsville road. Average sample, by P. N. Moore."

In irregular layers, varying in color and density.

No. 1642—LIMONITE. "From Meredith Ray's farm, Taylor's Fork of Bear Creek, opposite the Chalybeate Spring. Average sample, by P. N. Moore."

A pretty dense ore, generally of a dark-brown color, with some lighter colored portions.

COMPOSITION OF THESE GRAYSON COUNTY LIMONITE ORES, DRIED AT 212° F.

	_		_	_	_	_		_	_	_	_			_	_	_		_		
																			No. 1641.	No. 1642.
Iron peroxide																			57.830	44.528
Alumina		٠											•						6.719	1.36
Manganese oxide		•				•							•				÷		Not determ	ined.
Lime carbonate																			.290	5.59
Magnesia																			.122	.600
Phosphoric acid																			.921	1.074
Sulphuric acid	•	•	•			•	•	•	•	•	•	•	•	•	•		•	•	not deter'd.	
Water expelled at red heat .		•				•	•	•	•	•	•	•	•	•			•		12.180	8.940
Silica and insoluble silicates	•		•		•		•	•			•	•	•	•		•			21.040	37.380
Undetermined and loss	•	•	•	•	٠	•	•	•	•	•	•	•	•	:	•	•	•	٠	.898	. 360
Total	٠	•	٠	٠	٠		٠	٠	٠	•	•			٠	٠	٠	×		100.000	100.000
Iron, per centage	•		•	•					•		•				•	•	•	•	40.481	31.169
Phosphorus, per centage		•		•	•	•		•	٠	•	•					•			.412	.468
Sulphur, per centage					•	٠		•	•			•	•	•	•	•		<del>-</del>	not deter'd.	.060
Silica, per centage		•		•														<del>-</del>	14.360	not deter'd

It is probable the phosphorus is somewhat over-estimated in these ores.

No. 1644 — CLAY IRON-STONE. "The glady ore, on the old Brownsville and Litchfield road, west of Bear Creek, Grayson county."

A dark-grey, fine-granular clay iron-stone, with much investing limonite ore.

					(	co	MP	os	IT	101	v,	DRIED AT	212° F.
Iron carbonate			•									16.598	= 37.945 per cent. of iron.
Iron peroxide						•						42.761	= 37.945 per cent. or from.
Alumina				٠								4.994	
Lime carbonate												2.840	
Magnesia carbonate							٠					not det'd.	
Phosphoric acid			•									1.017	= .444 per cent. of phosphorus.
Sulphuric acid												a trace.	
Silica and insoluble	sil	ica	ate	s.								20.830	
Water and loss												8.054	
												100.000	

## BOYD COUNTY.—(Continued.)

No. 1645—COAL. No. 7. Used at Ashland Furnace.

A bright pure-looking coal, having but little fibrous coal between its laminæ; has some little bright pyrites and thin scales of lime sulphate in the seams.

COMPOSITION, AIR-DRIED.—SPECIFIC GRAVITY = 1.291.	
Hygroscopic moisture 4.80 Volatile combustible matters	39.00 54.90
	00.00

A very good and pure coal, which favorably compares with the best so-called "Block coal" of Indiana, and is well adapted to the purpose for which it is used.

## CARTER COUNTY.—(Continued.)

No. 1646—Coal. No. 1. "From Graham bank. Little Fork of Little Sandy river. Collected by P. N. Moore."

A pure-looking coal, which has some fibrous coal between its laminæ; but shows very little pyrites.

No. 1647—COAL. No. 1. "From Graham bank, &c. Sample from all parts of the mine."

### COMPOSITION OF THESE CARTER COUNTY COALS, AIR-DRIED.

	No. 1646.	No. 1647.
Specific gravity	1.269	not deter'd.
Hygroscopic moisture	3.50 36.30 60.20	3.60 35.40 61.00
Total	100.00	100.00
Total volatile matters	39.80 57.30 2.90	39.00 57.60 3.40
Total	100.00	100.00
Character of the coke	Spongy.	Spongy.
Color of the ash	Brownish- grey.	Brownish- grey.
Per centage of sulphur	1.148	1.107

Remarkably good and pure coals.

# GREENUP COUNTY .- (Continued.)

No. 1648—Coal. No. 1. "Raccoon Creek. Raccoon Furnace. Collected by P. N. Moore."

A splint coal, with quite thin laminæ and considerable fibrous coal between. Some little iron stain, but little appearance of pyrites.

No. 1649—COAL. "Hunnewell cannel coal. Hunnewell mines."

	No. 1648.	No. 1649.
Specific gravity	. 1.409	1.306
Hygroscopic moisture	. 4.10 . 28.90 . 67.00	1.50 52.20 46.30
Total	. 100.00	100.00
Total volatile matters	. 33.00 . 49.60 . 17.40	53.70 40.60 5.70
Total	. 100.00	100.00
Character of the coke	. Pulverulent	Very friable
Color of the ash	Light-grey, nearly white	Light yellowish- grey.
Per centage of sulphur	. 0.655	0.782

This cannel coal is remarkably pure and good. Its proportion of volatile combustible matters (52.20 per cent.) is remarkably great.

# оню соинту.—(Continued.)

No. 1650—Coal (D.) "From Taylor coal mines, near Beaver Dam, Ohio county. Collected by C. J. Norwood. (Rather better than a fair average.")

A bright-looking coal, with but little fibrous coal between the laminæ, but with some scales of bright pyrites.

No. 1651—Coal (D.) "Stevens' coal mine, near Beaver Dam, &c. Collected by C. J. Norwood."

Has more fibrous coal than the preceding, but shows less pyrites. Iridescent in parts.

# COMPOSITION, AIR-DRIED.

	No. 1650.	No. 1651.
Specific gravity	1.315	1.316
Hygroscopic moisture	3.30 35.84 60.86	3.30 36.76 59.94
Total	100.00	100.00
Total volatile matters	39.14 54.36 6.50	40.06 52.60 7·34
Character of the coke		Spongy.
Color of the ash	Chocolate- grey.	Brownish- grey.
Per centage of sulphur	3.874	2.608

These are both very good coals; ranking amongst the best.

1
_
0
2120
=
Y
•
5
_
DRIED
(=)
-
2
-
200
٠.
U,
_
=
Ç
SUB-SOILS.
~
-
7
J.
U,
-
=
0
SOHES
-
-
BLE
-
×

Sand and silicates.	88.8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	\$3.500. Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  Water lost at 3800.  \$3.500. \$3.500.  ### Property in the sili-  ### Property in t	\$8.3.765, 1.335 and sailicates.  Sand and silicates.  Water lost at 3800.  Sand and silicates.  Sand and silicates
Sand and silicates.	8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	Signature (Signature (	88.3.765 1.23 2.35 and and silicates.  Sand and silicates.  Water lost at 3800.  Water lost a
		Hygroscopic moist-  1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.	Hygroscopic moist-  1. 1. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2.

L'ounitary)	Communication of the communica
3	2
otto cotto	Ú
:	=
ć	Ö
U	ŗ.
P	٩
÷	2
U	n
,	i
ĭ	Š
01100	=
۶	ļ
٦	•
	•
•	
٢	ď
*	
11.11	5

Remarks.	Virgin soil sub-soil (on sandstone).  Virgin soil sub-soil (on limestone).  Virgin soil sub-soil on limestone).  Old field ton limestone).  New soil (coaled land), Fea Ridge. Sub-soil of same.  Old field (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same   Sub-soil of same.  Old field.  Sub-soil of same.  Old field (on limestone).  Sub-soil of same (on limestone).  Sub-soil of same (on limestone).  Sub-soil of same (on limestone).  Old field (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same (on limestone).  Virgin soil (on limestone).  Sub-soil of same (on limestone).
Extracted from 1000 parts by carbonic acid water.	
S sda in the silicates.	
Potash in the sili- cates.	2. 70
Hygroscopic moist- ure.	[
Water lost at 3800.	28.00 28.00
Sand and silicates.	\$\times \circ \cir
Soda.	4 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Potash.	25.00 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Sulphuric acid.	1125 not est 1125
Phosphoric acid.	100 00 00 00 00 00 00 00 00 00 00 00 00
Magnesia.	100 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Lime carbonate.	1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Manganese oxide.	
lron oxide.	24.6.6.4.6.6.6.6.6.6.6.6.6.6.6.6.6.6.6.6
.snimuiA	
Organic and volatile matters.	8 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
County.	Grayson. Hardin.
Number in Report.	71.25.66.66.66.66.66.66.66.66.66.66.66.66.66

. 1°	637 Ohio 3.550 637 Ohio 3.350 6. rs St. of California 7.740  • Total alkalies separated by fusion.	3.350 3.350 7.740	7.047 4.066 6.475 11.117		8. 8. 8. 8. 8. 8. 8. 8. 8. 8. 8. 8. 8. 8	1. 596	258 .093 not est .273  0.144  88.841 .915 .104 .124 not est .333  .012 91.990 .775 .171 .140 not est .269  .230 89.517 .775 1.596 .093  0.082  .727  .983  74.070  2.	st 333 st 333 st 727 st with alk	. 139 8 . 230 8 . 230 8 . 983 7	89.517 74.070	9.15 2.400 .775 1.450 .775 2.575 2.803				Sub-soil of same (on sandstone). Old field (on sandstone). Sub-soil of same (on sandstone). Adobe soil, Sacramento Valley.
					TAI	BLE	II. LIN	LIMESTONES, &c., DRIED	NES,	kc., D	RIED A	AT 212°	٠. ب		
Number in report.	County.	Specific gravity.	Lime carbonate.	Magnesia carbonate.	-saimulA	Iron oxide.	Phosphoric acid.	Sulphuric acid.	Potash.	Soda	Silica and silicates.	Per centage of lime.	Per centage of phos- phorus.	Per centage of sul- phur.	Remarks,
1313 1334 1334 1423 1423 1423 1423 1423	Butler Carter Carter Carter Carter Carter Edmonson Edmonson Edmonson Edmonson Edmonson Edmonson Edmonson Carter Ca	not det. 2.634 2.700 2.678 2.678 2.678 2.680 2.680 2.700 2.680	93.020 93.020 97.720 95.150 77.750 90.050 90	2.088 2.29r 100 est. 245 575 575 6.24r 401 7707 385 220 220 220 220 220 220 220 220 220 22	0.917 0.3000 0.3000 0.0000 0.	9977 3388 443 443 555 565 686 686 686 686 686 686 686 686	6.000 6.000	0.64 0.533 0.04 1.09 0.044	113 00 01 01 01 01 01 01 01 01 01 01 01 01	0.384 0.387 1.68 1.88 1.586 1.58	6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	52.091 52.1091 53.1092 53.1092 53.1092 54.101 54.10	0.100	0.242 0.242 not est. 310 310 104 077 017 017 not est.	S. C., Barren river, Airdrie Furnace. Lower Silurian. Boone Furnace (flux). Iron Hills Furnace (flux). Mt. Savage Furnace (flux). Mt. Savage Furnace (flux). Oblitic, sub-carboniferous. Sub-carboniferous, upper part. Sub-carboniferous, inhographle. Ouicklime (Lower Silurian). Impure calc. spar (Lower Silurian). Pen Ridge (ferruginous). Used as flux, Raccoon Furnace. Used as flux, Raccoon Furnace. Blue argillaceous (Lower Silurian). Quicklime (Star Lime Company). Cane Ridge Ilmestone.

TABLE III (A). IRON ORES (LIMONITES), DRIED AT 212° F.

Remarks.	Old Slate Furnace. Slate ore, Cane Creek. Slate ore, Cane Creek. Slate ore, Cane Creek. State furnace yellow kidney. Bellefout Furnace yellow kidney. Buena Vista Furnace, Straight Creek. Star Furnace black kidney. J. E. Taylor's (L. Reedy). Star Furnace black kidney. J. E. Taylor's (L. Reedy). Star Furnace black kidney. Main Block, Lambert. Main Block, Lambert. Smith Hill Crerman. Smith Hill Creek. Gravin's Hill Block. Graver Block tused farm. Frederick's bank. Rock Creek. Limestone ore, Tygert Creek. Limestone ore, Shover drift. Limestone ore, Shover drift. Limestone ore, Shover drift. Limestone ore, Powder-mill Hollow. Lower Block, J. Thompson's.
Per cent of silica.	0.011 6.160 0.86 29.56 0.85 19.98 0.55 19.98 0.55 11.650 0.95 11.650 0.95 11.650 0.95 12.250 0.95 27.35 0.95 27.35 0
Per cent. of sulphur.	n n n n n n n n n n n n n n n n n n n
Per cent. of phos-	ŏ · · · · · · · · · · · · · · · · · · ·
Per cent. of iron.	53. 354 41.3.73 41.3.73 41.3.73 41.3.73 41.3.73 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 43.4.13 45.8.85 45.865 45.865 46.865 46.865 46.865 47.86
Moisture and loss.	
Silica and silicates.	12.300 8 18. 10.156 31.294 10.156 31.394 10.156 31.394 10.156 31.394 10.156 31.394 11.280 2.600 11.280 2.600 11.280 2.600 11.280 2.600 11.280 2.600 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.380 2.500 11.50 31.35 31. 11.50 31.55 31. 11.50 31.50 31.
Water (combined).	0.090 12.300 8 18.2 227 10.156 21.21 0.89 8.77 15.720 0.94 11.220 21.480 0.95 10.439 19.080 1.38 7.924 41.80 1.38 7.924 41.80 1.38 7.924 41.80 1.38 7.924 41.80 1.38 7.924 41.80 1.28 7.924 41.70 1.79 9.504 44.70 1.71 10.704 71.840 1.71 10.704 71.840 1.71 10.704 71.840 1.71 10.704 71.840 1.71 10.704 71.81 1.71 10.704 71.81 1.72 10.800 12.65 1.73 11.73 11.65 1.73 11.73 11.65 1.74 11.73 11.65 1.75 11.73 11.55 1.75 11.73 11.73 1.75 11.73 1
Sulphuric acid.	0 00 00 00 00 00 00 00 00 00 00 00 00 0
Phosphoric acid.	
blagnesia.	2.29 2.275 2.275 2.275 2.29 2.345 2.345 2.345 2.345 2.345 2.345 2.345 2.345 2.345 2.345 3.441 3.44
Гіте сагропасе.	0.430 0.130 3.58 a trace 3.58 a trace 3.54 0.130 4.22 0.380 a trace a
Manganese brown oxide.	392 0.430 334 338 353 4 174cc 394 4 20 394 4 20 394 4 20 395 21 14cc 395 31 14
Alumina.	# 4 1 4 4 1 4 2 4 W 1 4 4 N 4 W 2 4 1 0 W 2 4 1 4 4 1 0 0 U 4 1 U 1 U 1 U 1 U 1 U 1 U 1 U 1 U 1 U
Ігов сагровате.	8.821 8.831 19.435 17.756
Iron peroxide.	58. 56.77 58. 56.77 58. 56.77 58. 56.77 58. 56.77 58. 56.77 58. 56.77 58. 56.77 58. 56.77 59. 57 59.
County.	Bath Bath Boyd Boyd Boyd Boyd Boyd Boyd Boyd Boyd
Number in report.	25.00

	-				And carbonic acid.	nd carbo	_ ``			Line		• Carbonates.	10
Near Noin Furnace, Brownsville road,	ot est 14.360	. 412 no	. 921 not est 12. 180 21. 23. not est 19. 138	80 21. 23 Jn	1.065 not est 12.38-51.23	1.065		2002.	ÈÈ	5.5	7.340	_	999
Roasted ore, Airdrie Furnace.			41.867	29.88	500.			72. 12.263	- ~	2.972	0 810	Muhlenburg	8 8
Martin ore.			. 598 48.822	.21611.25012.730	. 216 11.3		0.021	200		2.930		Minhenhing	8
From J. M. Hope's land. Average sample.	.024 12.860	820.	175 12.800	5 133.530	050		_	20.1		7.07	. 195	Muhlenburg	8
From 1. M. Hope's land, upper part.	07:12		185 44 35	13: 12: 43: 17: 25:		+ 7	7	-	6	62.5	3 048	Muhlenburg	9
Any line Furne, from Mountain bank. Av ge sample.	200.61	Ŧ.	18.57	5 20.50	=	•	a trace	*i - 104	.1.	a trace	76. 6y		000
Suwannee Furnace, railroad cut.	.083 21.160	. 189	46.819			·	co a trace	00.		90	66.117	Lyon	250
Suwannee Furnace, bank near furnace.	.045 18. 16.	.120	.000 40.36;	113 9.850 18.910	3.0	.275					59.37	Lyon	1597
Suwannee Furnace (Big Showing).	212 26 8 30		141.550	8 40.00 000	000		•	3	5. 402 4 11400		50.850	sur	1580
Ochrous near St. Charles' mine.	.341 20.000	9	. 652 9. 500 25. 930 1. 002 42. 144	20025.930	.625	101.	.381		1.044 a trace	-	60.20 not est	:	1530
Limestone ore (slate ore).	.042 18.80	.025	40.385	0.125.450	.105 10.3	.057		.150	17	-	57.55t not es	:	1520
	.049 35.960	190.	.215 31.413	So 39 o80	8.6 Ezr.	.166		66.	83 . 20		44. 876 not est	Greenup	200
	ogt . tt uta.	<u>8</u>	.810 25.889	3046.760	.116 8.3	.367			80	5. 508	6 oBe not e		200
Kidney Block, McAllister Point.		.075	45.204	50 21.230	. 151 11.2	.172	.820	00	st 1.360	St nor	64 car not est not est		25.5
Rough ore, Clay Lick Creek.		not est no	. 29.792	st not est .	col not est not est not est not est	not est	not est	st not es	St not o	of the second	27. 984 not est not est not est not est not	Creenup	1524
Kidney ore, Osenton bank.		not est inc	47.589	st not est	est not est not est not est not est	notest	not ex	So Jours	1000		So. of morest not set not est not est not	:	1523
Main Block, Brushy Knob bank.		not est inc	130.7881	st not est	est not est not est not est not est	not es:	not ex	TO TOT IS	2000	+	So. 279 11. 392 4. / Og a trace		1533
Kidney ore, Buffalo Farm.	104 15.260	362		260 0.17316.030	2000	200	,,,,	200	000	3.700	08.030	:	1521
Solis Sol Main Block T. Morton hank	000000000000000000000000000000000000000		23.507	57 in 240	157 5.4	. 537	F	33		4.0	13.39614.972 4.077	Greenup	53
Main Block (calcareous).	070113. 530	727	22. 507	lose Aries	100	222	•						

	1
f+:	
_	
°,	
2	
5	1
~	
0	
$\Xi$	
2	
2	
$\widehat{\mathbf{s}}$	ĺ
H	
Ž	
2	
S	
÷	
ä	
~	
-	
>	
Ķ	
H	
೭	
IRON ORES (CLAY IRON-STONES), DRIED AT 212° F.	
M	
×	
0	
Z	
0	
8	
_	
٠	
m	
_	
=	
H	
E	
크	
9	
TABLE III (B).	

Remarks.	J. P. Jones' drift.  Wilson Creek Blue Block, Star Furnace. Williams' Creek limestone ore, Star Furnace. John Hudson's. Knob Lack. Ferruginous limestone. Old Orchard diggings. Old Orchard diggings. Horsley bank. Horsley bank. Tygert Creek. Sinking Creek. Foxden ore. Mt. Savage Furnace. Mt. Savage Furnace. Mt. Savage Furnace. Lawer Block, Alcorn Creek. Hue Kidney, Kenton Furnace. Conglomerate ore, Buffalo Furnace. Lower Block, Ananda Furnace. Lower Block, Ananda Furnace. Main Block, Ananda Furnace. Conglomerate ore, Buffalo Furnace. Main Block ore grey ore, Laurel Furnace. Conglomerate ore, Womed's bank. Main Block ore grey ore, Laurel Furnace. Crey ore, Raccoon Furnace. Slate Iron ore, Blockner Furnace.
Per cent. of silica.	205 115.5 152 25.20 153 42.76 154 42.76 205 met est 205 met est
Per cent. of sulphur.	٠ . ٠ .
Per cent. of phos-	
Per cent. of iron.	5.305 24.59.1 3.935 24.59.1 3.937 27.041 4.047 22.99.9 1.955 40.57.5 5.307 37.57.5 5.307 37.57.5 5.307 37.57.6 6.005 31.59.5 95.19.11.5 95.19.11.5 785 33.06.2 4.777 29.685 4.777 29.685 4.777 20.075 5.627 30.975 7.65 36.10.3 8.785 40.11.8 8.785 40.11.9 6.005 31.62.0 7.65 30.00.0 7.65 30.00
Water and loss.	트 ^^ 10일 : 사용하는 하는 하는 사용하는 사용하는 10일 하는 10
Silica and silicates.	2.377 0.267 19.730 2.779 385 18.360 2.77 157 24.030 467 381 28.440 972 473 44.43 113 meterizi 260 114 7.40 21.100 115 1.251 10.20 116 2.31 10.20 117 1.251 10.20 118 2.420 119 2.51 10.20 119 2.51 10.20 119 2.51 10.20 119 1.51 20.23 119 1.50 2.35 119 1.50 2.
Sulphuric acid.	0.2671 .8551 .3571 .473 .473 .12851 .12851 .12851 .12851 .12851 .12851 .13851
Phosphoric acid.	
Manganese carbon- ate.	691 0.455 080 .572 1800 .573 1800 .573 1800 .573 1800 .573 1800 .573 1800 .793
Magnesia carbonate.	045 0445 404 6 FOW H4 FARE
Lime carbonate.	ମିନ୍ଦିନ୍ଦ୍ୟିକ , ଏହମ୍ମିନିଏ ଓ କୁଲ୍ଲ ନ୍ର୍ୟିକ୍ର ଓ ମୁ
.saimulA	11.968 1.106.
Iron peroxide.	32. 285 12. 784 96. 822. 1. 276 96. 822. 1. 276 29. 914 17. 915 21. 581 17. 915 22. 583 17. 315 24. 405 91. 624 91. 62. 316 47. 391 9. 734 47. 814 9. 654 47. 814 9. 654
lron carbonate.	3.362 68 54 3.362 68 854 2.879 914 17 2.99 17 17 20 18 2.581 17 20 18 2.59 21 17 20 18 2.59 21 17 20 18 2.59 21 17 20 18 2.59 21 20 18 2.50 21 20 20 20 20 20 20 20 20 20 20 20 20 20
Specific gravity.	3.362.66 3.362.66 2.879.24 2.879.24 2.879.24 2.70.00 2.70.00 3.280.54 3.297.74
County.	Boyd Boyd Boyd Boyd Boyd Butler Carter Bull
Number in Report.	4 4 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2

TABLE IV. COALS, AIR-DRIED.

Reniarks.	Buena Vista Furnace (coal 7), Straight Creek. Reliebant Furnace coal 6, Turkey-pen Hollow. Bellebant Furnace coal 6, Turkey-pen Hollow. Bellebant Furnace coal 6. Selected sample. Chadwick Creek (coal, No. 7). Buena Vista Furnace, Straight Creek (coal 5). Rey's Creek coal. Rey's Creek coal. Rey's Creek coal. Rey's Conpany, mine 4, Coalton (No. 7). Ashland Company, Dry Branch (No. 7). Ashland Company, Dry Branch (No. 7). Ashland Company, Trace Creek (No. 7). Ashland Company, Trace Creek (No. 7). Ashland Company, Trace Creek (No. 7). Ashland Company, Sub-conformerate f). Stevens, coal, Bast Creek. W. A. Batt's coal, Little Sandy (No. 7). Nr. Bryan's bank (No. 7, upper layer). Star Furnace (coal, No. 7, upper layer). Star Furnace (coal, No. 7, upper layer). Star Furnace (coal, No. 7, upper layer). Mr. Savige property (coal, No. 7, upper part). W. Pitchard's bank. Mr. Savige property (coal, No. 7, upper part). W. Pitchard's bank. Mr. Savige property (coal, No. 7, upper part). Mr. Savige property (coal,
Per centage of sul- phur.	4.55 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5 4.5
Color of the ash.	Light blac grey Light purple-grey Light purple-grey Lillac grey Light blac grey Light blac grey Lillac grey Light brown grey Dove cel sred Brownish blac grey Nearly white Lillac-grey
Character of the coke.	Dense. Dense. Dense. Dense. Spangy Spangy Spangy Spongy Dense porous Spongy Dense spongy Dense spongy Calhular Spongy Spongy Dense spongy Dense spongy Dense spongy Dense spongy Dense spongy Spongy Spongy Dense spongy Dense spongy Dense spongy Spongy Spongy Spongy Dense spongy Spongy Spongy Dense spongy
Ashes,	8 8 8 8 8 9 4 8 9 8 9 8 5 4 4 5 5 5 5 6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
Carlson in the coke.	\$\frac{1}{2}\$\frac
Total volatile mat-	\$ \dagger \text{3 \text{9 \text{in } i
Coke.	\$
Volatile combustible matters.	\$\frac{1}{2} \frac{1}{2} \frac
Hygroscopic moist- ure.	Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q
Specific gravity.	1, 328 1, 328 1, 338 1, 340 1,
County.	Boyd
Number in Report.	1279 12804 12804 1281 1282 1283 1288 1288 1288 1288 1288

-	To all lines	
•	ŧ	
	ď,	į
	=	;
	2	
	=	
	5	
1	ς	
ζ	_	,
-	-	
	1	
	'	
1	_	
ř		•
•		
1		
٠	í	١
9		
-	×	
	-	۱
4		
	-	
٠	•	
٠	-	
•	7	
1	7	١
i	ī	
•	_	
-		•
:	>	•
٠	>	
	8	
ŀ	•	
	_	
2		
-		
:	-	,
E	٠	۱
-7		

Remarks.	Tar Lick Coal, Dismal Creek. Gravelly Lick, Miller's Fork of Bear Creek. Brushy branch of Calloway Creek.			2 - -	رر	33	Alcorn Cre			Coal, No. 6, Hunnewell Furnace.		S	F. Swetman's bank (Coal, No. 1), Brushy Creek.	Coal, No. 1, Hopps, Mill, Cane's Creek. Coal, No. 3, Holbrook's coal, Brushy Creek.	3		Sub-coglomerate, on Ledford's land. Bituminous shale above S. C. limestone.	Coke, from No. 12 coal (sixteen )		Paradise mine (Airdric), coal 11, lower division.	Paradise mine (Airdrie), middle layer.	
Per centage of sul-	3.563	6 - 5 - 5 - 5 - 5 - 5 - 5 - 5	2.892	1.400	5.934	3.647	2.507	0.740	3.5	5.263	4.213	2 759	.736	2.109	3.785	. 997	4.092	oto.	1.438	4.573	3.158	2.727
Color of the ash.	Light brownish grey . Brownish grey	Lilac-grey . Light chocolate	Nearly white Brownish salmon grey	Chocolate	Lilac grey	Dark lilac-grey Dark lilac-grey	Lilac-grey	Lilac grey	Light lilac-grey	Grey-purple	Dark brownish purple	Light filac-grey	Light grey-buff	Vellowish-white	Grey-purple	Light brownish-grey		owish-grey .	Lilac-grey	Dark lilac grey	Light lilac-grey	Brownish salmon-grey Light lilac-grey
Character of the coke.	Spongy Dense spongy Light friable	Light spongy Light spongy	Friable	Frable Light spongy	Dense.	Spangy	Friable Sponey	Spongy	Dense	Spingy	Spongy	Light spangy	Light spongy	Priable	Light spongy	Dense	Dense		Dense spongy	Sp.mgy	Spongy	Dense spongy Light spongy
Ashes.	15.7	: : : : : : : : : : : : : : : : : : :	26.6 + 6	5.0	3.5	0.5	12.6	9	÷ 5	9 6 2 2	7.5	20.0	2	5.0	7.5	7.4	14,00	· ÷	50	2	9 9	2.3
Carbon in the coke.	6.5 % 2.8 %	÷ = 3	4.5	55 to	54.55	51.31	52.33	, .0 .	\$ <del>5</del>	51.4	47.50	24.0	2.50	\$ 0.05 42.05	31.14	7.05	50.24		10 30 10 30 10 30	, .,	3 5	3. 6 3. 8
Total volatile mat-	# # # # # # # # # # # # # # # # # # #	5655	1000		₹.	25	_	_	5 .0 2 .5 		3 = 3	_	2 20	7 S		\$ 5° ₹	76.7	_	35.0	_	3.5	<del>.</del>
Coke.	32.2	533	3.3	33	2. S.	62.5	3 8	3.		7.50	32. 2	÷ :	S.S.	7. s 5 2 3	.53.	λ : γ <u>:</u>	5.5	33	5.6	3	5.6	28.
Volatine combustible	# 15 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	502 - 190)	r v À	9.5	# 35 # 35 # 35	÷ ;	-	-	ţż	35.6	, E.	-	9.4	5.5	, S.	: 3 8:3	3.45	+	1.10	1	35.95	2 5
Hygroscopic moist-	4+4	m no	++	4 4	Ž 20	40	E 4	m	+ +	÷ ~	٠	n ÷ .	+ 40	÷ ÷	in n	N 0	0 0	7	m •	4 4	- · č	m ÷
Specific gravity.	1.3%	65	1.512	1.316	1.450	1.374	75.8	1.20	1. 315	1.305	1.355	. 32.	1.28	1.37	1.35	1.284	lot of	not es	1.27	3.5	1.320	1.221
County.	Grayson Grayson	Grayson.	Grayson	Greenup	Greenup Greenup	Greenup	Greenup	Greenup	Greenup	Greenup	Greenup	Hopkins	Lawrence	Lawrence	Lawrence	Menifee	Menifee	Muhlenburg	Muhlenburg	Muhlenburg	Muhlenburg	Muhlenburg
Number in Report.	# £ 5 3	1451	1454	79.59 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.0	1480	1488 198 199	1495	1492	6 6 7 7	1495	1457	1579	1589	2651	1592	63	1603	1617	1618	1640	1622	1623

Mercer coal mines.  Muhlenburg coal mines, upper seam.  Muhlenburg coal mines, main working bed.  Muhlenburg coal mines, average head of main entry.  Kibrous coal or mineral charcoal.  Carbonaceous mud.  Rockport coal mines, average sample along entry.  Rockport coal mines, general average of mine.  Rockport coal mines, general average of mine.  Star Furnace coal, Jackson county, Ohio.  Hocking Valley oad, average sample whole bed.  Hocking Valley, average of iupper twenty-eight inches.  Hocking Valley, average of lower eighteen inches.  Big Muddy coal, Jackson county, Illinois.  Indiana Block coal, near Brazil, Clay county.  Indiana Block coal, lower seam.  Coal, No. 7, Graham bank.  Coal, No. 1, Raccoon Creek.  Coal, No. 1, Baccoon Creek.  Coal, D. Taylor's coal mines.	
24.74.24.24.24.24.24.24.24.24.24.24.24.24.24	
Lilac-grey Lilac-grey Lilac-grey Lilac-grey Light brownish-grey Light brownish-grey Light lilac-grey Light lilac-grey	\$See 1650.
<u> </u>	Se
90.66 11.80 Light spongy	
8 30 2 2 3 2 4 2 2 3 3 4 2 2 3 3 4 2 2 3 3 3 4 2 3 3 3 4 2 3 3 3 3	1648.
5.51 m at 20	‡See 1648
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	
\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	
# 6 6 4 4 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	940
8 1 2 8 8 5 8 8 3 4 9 4 5 4 7 4 4 9 4 4 9 4 9 5 5 8 9 5 5 8 9 9 5 5 8 9 9 9 9 9 9 9	1 Sec 1646
1.388 1.333 1.334 1.334 1.334 1.335	_
Muhlenburg	• See 1645.
1628 1628 1629 1632 1632 1632 1632 1632 1632 1632 1632	• See

TABLE V (A). MARLY SHALES, MARLES, SILICIOUS CONCRETIONS, &c., DRIED AT 212° F.

Remarks	Marly shale, near Clinton Furnace, Silicious mudstone. Silicious mudstone. Marl under clay (feruginous). Marly shale, Cincinnati Group. Marl mudstone). Clay shale, Newport Reservoir. Clay shale, Newport Reservoir. Clay, brick clay. Saudy, feruginous clay. Ferruginous clay. Sand, moulding sand.	Marly shale, Cincinnati Group. Marly shale, Cincinnati Group. Sandy sub-soil, Little Sandy river. Green marly shale. Marly shale (mineral paint). Marly shale (mineral paint).	Silicious clay (indurated). Soft sandstone or silicious concretion. Soft sandstone or silicious concretion. Soft sandstone or silicious concretion. Pest Tertury clay, Grand Chain. Marly shale, Sunset Lick.	Same, analyzed by fusion. Soft sandstone, Horse Branch.	Marl (cut of Cumberland & Ohio Rallr'd, Eminence). Silicious grit. Silicious grit. Marly clay, Cincinnati Group, Lower Silurian. Brick clay. Marly shale, Cincinnati Group. Marly shale, Cincinnati Group.
Water, &cc.	3.833 3.445 3.455	4.85. 3.83. 3.83. 3.84. 5.67. 5.67.	5.85 3.00 1.00 5.15 6.25 6.25 6.25 6.25 6.25 6.25 6.25 6.2	3.00.1	
Total soda.	6.93 1.5.13 1.6. 1.6. 1.6. 1.5.5. 1.5	. 587 . 587 . 587 . 733 . 733	1 2 8 1 8 3	.78.	. 52. . 76. . 90. . 915.
Total potash.	3.989 2.735 .032 3.54 1.329 3.045 4.124 1.324 2.698 2.698 0.756	3.298 4.471 3.366 8.479 7.130 5.404.3	23. 23. 23. 23. 23. 23. 23. 23.	4.625	2.100 .825 .847 2.538 2.139 2.447
*.ebo2	80			: 0	: :::::
*.desioq	1.387	3.565	2.9te		: ::::::
Sulphuric acid.	217	.233 .233 .738 .738 .570 .570	.501 727 727 729 1.188 720	. 2049	164 .961 639 not est 166 not est 166 not est 667 not est 667 not est 128 not est
Phosph'ic acid.	217 .079 .486 a trace .230 .001 .345 and est .25 and est .25 and est .102 and est a trace and est and	. 22.3 . 435 . 435 . 217	20. 12.0. 12.0. 12.0. 12.0.	.370	not est not est . 539 not est . 106 not est . 258 not est . 667 not est
Magnesia	0.684	2.298 2.298 930 1.210		1.158	
Magnesia car- bonate.	.920 .345 .1.135 .2.56 .1.135 .2.56 .2.135 .2.135 .2.135 .2.135 .3.24 .3.25 .3		::::::	: :	1 111111
Lime.		8.736 3.066	,	.538	: ::::::
Lime carbonate.	0.480 .500 11.060 13.19 9.800 .660 6.850 atrace .160 .863 .864 .740 .740	7 80, 4.560 1.440	8. 6. 3. 8. 8. 5		65.4. 67.7. 68.88. 86.88.
Iron oxide.		11.500 10.415 15.395 15.395 816 6.997	8.350 7.809 7.809 9.129 9.133	3013.480	7.146/11.040 H. 56 16.500 . 48 15.793 . 65% 29.971 . 76 22.256 1.000 21.000 . 68%
.saimulA	12.643 14.959 20.860 28.050 12.050 29.450 20.450 20.500 12.250 12.250 12.700 3.500	12.269 5. 16.782 11. 10.415 16.816  6. 18.831  9.	"-[	7.040	16.500 15.793 29.971 22.256 21.000 22.850
Silica.	76.060 47.320 68.700 58.080 51.420 72.660 72.660 82.560 57.160 57.160 88.560 88.560	54.160 13.269 15.559 57.260 16.782 11.500 84.000 11.500 10.415 15.395 50.360 16.816 6.997 52.060 18.831 9.200	74.960 81.065 94.060 70.665	60.060	23.700 77.460 56.400 68.360 47.160
Silica and sili- cates.	66.680	77.380	71.560	87.700	
County.	Boyd. Bracken Bracken Campbell	Campbell Campbell Campbell	Fulton Fulton Fulton Fulton Fulton Fulton Grayson Grayson Grayson Grayson Fulton Grayson Fulton Fult	Grayson	581 Kenton
Number in Re- port.	13.03 13.03 13.16 13.16 13.16 13.20 13.20 13.20 13.20 13.20	1336 1336 1336 1431 1431 1431 1431 1431	******	146	1581 1581 1583 1584 1584 1586

TABLE V (B). CLAYS, &c., DRIED AT 212° F.

Remarks.	Fire-clay, Boone Furnace property.  Fire-clay, Boone Furnace property.  Fire-clay, Boone Furnace property.  Fire-clay, Boone Furnace property.  Fire-clay, under twelve inch coal, Geo. Ossenton's.  Clay shale, Grayson.  Porcelain clay, of St. Vriciex.  Porcelain clay, of China.	Stourbridge fire-clay. Crucible clay, of Almerode. Post Tertiary clay, foot of Grand Chain.	Fire-clay, Kenton Furnace, Louder's land. Fire-clay, Kenton Furnace, Powder-mill Hollow. Clay, Pea Ridge, near Hunnewell. Clay, Pea Ridge, near Hunnewell. Clay, Pea Ridge, two and a half feet bed. Clay, Pea Ridge, fourteen inch, thrd bed. Fire-clay, Thomas' bank, Shultz's Creek.	Russ' coal mines, fire-clay, below the coal.
		Carcino, Car		
Water expelled at red heat.	13.030 11.783 11.783 7.756 8.522 8.330 13.133 8.200	1.000 5.219	13.6% 6.8% 6.8% 13.3% 7.3% 10.6%	4.195
Soda.	.283 .341 .679 .584 .728 .515 .213 not ext.	r, goo	# \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	:+52
Potash.	.289 .250 .212 .212 .963 .963 .751 2.093 not est	not e	2.6.1 2.6.1 1.916 1.1.16 1.1.17 1.1.17	2.9.0
Sulphuric acid.	not est. not est. not est. not est. 157 not est. not est.	not est. not est.	not est. not est. not est. not est. not est. a trace.	3 282
Phosphoric acid.	. 255 . 553 . 243 . 147 . 347 . 940 . 127 not est.	not est. not est.	. 626 . 371 . 563 . 563 . 626 . 498 . 358	621.
Magnesia.	a trace. a trace. a trace. a trace. a trace. 229 7, 121 520	not est. 1,000	2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2	. 455
Lime.	. 112 . 145 a trace. a trace. . 145 . 538 #. 300 not est.	Soo.	157 157 1015 1015 1015 1015 1015 1015 10	Eus.
Iron oxide.	a trace. a trace. a trace. a trace. a trace. a trace. not est. not est.	3.000	1.820 1.820 1.720	182
.saimulA	33.471 38.531 38.531 27.246 45.775 24.604 36.920 30.300	34.370 3	35-281 22-735 22-679 36-620 22-092 31-077 40-661	26.281
Sillica.	45.56 54.55 54.55 54.55 56.06 56.06 57.30 57.30	63.400	66.968 66.968 67.788 67	63.180
County.	Carter Carter Carter Carter Carter Carter Carter Carter China	England Germany(?)	Greenup Greenup Greenup Greenup Greenup	Muhlenburg
Number in Report.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(g')	1489 1489 1489 1489 1489	1613

Carbonate.

TABLE VI. PIG IRONS.

Remarks.	Hot blast, No. 1, Bellefont Furnace. Hot blast, No. 1, Buena Vista Furnace. Stone coal, No. 1 mill, Ashland Furnace. Stone-coal, No. 2 mill, Ashland Furnace. Stone-coal, foundry iron, Ashland Furnace. Foundry iron, No. 2, Boone Furnace. Hot blast, No. 1, Brom Hills Furnace. Hot blast, No. 1, Buffalo Furnace. Cold blast, No. 1, Buffalo Furnace. Hot blast, No. 1, Buffalo Furnace. Hot blast, No. 2, Hunnewell Furnace. Hot blast, No. 2, Hunnewell Furnace. Hot blast, No. 2, Hunnewell Furnace. Silver-grey, Airdrie Furnace.
Total carbon.	3.570 2.280 2.
Sulphur.	
Phosphorus.	194 385 385 385 395 395 461 836 669 669 669 684 684 1029 11029
Sodium.	. 047 . 032 . 047 . 032 . 041 . 010 . 048 . 041 . 048 . 041 . 048 . 041 . 048 . 041 . 048 . 041 . 048 . 041 . 048 . 041 . 048 . 041 . 056 a trace . 104 . 004 . 056 a trace . 104 . 004 . 056 a trace . 104 . 004
Potassium.	1.095 . 047 . 032 . 040
Magnesium,	644 104 (995 (947 ) 032   684 104 (995 (963 ) 001 ) 684 105 (395 (963 ) 001 ) 684 105 (395 (963 ) 001 ) 684 105 (395 (963 ) 001 ) 684 105 (305 ) 005   684 105 (305 ) 005 (305 ) 685 (305 ) 005 (305 )
Calcium.	104 1045 1045 1045 1045 1045 1045 1045 1
-munimulA	389 1.160 1.93 1.14 1.095 0.047 0.92 540 600 1.054 1.10 1.095 0.063 0.010 540 1.120 1.00 1.15 1.33 1.00 1.00 1.00 1.00 1.00 1.00 1.00
-Sel2	1.166 649 546 770 1.120 1.120 6.83 6.83 6.83 6.83 6.83 6.83 6.83 6.83
Silicon.	0 - MICO 11 - N - + D 11 M N D D D D
Manganese.	.054 .256 .236 .236 .050 .050 .050 .050 .050 .050 .050 .05
Combined carbon.	.220 .210 .110 .740 .740 .740 .630 .630 .750 .630 .750 .750 .750 .750 .750
Graphite.	3. 1. 4. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6.
Iron.	293.208 293.208 39.208 39.208 39.731 39.505 39.731 39.735
Specific gravity.	7.132 93.208 7.132 93.208 7.137 91.4712 6.4019.3712 6.50190.893 6.42190.958 6.9019.323 7.0119.305 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82591.656 6.82686.8558 7.04192.368 6.82686.8558 7.775286.86586 7.775286.86596
County.	Boyd. Boyd. Boyd. Boyd. Boyd. Carter.
Number in Report.	1293 1796 1796 1796 1797 1797 1797 1797 1797