

THE CONTINENTAL CO.

225 West Market Street

Jackson 2167

Louisville 2, Kentucky

Jackson 2168

MAJOR APPLIANCES

December 28, 1945

PLASTICS

The Inland Steel Corp.
Wheelwright, Ky.

Gentlemen:

Thank you for your Purchase Order #28354. We are pleased to hear of your interest in our product.

The full directions for application are printed on each can and are shown in our literature but, so that you may have these directions on hand in your files, I shall give them to you in this letter.

The methods and characteristics of application of R-MIR-DEK are as follows:

1. Can be applied to metal, wood, or concrete surfaces which are painted or unpainted.
2. Applied with either spray or trowel.
 - a. Thin 1 gallon R-MIR-DEK with one-half pint of R-MIR-DEK Extender to spray both coats.
 - b. For troweling, thin same as above to apply first coat and use as received for second coat.
3. Application Procedure:
 - a. Clean surface free from grease and dirt with Primary-Extender, using clean cloth or brush. Wipe off with clean dry cloth and allow to dry - about 15 to 20 minutes requires.
 - b. Apply first coat of R-MIR-DEK in a very thin layer and allow to dry, about two to four hours.
 - c. Apply second coat to a total uniform depth of 0.025 plus or minus 0.005 inches. Allow to dry completely, about 6 hours will be required.

*J.D.B.
11/21/46
Mahan*